Model 21

**Vishay Spectrol** 

Www.vishay.com

### 46.02 mm Diameter 15 Turn Dial




QUICK REFERENCE DATA	
Sensor type	DIALS
Market appliance	Industrial
Dimensions	46 mm dia.

MECHANICAL SPECIFICATIONS	
PARAMETER	
Mounting	Direct to shaft with # 4 to 40 hex socket set screw located adjacent to no. 75 on graduated dial
Numeral size: Counter wheel: Graduated dial:	0.90" H x 0.013" W (2.29 cm x 0.33 cm) 0.109" x 0.018" (2.77 cm x 0.46 cm)
Graduation size: Numeral and every Fifth Intermediate Width	0.55" L (1.40 cm) 0.035" L (0.89 cm) 0.012" (0.30 cm)
Weight	3.0 max. (85.05)

#### FEATURES

- Round vernier scale
- 1 <sup>13</sup>/<sub>16</sub>" dia.
- $1/_4$ " or  $1/_8$ " or 6 mm metric bore shaft adapter
- Satin chrome finish with black markings
- Black chrome finish with white markings
- Brushed chrome finish with black markings
- Material categorization: For definitions of compliance please see <u>www.vishay.com/doc?99912</u>

OPERATIONAL SPECIFICATIONS		
Readout and operation	1499 turns total The number in window (0 thru 14) indicates completed number of turns of the drive sleeve. Graduated circular dial indicates the percent of the partial turn of the drive sleeve	
Transfer point	The number in center of window shall change as graduated dial rotates between 94 and 0	
Rotation	Readout shall increase with clockwise and decrease with counterclockwise rotation	
Accuracy	Zero blacklash between graduated dial and the drive sleeve	



Revision: 05-Jul-12

Document Number: 57088



COMPLIANT



Vishay

# Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and/or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.

# **Material Category Policy**

Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as RoHS-Compliant fulfill the definitions and restrictions defined under Directive 2011/65/EU of The European Parliament and of the Council of June 8, 2011 on the restriction of the use of certain hazardous substances in electrical and electronic equipment (EEE) - recast, unless otherwise specified as non-compliant.

Please note that some Vishay documentation may still make reference to RoHS Directive 2002/95/EC. We confirm that all the products identified as being compliant to Directive 2002/95/EC conform to Directive 2011/65/EU.

Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as Halogen-Free follow Halogen-Free requirements as per JEDEC JS709A standards. Please note that some Vishay documentation may still make reference to the IEC 61249-2-21 definition. We confirm that all the products identified as being compliant to IEC 61249-2-21 conform to JEDEC JS709A standards.

# **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Potentiometer Tools & Hardware category:

Click to view products by Vishay manufacturer:

Other Similar products are found below :

 006-1-1
 006-1-2
 7071
 7071E
 7072E
 FKS-1/4
 A-0709-H
 A-0709-K
 H-38-3
 1220A
 ACCPOTECB303651550
 H-858
 H-37-5
 H 

 38-1
 7074E
 RK14K1240A4S
 HARDWARE
 ACCTRIADB30603
 ACCTR514-4002
 ACCTR512-0022
 H-37-4
 H-38-9

 H-862
 006-1-0
 H-38-2
 H-37-1
 ACCTRITOB308-T000
 ACCPOTECB303653230
 6533
 008T000
 H-117P
 H-1202-1
 H-1202-2
 H-127
 H 

 37-2
 H-38-11
 H-58P
 H-852
 H-853
 H-857
 H-90
 H-91
 H-92-1
 45T3
 H-82
 RS-2
 6533E