

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

PROPOWER LABEL REMOVER

Aerosol

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Cleaners - Heavy duty

## 1.3. Details of the supplier of the safety data sheet

Premier Farnell 150 Armley Road Leeds LS12 2QQ

Tel.: +44 (0) 870 129 8608

#### 1.4. Emergency telephone number

+44 (0) 870 202530

### **SECTION 2: Hazards identification**

## 2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Physical : Aerosols, category 1

Extremely flammable aerosol.

Pressurised container: May burst if heated

Health : Skin irritation, category 2

Causes skin irritation.
Skin sensitization, category 1
May cause an allergic skin reaction.

Specific target organ toxicity - single exposure, category 3

May cause drowsiness or dizziness.

Environment : Hazardous to the aquatic environment, acute category 1

Very toxic to aquatic life with long lasting effects.

Classification according to 67/548/EEC or 1999/45/EC:

Extremely Flammable

Xi : Irritant

N : Dangerous For The Environment

Health : R38: Irritating to skin.

R43: May cause sensitization by skin contact. R67: Vapours may cause drowsiness and dizziness.

Physical : R12: Extremely flammable.

Extremely Flammable

Environment : R50/53: Very toxic to aquatic organisms, may cause long-term adverse effects

in the aquatic environment.

2.2. Label elements

Labelling according to Regulation (EC) No 1272/2008

Product identifier : Contains: Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics,

< 2% aromatics Orange, sweet, extract





Hazard pictogram(s)







Signal word : Danger

Hazard statement(s): : H222 : Extremely flammable aerosol.

H229: Pressurised container: May burst if heated.

H315: Causes skin irritation.

H317: May cause an allergic skin reaction. H336: May cause drowsiness or dizziness.

H410: Very toxic to aquatic life with long lasting effects.

Precautionary statement(s) : P102 : Keep out of reach of children.

P210: Keep away from heat, hot surfaces, sparks, open flames and other

ignition sources. No smoking.

P211: Do not spray on an open flame or other ignition source.

P251: Do not pierce or burn, even after use.

P261 : Avoid breathing dust/fume/gas/mist/vapours/spray. P271 : Use only outdoors or in a well-ventilated area.

P410/412 : Protect from sunlight. Do not expose to temperatures exceeding

50°C/122°F.

P501-2: Dispose of contents/container to an authorised waste collection point.

#### 2.3. Other hazards

None

## **SECTION 3: Composition/information on ingredients**

#### 3.1. Substances

Not applicable.

## 3.2. Mixtures

Hazardous ingredient	CAS-nr.	EC-nr	w/w %	Symbol	R-phrases*	Notes
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics	64742-48-9	919-857-5	30-60	Xn	10-65-66- 67	В
Hydrocarbons,C3-4-rich, petroleum distillate Petroleumgas (1,3-butadiene < 0.1%)	68512-91-4	270-990-9	10-30	F+	12	K,G
Orange, sweet, extract	8028-48-6	232-433-8	10-30	Xn,N	10-38-43- 50/53-65	

### **Explanation notes**

B: substance with national established workplace exposure limit

G: exempted from the obligation to register in accordance with art.2(7)(a)of REACH Regulation No 1907/2006

K: not classified as carcinogen, less than 0.1% w/w 1,3-butadiene (Einecs-nr. 203-450-8)

Hazardous ingredient	Registration number	CAS- nr.	EC-nr	w/w %	Hazard Class and Category	Hazard statement	Notes
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics	01-2119463258- 33	64742- 48-9	919- 857-5	30-60	Flam. Liq. 3, Asp. Tox. 1, STOT SE 3	H226, H304, H336	В
Hydrocarbons,C3-4-rich, petroleum distillate Petroleumgas (1,3-butadiene < 0.1%)	-	68512- 91-4	270- 990-9	10-30	Press. Gas, Flam. Gas 1	H280, H220	K, G





Hazardous ingredient	Registration number	CAS- nr.	EC-nr	w/w %	Hazard Class and Category	Hazard statement	Notes
Orange, sweet, extract	01-2119493353- 35	8028- 48-6	232- 433-8	10-30	Flam. Liq. 3, Skin Irrit. 2, Skin Sens. 1, Asp. Tox. 1, Aquatic Acute 1, Aquatic Chronic 1	H226, H315, H317, H304, H400, H410	

Explanation notes

B: substance with national established workplace exposure limit

G: exempted from the obligation to register in accordance with art.2(7)(a)of REACH Regulation No 1907/2006

K: not classified as carcinogen, less than 0.1% w/w 1,3-butadiene (Einecs-nr. 203-450-8)

(\*Explanation phrases : see chapter 16)

## **SECTION 4: First aid measures**

## 4.1. Description of first aid measures

Contact with eyes : If substance has got into eyes, immediately wash out with plenty of water Seek medical advice

Contact with skin : Remove contaminated clothing immediately and drench affected skin with plenty of water. Then

wash with soap and water Seek medical advice

Inhalation : IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Call a POISON CENTER or doctor/physician if you feel unwell.

Ingestion : If swallowed do not induce vomiting because of risk of aspiration into the lungs.

If aspiration is suspected obtain immediate medical attention

#### 4.2. Most important symptoms and effects, both acute and delayed

Inhalation : Excessive inhalation of solvent vapours may give rise to nausea, headaches and dizziness Ingestion : After vomiting of swallowed product aspiration into lungs is likely. Solvents may induce

chemical pneumonia.

Symptoms: sore throat, abdominal pain, nausea, vomiting

Skin contact : Irritating to skin

May cause sensitisation by skin contact.

Symptoms: redness and pain

Eye contact : May cause irritation. Symptoms : redness and pain

## 4.3. Indication of any immediate medical attention and special treatment needed

General Advice : If you feel unwell, seek medical advice (show the label where possible

If symptoms persist always call a doctor

## **SECTION 5: Firefighting measures**

## 5.1. Extinguishing media

Foam, carbon dioxide or dry agent

## 5.2. Special hazards arising from the substance or mixture

Aerosols may explode if heated above 50°C

Forms hazardous decomposition products CO,CO2

#### 5.3. Advice for firefighters

Keep container(s) exposed to fire cool, by spraying with water

In case of fire, do not breathe fumes





## **SECTION 6: Accidental release measures**

### 6.1. Personal precautions, protective equipment and emergency procedures

Shut off all ignition sources

Ensure adequate ventilation

Wear protective gloves/protective clothing/eye protection/face protection.

#### 6.2. Environmental precautions

Do not allow to enter public sewers and watercourses

#### 6.3. Methods and material for containment and cleaning up

Absorb spillage in suitable inert material

#### 6.4. Reference to other sections

For further information see section 8

## **SECTION 7: Handling and storage**

### 7.1. Precautions for safe handling

Keep away from heat and sources of ignition

Take precautionary measures against static discharges

Equipment should be earthed

Use explosion-proof electrical/ventilating/lighting/.../equipment.

Use only non-sparking tools.

Do not breathe aerosols or vapours.

Ensure adequate ventilation

Do not get in eyes, on skin, or on clothing.

Wear protective gloves/protective clothing/eye protection/face protection.

Contaminated work clothing should not be allowed out of the workplace.

### 7.2. Conditions for safe storage, including any incompatibilities

Pressurized container : protect from sunlight and do not expose to temperatures exceeding 50°C. Keep out of reach of children.

## 7.3. Specific end use(s)

Cleaners - Heavy duty

## **SECTION 8: Exposure controls/personal protection**

## 8.1. Control parameters

Exposure limits:

No information available

## 8.2. Exposure controls

Control procedures : Ensure adequate ventilation

Keep away from heat and sources of ignition

Take precautionary measures against static discharges

Personal protection : Take precautions to avoid contact with skin and eyes when handling the product

Ensure adequate ventilation

Inhalation : In case of insufficient ventilation, wear suitable respiratory equipment

Hands and Skin : Wear suitable protective gloves against chemicals

Recommended gloves : Nitrile

Eyes : Wear safety goggles.

Environmental protection : Avoid release to the environment. Collect spillage.





## **SECTION 9: Physical and chemical properties**

## 9.1. Information on basic physical and chemical properties

(for aerosols data for the product without propellant)

Appearance : physical state : Propane/butane propelled liquid

Colour : Colorless
Odour : Citrus
pH : Not applicable

Boiling point/range : 145°C Flash point : 36°C

Evaporation rate : Not available

 $\begin{array}{lll} \mbox{Explosion limits: upper limit} & : 9.4\% \\ \mbox{Lower limit} & : 0.6\% \\ \end{array}$ 

Vapour pressure : Not available

Relative density : 0.795 g/cm3 (@ 20°C) Solubility in water : Insoluble in water

Auto-ignition : > 200°C
Viscosity : Not available

9.2. Other information

VOC : 703 g/l

## SECTION 10: Stability and reactivity

#### 10.1. Reactivity

No hazardous reactions known if used for its intended purpose

## 10.2. Chemical stability

Stable

### 10.3. Possibility of hazardous reactions

No hazardous reactions known if used for its intended purpose

## 10.4. Conditions to avoid

Avoid overheating

## 10.5. Incompatible materials

Strong oxidising agent

### 10.6. Hazardous decomposition products

CO.CO2

## **SECTION 11: Toxicological information**

## 11.1. Information on toxicological effects

Information on likely routes of exposure:

Inhalation : Inhalation of solvent vapours may give rise to nausea, headaches and dizziness Ingestion : After vomiting of swallowed product aspiration into lungs is likely. Solvents may induce

chemical pneumonia.

Skin contact : May cause sensitisation by skin contact. Irritating to skin

Eye contact : May cause irritation.

Toxicological data:

No information available





## **SECTION 12: Ecological information**

## 12.1. Toxicity

Hazardous to the aquatic environment, acute category 1 Very toxic to aquatic life with long lasting effects.

## Ecotoxicological data:

No information available

#### 12.2. Persistence and degradability

No information available

## 12.3. Bioaccumulative potential

No information available

### 12.4. Mobility in soil

Insoluble in water

### 12.5. Results of PBT and vPvB assessment

No information available

#### 12.6. Other adverse effects

No information available

## **SECTION 13: Disposal considerations**

#### 13.1. Waste treatment methods

Product : This material and its container must be disposed of in a safe way.

Do not discharge into drains or the environment, dispose to an authorised

waste collection point.

National regulations : Disposal should be in accordance with local, state or national legislation

## **SECTION 14: Transport information**

14.1. UN number

UN-number : 1950

14.2. UN proper shipping name

Proper shipping name : AEROSOLS (Orange sweet ext.)

14.3. Transport hazard class(es)

Class : 2.1 ADR/RID - Classification code : 5F

14.4. Packing group

Packing group : Not applicable

14.5. Environmental hazards

ADR/RID - Environmentally

hazardous : Yes

IMDG - Marine pollutant : Marine pollutant

IATA/ICAO - Environmentally

hazardous : Yes

## 14.6. Special precautions for user

ADR/RID - Tunnelcode : (D)
IMDG - Ems : F-D, S-U
IATA/ICAO - PAX : 203
IATA/ICAO - CAO : 203





#### 14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Not applicable.

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

The Safety Data Sheet is compiled according to the current European requirements.

Dir. 2013/10/EU, 2008/47/EC amendment of the aerosol dispenser directive 75/324/EEC.

EU-directive 99/45/EC

Regulation (EC) No 1272/2008 (CLP)

Regulation (EC) No 1907/2006 (REACH)

## 15.2. Chemical safety assessment

No information available

### SECTION 16: Other information

\*Explanation risk-phrases : R10: Flammable.

R12: Extremely flammable. R38: Irritating to skin.

R43: May cause sensitization by skin contact. R65: Harmful: may cause lung damage if swallowed.

R66: Repeated exposure may cause skin dryness or cracking.

R67: Vapours may cause drowsiness and dizziness.

R50/53: Very toxic to aquatic organisms, may cause long-term adverse effects

in the aquatic environment.

\*Explanation hazard statements: H220: Extremely flammable gas.

H226: Flammable liquid and vapour.

H280: Contains gas under pressure; may explode if heated.

H304: May be fatal if swallowed and enters airways.

H315: Causes skin irritation.

H317: May cause an allergic skin reaction. H336: May cause drowsiness or dizziness.

H400: Very toxic to aquatic life.

H410: Very toxic to aquatic life with long lasting effects.

This product should be stored, handled and used in accordance with good industrial hygiene practices and in conformity with any legal regulation. The information contained herewith is based on the present state of our knowledge and is intended to describe our products from the point of view of safety requirements. It does not guarantee any specific properties. Apart from any fair dealing for purposes of study, research and review of health, safety and environmental risks, no part of these documents may be reproduced by any process without written permission from CRC.

**Part Number** 

PPC108

Important Notice: This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. pro-POWER is the registered trademark of the Group. © Premier Farnell plc 2012.



## **X-ON Electronics**

**Authorized Distributor** 

Click to view similar products for Pro Power manufacturer.

Other Similar products are found below:

PPCY4C075100M PPCY3C10050M PPC217 PP001328 PP001316 PP001109 PP001088
PP000940 PP030 PP000909 PP001326 PP001308 PP000877 PP000868 PP000704
PP001163 PP001156 PP001085 PP000510 PP001076 PP000944 PP000914 PP000407
PP000386 PP000870