

Printview: Fuse disconnect terminal block with pivoting fuse holder; for miniature fuses ¼" x 1¼"; 120 V; with blown fuse indication by neon lamp - Item No.: 281-623/281-418

**WAGO**® online catalog / eShop

## Fuse disconnect terminal block with pivoting fuse holder; for miniature fuses ¼" x 1¼"; 120 V; with blown fuse indication by neon lamp

Item No.: 281-623/281-418



Fuse disconnect terminal block with pivoting fuse holder; for miniature fuses ¼" x 1¼"; 120 V; with blown fuse indication by neon lamp

### Marking

RoHS ✓  
Compliant

### Business data

Supplier	WAGO
Item no.	281-623/281-418
GTIN / EAN	4045454871567
Content	1
Order amount	50
Customer item number	

### Notes

Safety information 1: Electrical ratings are given by the fuse and blown fuse indication.

### Technical data

#### Miscellaneous

Total number of connection points	2
Total number of potentials	2
Color	gray
Ratings according to 1	IEC/EN 60947-7-3
Pollution degree (1)	3
Rated voltage EN (1) [V]	800 [V]
Rated surge voltage (1) [kV]	8 [kV]
Nominal current [A]	10 [A]

Printview: Fuse disconnect terminal block with pivoting fuse holder; for miniature fuses ¼" x 1¼"; 120 V; with blown fuse indication by neon lamp - Item No.: 281-623/281-418

<b>Technical data</b>	
<i>Connection technology (1)</i>	<i>CAGE CLAMP®</i>
<i>Solid sizes 1</i>	<i>0.08 ... 4 mm<sup>2</sup> / 28 ... 12 AWG</i>
<i>Fine-stranded wires 1</i>	<i>0.08 ... 4 mm<sup>2</sup> / 28 ... 12 AWG</i>
<i>Strip length 1</i>	<i>9 ... 10 mm / 0.35 ... 0.39 in</i>
<i>Type of wiring</i>	<i>Front-entry wiring</i>
<i>Design</i>	<i>angled</i>
<i>Marking level</i>	<i>Center marking</i>
<i>Insulating material</i>	<i>Polyamide 66 (PA 66)</i>
<i>Fire load [MJ]</i>	<i>0.393 [MJ]</i>
<i>Weight [g]</i>	<i>19.825 [g]</i>
<i>Width</i>	<i>10 mm / 0.394 in</i>
<i>Height from upper-edge of DIN-rail [mm]</i>	<i>60 [mm]</i>
<i>Height from upper-edge of DIN-rail</i>	<i>60 mm / 2.362 in</i>
<i>Length</i>	<i>60 mm / 2.362 in</i>
<i>Type of mounting</i>	<i>DIN 35 rail</i>
<i>Safety information 2</i>	<i>Leakage current in case of blown fuse: Neon lamp &lt; 0.4mA</i>

Printview: Fuse disconnect terminal block with pivoting fuse holder; for miniature fuses ¼" x 1¼"; 120 V;  
with blown fuse indication by neon lamp - Item No.: 281-623/281-418

## Images & drawings



## Address

WAGO Kontakttechnik GmbH & Co. KG

Hansastr. 27

32423 Minden

Telefon: 0571/887-0

Fax: 0571/887-169

<http://www.wago.com>

© WAGO Kontakttechnik GmbH & Co. KG

Technische Änderungen und Irrtümer vorbehalten.

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [wago](#) manufacturer:*

Other Similar products are found below :

[750-460](#) [231-118/026-000](#) [231-303/026-000](#) [231-620/019-000](#) [257-403](#) [280-438](#) [280-831](#) [284-624](#) [210-111](#) [231-303/037-000](#) [231-446/001-000\\_NR](#) [232-216/026-000](#) [234-510](#) [264-726](#) [280-339](#) [0283-0671](#) [830-800/000-305](#) [750-512](#) [750-455](#) [51251782](#) [286-312](#) [713-1428/107-000](#) [731-138/048-000](#) [750-459](#) [750-517](#) [750-602](#) [793-3505](#) [826-172](#) [859-304](#) [280-335](#) [231-535/001-000](#) [2604-1105](#) [2604-1106](#) [2604-1504](#) [2606-1103/020-000](#) [2624-1103](#) [2626-3103/020-000](#) [821-104](#) [713-1107](#) [852-1411](#) [2106-1307](#) [2116-5307](#) [832-1205](#) [832-3604](#) [2009-110](#) [281-512/281-501](#) [286-336](#) [750-421](#) [750-838](#) [753-559](#)