

**RoHS  
Compliant**



## Application:

To be installed in dry and humid rooms and used as a termination and connection cable in the control, measuring and signal technology.

## Construction:

### Phase Conductor:

Fine-stranded copper conductor

### Insulation:

PVC (Polyvinyl Chloride)

### Separator:

Plastic foil tape

### Screen:

TCWB (Tinned Copper Wire Braid)

### Sheath:

PVC (Polyvinyl Chloride)

## Characteristics:

### Voltage Rating:

0.14mm<sup>2</sup> : 350V  
Above 0.14mm<sup>2</sup> : 500V

### Test Voltage:

0.14mm<sup>2</sup> : 800V  
Above 0.14mm<sup>2</sup> : 1200V

### Temperature Rating:

Fixed : -40°C to +80°C  
Flexed : -5°C to +50°C

### Min. Bending Radius:

Flexed : 10 × overall diameter

### Sheath Colour:

Grey

## Cable Standards

Made in accordance with the following:  
Generally to DIN VDE 0812, BS EN/IEC 60332-1-2

## Dimensions:

Part Number	No. of Cores	Nominal Cross Sectional Area mm <sup>2</sup>	Conductor Construction		Conductor Loop Resistance Ω/km	Overall Diameter mm	Nominal Weight kg/km
			No. of Strands	Strand Diameter mm			
PP001174	2	0.25	14	0.16	75.5	4.3	20
PP001178		0.34	19	0.16	57.7	4.7	33
PP001182		0.5	16	0.21	37.8	5.2	42
PP001175	3	0.25	14	0.16	75.5	4.5	35
PP001179		0.34	19	0.16	57.7	4.9	41
PP001183		0.5	16	0.21	37.8	5.7	55
PP001176	4	0.25	14	0.16	75.5	4.8	44
PP001180		0.34	19	0.16	57.7	5.5	48
PP001184		0.5	16	0.21	37.8	6.3	68

# LiYCY Screened PVC Control Cable **pro-POWER**

Part Number	No. of Cores	Nominal Cross Sectional Area mm <sup>2</sup>	Conductor Construction		Conductor Loop Resistance Ω/km	Overall Diameter mm	Nominal Weight kg/km
			No. of Strands	Strand Diameter mm			
PP001177	5	0.25	14	0.16	75.5	5.2	50
PP001181		0.34	19	0.16	57.7	6.2	58

## Part Number Table

Description	No. of Cores	Nominal Cross Sectional Area mm <sup>2</sup>	Reel Length	Part Number
LiYCY Screened PVC Control Cable	2	0.25	50m	PP001174
		0.34		PP001178
		0.5		PP001182
	3	0.25		PP001175
		0.34		PP001179
		0.5		PP001183
	4	0.25		PP001176
		0.34		PP001180
		0.5		PP001184
	5	0.25		PP001177
		0.34		PP001181

**Important Notice :** This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. pro-POWER is the registered trademark of the Group. © Premier Farnell plc 2012.

# X-ON Electronics

Authorized Distributor

*Click to view similar products for [Pro Power manufacturer](#).*

Other Similar products are found below :

[PPCY4C075100M](#) [PPCY3C10050M](#) [PPC217](#) [PP001328](#) [PP001316](#) [PP001109](#) [PP001088](#)

[PP000940](#) [PP030](#) [PP000909](#) [PP001326](#) [PP001308](#) [PP000877](#) [PP000868](#) [PP000704](#)

[PP001163](#) [PP001156](#) [PP001085](#) [PP000510](#) [PP001076](#) [PP000944](#) [PP000914](#) [PP000407](#)

[PP000386](#) [PP000870](#)