

# H01N2-D BS EN 50525-2-81 Welding Cable

pro-POWER



RoHS  
Compliant

## Application:

These cables are used as a connection to welding robots in the automotive industry, shipyards and for manually/automatically operated lines and spot welding. The robust cable structure makes them resistant to low and high temperatures, ozone and radiation, oils, acids, fats and petrols.

## Cable Standards:

Made in accordance with the following:

BS EN 50525-2-81 (previously BS 638 Part 4, CENELEC  
HD22.6, VDE0282-6), BS EN 60332-1-2

## Construction:

Conductor	: Generally to Class 6 flexible copper conductor according to BS EN 60228 (previously BS 6360)
Separator	: PET (Polyester Tape)
Sheath	: Rubber compound, Type EM5 according to BS EN 50363

## Characteristics:

Voltage Rating	: 100V
Temperature Rating	: -40°C to +85°C (Fixed) -20°C to +85°C (Flexed)
Min. Bending Radius	: 6 × overall diameter (Flexed)
Sheath Colour	: Black & Red

## Electrical Characteristics:

### Duty Cycle and Current Carrying Capacity:

The current carrying capacity of a welding cable depends on the length of the duty cycle. The duty cycle is the length of time during which a loaded current passes through the cable over an operation period of 5 minutes, expressed as a percentage of that period. For example, if the current is flowing for the whole 5 minutes the duty cycle is 100%, and if the current is flowing for 1 minute the duty cycle is 20%.

As conductor temperature varies according to the time in use as well as current, ratings shown are given as a guide.

The permissible loading of the cable for duty cycles other than those shown in the table can be calculated using the following formula:

$$I = I_{100} \times \sqrt{100/F}$$

Where:

I : is the maximum permissible loading current for the required duty cycle.

$I_{100}$  : is the maximum permissible loading current for a duty cycle of 100%.

F : is the required duty cycle calculated as a percentage of the 5 minute operation period.

# H01N2-D BS EN 50525-2-81

## Welding Cable

pro-POWER

Typical guidance values for different welding processes are as follows:

Fully automatic welding 100%

Semi-automatic welding 65 - 85%

Manual Welding 30 - 60%

Very infrequent or occasional welding 20%

### Current Carrying Capacity:

Nominal Cross Sectional Area mm <sup>2</sup>	Current Rating for Single Cycle Operation over a Maximum Period of 5 Minutes Amps			
	100%	85%	60%	35%
10	100	103	108	122
16	135	145	175	230
25	180	195	230	300
35	225	245	290	375

Ambient Air Temperature : +25°C

Max. Conductor Temperature : +85°C

The above table is from HD 516 S2:1997

### De-Rating Factors:

Ambient Temperature	+25°C	+30°C	+35°C	+40°C	+45°C	+50°C	+55°C
De-Rating Factor	1.0	0.96	0.91	0.87	0.82	0.76	0.71

### Conductors:

Flexible Copper Conductors for Single Core Cables

Nominal Cross Sectional Area mm <sup>2</sup>	Max. Diameter of Wires in Conductor mm	Max. Resistance of Conductor at 20°C
		Plain Wires Ω/km
10	0.21	1.91
16	0.21	1.21
25	0.21	0.78
35	0.21	0.554

### Dimensions:

Part Number	No. of Cores	Colour Codes	Nominal Cross Sectional Area mm <sup>2</sup>	Nominal Thickness of Insulation mm	Nominal Overall Diameter mm	Nominal Weight kg/km
PP000939	1	Black	10	2	9	146
PP000940	1		16	2	10	204
PP000942	1		25	2	11.5	290
PP000944	1		35	2	12.5	384

[www.element14.com](http://www.element14.com)

[www.farnell.com](http://www.farnell.com)

[www.newark.com](http://www.newark.com)

[www.cpc.co.uk](http://www.cpc.co.uk)

pro-POWER

# H01N2-D BS EN 50525-2-81 Welding Cable



Part Number	No. of Cores	Colour Codes	Nominal Cross Sectional Area mm <sup>2</sup>	Nominal Thickness of Insulation mm	Nominal Overall Diameter mm	Nominal Weight kg/km
PP000955	1	Red	10	2	9	146
PP000941	1		16	2	10	204
PP000943	1		25	2	11.5	290
PP000945	1		35	2	12.5	384

## Part Number Table

Description	Sheath Colour	Reel Length (m)	Part Number
H01N2-D BS EN 50525-2-81 Welding Cable	Black	50	PP000939
			PP000940
			PP000942
			PP000944
	Red		PP000955
			PP000941
			PP000943
			PP000945

**Important Notice :** This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. pro-POWER is the registered trademark of the Group. © Premier Farnell plc 2012.

# X-ON Electronics

Authorized Distributor

*Click to view similar products for [Pro Power manufacturer](#).*

Other Similar products are found below :

[PPCY4C075100M](#) [PPCY3C10050M](#) [PPC217](#) [PP001328](#) [PP001316](#) [PP001109](#) [PP001088](#)

[PP000940](#) [PP030](#) [PP000909](#) [PP001326](#) [PP001308](#) [PP000877](#) [PP000868](#) [PP000704](#)

[PP001163](#) [PP001156](#) [PP001085](#) [PP000510](#) [PP001076](#) [PP000944](#) [PP000914](#) [PP000407](#)

[PP000386](#) [PP000870](#)