

H07RN-F BS EN 50525-2-21

Unscreened Multicore Flexible Rubber Cable **pro-POWER**

Voltage Drop

Nominal Cross Sectional Area mm ²	DC or Single-Phase AC mV/A/m	Three-Phase AC mV/A/m
1	46	40
1.5	32	27
2.5	19	16

Conductor operating temperature: 60°C

Electrical Characteristics (4mm² and above)

Current Carrying Capacity

Nominal Cross Sectional Area mm ²	60°C Conductor Operating Temperature			85°C Conductor Operating Temperature		
	Single-Phase AC or DC		Three-Phase AC	Single-Phase AC or DC		Three-Phase AC
	1 Two Core Cable, With or Without Protective Conductor Amps	2 Single Core Cables Amps	1 Three Core, Four Core or Five Core Cable Amps	1 Two Core Cable, With or Without Protective Conductor Amps	2 Single Core Cables Touching Amps	1 Three Core, Four Core or Five Core Cable Amps
4	30	-	26	41	-	36
6	39	-	34	53	-	47

Ambient temperature : 30°C

Conductor operating temperature : 60°C / 85°C

Voltage Drop

Nominal Cross Sectional Area mm ²	Two Core Cable, DC mV/A/m	Two Core Cable, Single-Phase AC mV/A/m	1 Three Core, Four Core or Five Core Cable, Three-Phase AC mV/A/m
4	12	12	10
6	7.8	7.8	6.7

Conductor operating temperature: 60°C

De-Rating Factors:

Ambient Temperature	+35°C	+40°C	+45°C	+50°C	+55°C
De-Rating Factor	0.91	0.82	0.71	0.58	0.41

H07RN-F BS EN 50525-2-21

Unscreened Multicore Flexible Rubber Cable **pro-POWER**

Dimensions:

Part Number	No. of Cores	Nominal Cross Sectional Area mm ²	Nominal Thickness of Insulation mm	Nominal Overall Diameter mm	Nominal Weight kg/km
PP000946	3	6	1	14.78	390
PP000947	4	1	0.8	9.63	142
PP000948	4	1	0.8	9.63	142
PP000949	4	6	1	16.4	449
PP000950	5	1.5	0.8	11.8	206
PP000951	5	1.5	0.8	11.8	206
PP000952	5	2.5	0.9	14	297
PP000953	5	4	1	16.2	422
PP000954	7	1.5	0.8	15.13	315

Part Number Table

Description	Reel Length (m)	Part Number
H07RN-F BS EN 50525-2-21 Unscreened Multicore Flexible Rubber Cable	50	PP000946
	100	PP000947
	50	PP000948
	50	PP000949
	100	PP000950
	50	PP000951
	50	PP000952
	50	PP000953
	50	PP000954

Important Notice : This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. pro-POWER is the registered trademark of the Group. © Premier Farnell plc 2012.

X-ON Electronics

Authorized Distributor

Click to view similar products for [Pro Power manufacturer](#).

Other Similar products are found below :

[PPCY4C075100M](#) [PPCY3C10050M](#) [PPC217](#) [PP001328](#) [PP001316](#) [PP001109](#) [PP001088](#)

[PP000940](#) [PP030](#) [PP000909](#) [PP001326](#) [PP001308](#) [PP000877](#) [PP000868](#) [PP000704](#)

[PP001163](#) [PP001156](#) [PP001085](#) [PP000510](#) [PP001076](#) [PP000944](#) [PP000914](#) [PP000407](#)

[PP000386](#) [PP000870](#)