

3182B, 3183B LSZH / H05Z1Z1-F Unscreened Multicore Flexible Cable

pro-POWER

RoHS
Compliant



Application:

Used as an indoor general wiring cable primarily for installations in public areas. Examples include use on pendant lighting drops or as a general supply lead within hospital or airport projects. For installation where fire, smoke emission and toxic fumes create a potential threat to life and equipment.

Cable Standards:

Made in accordance with the following:

BS EN 50525-3-11 (HD21.14), BS EN/IEC 60332-1-2,
BS EN/IEC 60332-3-24.C

Construction:

Conductor : Class 5 flexible copper conductor according to
BS EN 60228 (previously BS 6360)
Insulation : LSZH (Low Smoke Zero Halogen) Type TI6 according to BS EN 50363
Sheath : LSZH (Low Smoke Zero Halogen) Type TM7 according to BS EN 50363

Characteristics:

Voltage Rating (Uo/U) : 300/500V
Temperature Rating : -20°C to +60°C
Min. Bending Radius : 5 × overall diameter
Core Identification : 2 core: Blue & Brown
3 core: Green/Yellow, Blue & Brown
Sheath Colour : White & Black

Electrical Characteristics:

Current Carrying Capacity and Mass Supportable

Nominal Cross Sectional Area mm ²	Current Carrying Capacity		Max. Mass Supportable by Twin Flexible Cord kg
	Single-Phase AC Amps	Three-Phase AC Amps	
0.75	6	6	3
1	10	10	5
1.5	16	16	5
2.5	25	20	5

www.element14.com
www.farnell.com
www.newark.com
www.cpc.co.uk

pro-POWER

3182B, 3183B LSZH / H05Z1Z1-F Unscreened Multicore Flexible Cable

pro-POWER

Voltage Drop

Nominal Cross Sectional Area mm ²	DC or Single-Phase AC mV/A/m	Three-Phase AC mV/A/m
0.75	62	54
1	46	40
1.5	32	27
2.5	19	16

Conductor operating temperature: 60°C*

* The tabulated values above are for 60°C thermoplastic or thermosetting insulated flexible cords and for other types of flexible cords they are to be multiplied by the following factors:

90°C thermoplastic or thermosetting insulation : 1.09

De-Rating Factors:

60°C Thermoplastic or Thermosetting Insulated Cords

Ambient Temperature	+35°C	+40°C	+45°C	+50°C	+55°C
De-Rating Factor	0.91	0.82	0.71	0.58	0.41

Conductors:

Class 5 Flexible Copper Conductors for Single Core and Multi-Core Cables

Nominal Cross Sectional Area mm ²	Max. Diameter of Wires in Conductor mm	Max. Resistance of Conductor at 20°C
		Plain Wires Ω/km
0.75	0.21	26
1	0.21	19.5
1.5	0.26	13.3
2.5	0.26	7.98

The above table is in accordance with BS EN 60228 (previously BS 6360)

Dimensions:

Part Number	No. of Cores	Colour Codes	Nominal Cross Sectional Area mm ²	Nominal Thickness of Insulation mm	Nominal Overall Diameter mm	Nominal Weight kg/km
PP000916	2	White	0.75	0.6	6.3	57
PP000917	2	Black	0.75	0.6	6.3	57
PP000918	2	White	1	0.6	6.6	65
PP000919	2	Black	1	0.6	6.6	65
PP000920	2	White	1.5	0.7	7.4	84
PP000921	2	Black	1.5	0.7	7.4	84
PP000922	3	White	0.75	0.6	6.7	68
PP000923	3	Black	0.75	0.6	6.7	68

www.element14.com
www.farnell.com
www.newark.com
www.cpc.co.uk

pro-POWER

3182B, 3183B LSZH / H05Z1Z1-F Unscreened Multicore Flexible Cable

pro-POWER

Part Number	No. of Cores	Colour Codes	Nominal Cross Sectional Area mm ²	Nominal Thickness of Insulation mm	Nominal Overall Diameter mm	Nominal Weight kg/km
PP000924	3	Black	1	0.6	7	78
PP000925	3	Black	1.5	0.7	8	107
PP000926	3	White	1.5	0.7	8	107
PP000927	3	White	2.5	0.8	9.9	163
PP000928	3	Black	2.5	0.8	9.9	163

Part Number Table

Description	Sheath Colour	Reel Length (m)	Part Number
3182B, 3183B LSZH / H05Z1Z1-F Unscreened Multicore Flexible Cable	White	100	PP000916
	Black		PP000917
	White		PP000918
	Black		PP000919
	White		PP000920
	Black		PP000921
	White		PP000922
	Black		PP000923
	Black		PP000924
	Black		PP000925
	White		PP000926
	White		PP000927
	Black		PP000928

Important Notice : This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. pro-POWER is the registered trademark of the Group. © Premier Farnell plc 2012.

X-ON Electronics

Authorized Distributor

Click to view similar products for [Pro Power manufacturer](#).

Other Similar products are found below :

[PPCY4C075100M](#) [PPCY3C10050M](#) [PPC217](#) [PP001328](#) [PP001316](#) [PP001109](#) [PP001088](#)

[PP000940](#) [PP030](#) [PP000909](#) [PP001326](#) [PP001308](#) [PP000877](#) [PP000868](#) [PP000704](#)

[PP001163](#) [PP001156](#) [PP001085](#) [PP000510](#) [PP001076](#) [PP000944](#) [PP000914](#) [PP000407](#)

[PP000386](#) [PP000870](#)