
pro-**Power**

RoHS

Compliant



Application:

RS232 data cables are general purpose overall screened cables. With protection against electrical interference, this cables are suitable for RS232 applications.

Construction:

Conductor	: Stranded tinned copper conductor
Insulation	: PVC (Polyvinyl Chloride)
Drain Wire	: Tinned copper
Screen	: Aluminium foil
Sheath	: LSF (Low Smoke and Fume)

Characteristics:

Voltage Rating	: 300V
Temperature Rating	: Fixed : -20°C to +80°C
Core Identification	: PP000886 - 4 core : Red, Black, White & Green PP000887 - 6 core : Red, Black, White, Green, Brown & Blue PP000888 - 8 core : Red, Black, White, Green, Brown, Blue, Orange & Yellow
Sheath Colour	: Grey

Electrical Characteristics:

Part Number	Capacitance at 1kHz pF/m	Max. Resistance of Conductor at 20°C Ω/km
PP000886		
PP000887	107	94.1
PP000888		

www.element14.com www.farnell.com www.newark.com www.cpc.co.uk



Dimensions:

Part Number	No. of Cores	AWG Size	Conductor Area CSA mm ²	No. of Max. Strands × Strand Size (mm)	Nominal Overall Diameter mm	Nominal Weight kg/km
PP000886	4				4.5	32
PP000887	6	24	0.2	7 × 0.2	5.3	37
PP000888	8				4.9	50

Part Number Table

Description	Reel Length (m)	Part Number	
Screened Cable, 4 Core, 24AWG, LSF		PP000886	
Screened Cable, 6 Core, 24AWG, LSF	100	PP000887	
Screened Cable, 8 Core, 24AWG, LSF		PP000888	

Important Notice : This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. pro-POWER is the registered trademark of the Group. © Premier Farnell plc 2012.

www.element14.com www.farnell.com www.newark.com www.cpc.co.uk



X-ON Electronics

Authorized Distributor

Click to view similar products for Pro Power manufacturer.

Other Similar products are found below :

 PPCY4C075100M
 PPCY3C10050M
 PPC217
 PP001328
 PP001316
 PP001109
 PP001088

 PP000940
 PP030
 PP000909
 PP001326
 PP001308
 PP000868
 PP000704

 PP001163
 PP001156
 PP001085
 PP0001076
 PP000944
 PP000914
 PP000407

 PP000386
 PP000870
 PP000870
 PP000944
 PP000914
 PP000407