

Individually Screened Multipaired LSZH 600V Computer, Security and Instrumentation Cable

pro-POWER

RoHS
Compliant



Application:

Individually screened LSZH (Low Smoke Zero Halogen) multi pair cable. The individual screens prevent cross-talk between the pairs and ensures excellent protection from electrical interference. Suitable for applications such as instrumentation, computer control systems and security applications.

Construction:

Conductor	: Tinned copper conductor
Insulation	: HDPE (High Density Polyethylene)
Shield	: Individual AL/PET (Aluminium/Polyester Tape)
Drain Wire	: Tinned copper
Sheath	: LSZH (Low Smoke Zero Halogen)

Characteristics:

Voltage Rating	: 600V
Temperature Rating	: -40°C to +70°C
Core Identification	: Pair 1 : Red & Black Pair 2 : White & Green
Sheath Colour	: Violet

Electrical Characteristics:

Nominal Capacitance pF/m	Impedance Ω	Velocity Ratio %	Max. DC Resistance of Conductor at 20°C Ω/km
115	45	66	54.2

Dimensions:

No. of Pairs	AWG Size	Conductor Area CSA mm ²	No. of Max. Strands × Strand Size (mm)	Nominal Overall Diameter mm	Nominal Weight kg/km
2	22	0.33	7 × 0.24	4.2	30

Part Number Table

Description	Reel Length (m)	Part Number
Individually Screened Pair Cable, 2PR, 22AWG	50	PP000868

Important Notice : This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. pro-POWER is the registered trademark of the Group. © Premier Farnell plc 2012.

www.element14.com
www.farnell.com
www.newark.com
www.cpc.co.uk

pro-POWER

X-ON Electronics

Authorized Distributor

Click to view similar products for [Pro Power manufacturer](#).

Other Similar products are found below :

[PPCY4C075100M](#) [PPCY3C10050M](#) [PPC217](#) [PP001328](#) [PP001316](#) [PP001109](#) [PP001088](#)

[PP000940](#) [PP030](#) [PP000909](#) [PP001326](#) [PP001308](#) [PP000877](#) [PP000868](#) [PP000704](#)

[PP001163](#) [PP001156](#) [PP001085](#) [PP000510](#) [PP001076](#) [PP000944](#) [PP000914](#) [PP000407](#)

[PP000386](#) [PP000870](#)