Screened FTP Cat 7 LSZH Cable 900MHz

pro-**Power**

RoHS Compliant



Application:

Horizontal Wiring in LAN

Multi-Construction : 4 Pair

Cable Construction

Conductor : Solid Bare Copper

Conductor Area CSA $: 0.26 \text{mm}^2$ Wire Size AWG: 23Construction $: 0.58 \pm 0.01$ Standard Dia.(mm): 0.58

Insulation : Skin - Foam - Skin

Average Thickness : 0.4

Insulation Dia.(mm) : $1.45 \pm 0.1 \times 2C$ Twist

Al-Pet shield(on each pair, Al outward) : ≥115%

Braiding Shield : Tin-Plated Copper Wire Construction : $0.12 \pm 0.003 \times 8 \times 6$

Jacket

Jacket Material : Low Smoke Zero Halogen (LSZH)

Flame Retardant Polyethylene

 Thickness(mm)
 : 0.8

 Dia.(mm)
 : 7.8 ±0.25

 Jacket Colour
 : Grey

Colour

Insulation colour are : Blue, White

Orange, White Green, White Brown, White

Characteristics

Max. Conductor DC Resistance at 20°C (Ω /Km) : <76.1 Rated Temperature(°C) : 70 Velocity ratio : 78%

 $Impedance(\Omega) \hspace{1.5cm} : \hspace{.1cm} 1\text{-}100 \hspace{.1cm} \text{Hz} \hspace{1.5cm} 100 \hspace{.1cm} \pm 15 \hspace{.1cm}$

100-250MHz 100 ±20 250-500MHz 100 ±25 500-1,000MHz 100 ±30



Screened FTP Cat 7 LSZH Cable 900MHz



Performance:

Frequency (MHz)	Attenuation (dB/100m) Max.	NEXT (dB/100m) Min.	PSNEXT (dB/100m) Min.	ELFEXT dB/100m) Min.	PSELFEXT (dB/100m) Min.	Return loss (dB/100m) Min.
1	2.01	78	75	78	75	20
4	3.74	78	75	78	75	23.01
10	5.86	78	75	78	75	25
16	7.41	78	75	71.22	68.22	25
31.25	10.41	78	75	65.4	62.4	23.64
62.5	14.88	75.46	72.46	59.38	56.38	21.54
100	19.02	72.4	69.4	55.3	52.3	20.11
250	30.97	66.43	63.43	47.34	44.34	17.32
500	45.26	61.92	58.92	41.32	38.32	17.3
600	50.1	60.73	57.73	39.74	36.74	17.3
900	63.01	58.09	55.09	36.22	33.22	13.43

Design:



Part Number Table

Description	Part Number
Cable, MULTIPR, 4PR, CAT 7, LSZH, GRY, 100m	PP000420
Cable, MULTIPR, 4PR, CAT 7, LSZH, GRY, 500m	PP000421

Important Notice: This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. pro-POWER is the registered trademark of the Group. © Premier Farnell plc 2012.

www.element14.com www.farnell.com www.newark.com www.cpc.co.uk



X-ON Electronics

Authorized Distributor

Click to view similar products for Pro Power manufacturer.

Other Similar products are found below:

PPCY4C075100M PPCY3C10050M PPC217 PP001328 PP001316 PP001109 PP001088
PP000940 PP030 PP000909 PP001326 PP001308 PP000877 PP000868 PP000704
PP001163 PP001156 PP001085 PP000510 PP001076 PP000944 PP000914 PP000407
PP000386 PP000870