

DeviceNet LSZH

Shielded Multipaired Cable

pro-POWER



RoHS
Compliant

Application:

A DeviceNet cable suitable for fixed application with LSZH (Low Smoke Zero Halogen) sheath. The accurate construction and the high shielding efficiency guarantee excellent transmissive performances in environments particularly polluted by electromagnetic interferences.

Cable Standards:

Made in accordance with the following:

BS EN/IEC 60332-1, BS EN/IEC 61034-2,
BS EN/IEC 60754-1, BS EN 50267-2-1, BS EN 50267-2-2

Construction:

Conductor	: Pair 1 - Data: Stranded tinned copper - 24AWG (0.25mm ²) Pair 2 - Power: Stranded tinned copper - 22AWG (0.35mm ²)
Insulation	: Pair 1 - Data: Foam-skin PE (Polyethylene) Pair 2 - Power: Solid PE (Polyethylene)
Shield	: AL/PET (Aluminium/Polyester Tape)
Drain Wire	: Tinned copper - 24AWG
Overall Shield	: TCWB (Tinned Copper Wire Braid)
Sheath	: FRNC-LSZH (Flame Retardant Non Corrosive - Low Smoke Zero Halogen)

Characteristics:

Voltage Rating	: 125V
Temperature Rating	: Fixed -20°C to +80°C Flexed -5°C to +50°C
Min. Bending Radius	: 10 × overall diameter
Insulation Identification	: Pair 1: Blue and White Pair 2: Red and Black
Sheath Colour	: Grey

Electrical Characteristics:

Electrical and Transmission Properties at 20°C

Max. DC Resistance of Conductor	: 77Ω/km (Data Pair) 52Ω/km (Power)
Capacitance at 800Hz	: 39nF/km (Data Pair)
Propagation Velocity at 10MHz	: 76% (Data Pair)
Impedance at 1MHz	: 120Ω (Data Pair)
Attenuation at 150kHz	: 1.0dB/100m
Attenuation at 500kHz	: 1.6dB/100m
Attenuation at 1MHz	: 2.3dB/100m
Dielectric Strength (Conductor/Conductor)	: 0.7kV AC / 1min
Dielectric Strength (Conductor/Shield)	: 0.7kV AC / 1min
Min. Insulation Resistance	: 5.0GΩ/km (Data Pair) 1GΩ/km (Power)
Transfer Impedance at 10MHz	: 15mΩ/m (Data Pair)

www.element14.com
www.farnell.com
www.newark.com
www.cpc.co.uk

pro-POWER

DeviceNet LSZH Shielded Multipaired Cable

pro-POWER

Dimensions:

No. of Pairs	Nominal Overall Diameter	Nominal Weight kg/km
2	6.9mm	70

Part Number Table

Description	Reel Length (m)	Part Number
DeviceNet LSZH Shielded Multipaired Cable	50	PP000902

Important Notice : This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. pro-POWER is the registered trademark of the Group. © Premier Farnell plc 2012.

www.element14.com
www.farnell.com
www.newark.com
www.cpc.co.uk

pro-POWER

X-ON Electronics

Authorized Distributor

Click to view similar products for [Pro Power manufacturer](#).

Other Similar products are found below :

[PPCY4C075100M](#) [PPCY3C10050M](#) [PPC217](#) [PP001328](#) [PP001316](#) [PP001109](#) [PP001088](#)

[PP000940](#) [PP030](#) [PP000909](#) [PP001326](#) [PP001308](#) [PP000877](#) [PP000868](#) [PP000704](#)

[PP001163](#) [PP001156](#) [PP001085](#) [PP000510](#) [PP001076](#) [PP000944](#) [PP000914](#) [PP000407](#)

[PP000386](#) [PP000870](#)