

# Screened Paired LSZH 600V Computer Cable

pro-POWER

RoHS  
Compliant



## Application:

A single pair LSZH (Low Smoke Zero Halogen) overall foil and braid screened cable suitable in applications for high speed data transmission where protection from interference is required.

## Construction:

Conductor	: Tinned copper conductor
Insulation	: HDPE (High Density Polyethylene)
Shield	: AL/PET (Aluminium/Polyester)
Drain Wire	: Tinned copper
Braid	: TCWB (Tinned Copper Wire Braid)
Sheath	: LSZH (Low Smoke Zero Halogen)

## Characteristics:

Voltage Rating	: 600V
Temperature Rating	: -40°C to +70°C
Core Identification	: White/Blue & Blue/White
Sheath Colour	: Violet

## Electrical Characteristics:

Nominal Capacitance (Conductor To Conductor) pF/m	Impedance Ω	Velocity Ratio %	Max. DC Resistance of Conductor at 20°C Ω/km
42 ±5	120 ±15	66	84.8

## Dimensions:

No. of Pairs	AWG Size	Conductor Area CSA mm <sup>2</sup>	No. of Max. Strands × Strand Size (mm)	Nominal Overall Diameter mm	Nominal Weight kg/km
1	24	0.2	7 × 0.2	5.9	54

## Part Number Table

Description	Reel Length (m)	Part Number
Screened Pair Cable, 1PR, 24AWG	50	PP000893

**Important Notice** : This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. pro-POWER is the registered trademark of the Group. © Premier Farnell plc 2012.

www.element14.com  
www.farnell.com  
www.newark.com  
www.cpc.co.uk

pro-POWER

# X-ON Electronics

Authorized Distributor

*Click to view similar products for [Pro Power manufacturer](#).*

Other Similar products are found below :

[PPCY4C075100M](#) [PPCY3C10050M](#) [PPC217](#) [PP001328](#) [PP001316](#) [PP001109](#) [PP001088](#)

[PP000940](#) [PP030](#) [PP000909](#) [PP001326](#) [PP001308](#) [PP000877](#) [PP000868](#) [PP000704](#)

[PP001163](#) [PP001156](#) [PP001085](#) [PP000510](#) [PP001076](#) [PP000944](#) [PP000914](#) [PP000407](#)

[PP000386](#) [PP000870](#)