

Defence Standard 61-12 Part 4 - 7-2-C Screened Multicore Cable

pro-POWER

RoHS
Compliant



Specifications:

Conductor Material	: Tinned Copper
Conductor Area CSA	: 0.22mm ²
Construction	: T0.2± 0.008×7
Stranded Dia.(mm)	: 0.58
Insulation Material	: PVC
Insulation Colours	: See Insulation Colours Table
Insulation Thickness	: 0.31
Insulation Dia.(+/-0.1mm)	: 1.2
Braid Shield	: Tinned Copper
Nylon Rip Cord	: 150D
Jacket Material	: PVC
Jacket Colour	: Grey
Jacket Thickness(mm)	: 0.35

Electrical Characteristics:

Max. Conductor DC Resistance at 20°C (Ω/Km)	: <93.8
20°C Insulation Resistance (MΩ/Km)	: >200
Rated Temperature(°C)	: 80
Rated Voltage(V)	: 440

Insulation Colours table

Conductor Number	Colour
1	Red
2	Blue
3	Green
4	Yellow
5	White
6	Black
7	Brown
8	Violet
9	Orange
10	Pink
11	Turquoise
12	Grey

Conductor Number	Colour
13	Red/Blue
14	Green/Red
15	Yellow/Red
16	White/Red
17	Red/Black
18	Red/Brown
19	Yellow/Blue
20	White/Blue
21	Blue/Black
22	Orange/Blue
23	Green/Blue
24	Grey/Blue

Conductor Number	Colour
25	Yellow/Green
26	White/Green
27	Green/Black
28	Orange/Green
29	Grey/Green
30	Yellow/Brown
31	White/Brown
32	Brown/Black
33	Grey/Brown
34	Yellow/Violet
35	Violet/Black
36	White/Violet

Defence Standard 61-12 Part 4 - 7-2-C Screened Multicore Cable



Part Number Table

Description	No. of Conductors	Jacket Diameter (mm)	Braiding	Filler	Reel Length (m)	Part Number
Cable, Screen, 7/0.2mm	4	4.4	T0.1×16×8	-	25	PP000244
					100	PP000245
	8	6.1	T0.15×16×8	1.9PVC Strip	25	PP000246
					100	PP000247
	12	6.9	T0.15×16×8	-	25	PP000248
					100	PP000249
	20	8.6	T0.15×24×7	-	25	PP000250
					100	PP000251
	36	10.8	T0.15×24×9	1.2PVC Strip	25	PP000252
					100	PP000253

Important Notice : This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. pro-POWER is the registered trademark of the Group. © Premier Farnell plc 2012.

X-ON Electronics

Authorized Distributor

Click to view similar products for [Pro Power manufacturer](#).

Other Similar products are found below :

[PPCY4C075100M](#) [PPCY3C10050M](#) [PPC217](#) [PP001328](#) [PP001316](#) [PP001109](#) [PP001088](#)

[PP000940](#) [PP030](#) [PP000909](#) [PP001326](#) [PP001308](#) [PP000877](#) [PP000868](#) [PP000704](#)

[PP001163](#) [PP001156](#) [PP001085](#) [PP000510](#) [PP001076](#) [PP000944](#) [PP000914](#) [PP000407](#)

[PP000386](#) [PP000870](#)