

UL1061 - 20AWG PVC Hook-Up Wire

100m reel



Product Code: UL1061 PVC Hook-Up Wire

Product Description:

Application

Internal wiring of appliances where exposed to oil at temperature not exceeding 60°C.

Multi-construction

- Single

Construction:

Conductor Material : Tinned copper
 Conductor AWG : 20
 Conductor Construction : T0.32±0.005×7 (7×28AWG)
 Conductor Stranded Dia.(mm) : 0.56mm²
 Jacket Material : Semi-Rigid PVC
 Jacket Min. Thickness : 0.24
 Jacket Dia.(mm) : 1.47
 Jacket Colour : See Table Below


Packaging

- 100m reel

Electrical Characteristics:

Max. Conductor DC Resistance at 20°C (Ω/Km) : <33
 Rated Temperature (°C) AWM/Style 1061 : 80
 Rated Voltage (V) : 300
 20°C Insulation Resistance(MΩ.KM) : >200

Diagram:



Part Number Table

Description	Colour	Reel Length (m)	Part Number
20AWG 7/28 UL1061	Black	100	PP000220
	Blue		PP000221
	Grey		PP000222
	Red		PP000223
	White		PP000224
	Violet		PP000225
	Yellow		PP000226
	Green/Yellow		PP000227

Important Notice : This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. pro-POWER is the registered trademark of the Group. © Premier Farnell plc 2012.

X-ON Electronics

Authorized Distributor

Click to view similar products for [Pro Power manufacturer](#).

Other Similar products are found below :

[PPCY4C075100M](#) [PPCY3C10050M](#) [PPC217](#) [PP001328](#) [PP001316](#) [PP001109](#) [PP001088](#)

[PP000940](#) [PP030](#) [PP000909](#) [PP001326](#) [PP001308](#) [PP000877](#) [PP000868](#) [PP000704](#)

[PP001163](#) [PP001156](#) [PP001085](#) [PP000510](#) [PP001076](#) [PP000944](#) [PP000914](#) [PP000407](#)

[PP000386](#) [PP000870](#)