



ISSUE 10; September 2012 - RoHS 2011/65/EU

### Description

- Industry standard SMD crystal
- Plastic encapsulated
- Low profile version also available please contact our sales offices for details

### Frequency Range

- Frequency: 3.579545 to 89.999999MHz
- Frequency Stability:  $\pm 10.00$ ppm
- Frequency Tolerance:  $\pm 10$ ppm to  $\pm 100$ ppm

### General Specification

- Load Capacitance (CL): 10.0pF to 50.0pF or Series
- Drive Level: 100 $\mu$ W max
- Ageing:  $\pm 5$ ppm max per year at 25°C
- Shunt Capacitance (C0): 5pF max

### Operating Temperature Ranges

- 0 to 50°C
- 10 to 60°C
- 20 to 70°C
- 40 to 85°C

### Environmental Parameters

- Storage Temperature Range: -40 to 90°C
- Drop: 75cm drop (3 times) onto hard wooden board
- Vibration: 1.5mm amplitude, 10Hz-55Hz, 1min in 3 mutually perpendicular planes, duration 2hrs each plane

### Ordering Information


- Frequency\*
- Model\*
- Frequency Tolerance (@25°C)\*
- Frequency Stability (over operating temperature range)\*
- Operating Temperature Range\*
- Load Capacitance\*
- Overtone\*
- Example:  
10.0MHz 86SMX  
50/50/-40 to 85C/10 FUND

### Packing Details

- Pack Style: **Bulk**      Loose in bulk pack  
Pack Size: 100
- Pack Style: **Reel**      Tape & reel in accordance with EIA-481-D  
Pack Size: 1,000
- Alternative packing options available




### Outline (mm)



Pad Connections

- Crystal
- N/C
- N/C
- Crystal



### Sales Office Contact Details:

UK: +44 (0)1460 270200  
Germany: +49 (0)7264 9145-0

France: +33 (0)5 34 50 91 18  
USA: +1 (0)408.273.4530

Email: [info@iqdfrequencyproducts.com](mailto:info@iqdfrequencyproducts.com)  
Web: [www.iqdfrequencyproducts.com](http://www.iqdfrequencyproducts.com)

**Electrical Specification - maximum limiting values**

Frequency Range	Frequency Tolerance	Stability		Temperature Range	ESR Max	Vibration Mode
		Min	Max			
3.579545 to <3.999999MH	±10ppm to ±100ppm	±10ppm ±20ppm ±30ppm ±50ppm	±150ppm	0 to 50°C -10 to 60°C -20 to 70°C -40 to 85°C	200Ω	Fundamental
4.000000 to <4.499999MH	±10ppm to ±100ppm	±10ppm ±20ppm ±30ppm ±50ppm	±150ppm	0 to 50°C -10 to 60°C -20 to 70°C -40 to 85°C	150Ω	Fundamental
4.500000 to <4.999999MH	±10ppm to ±100ppm	±10ppm ±20ppm ±30ppm ±50ppm	±150ppm	0 to 50°C -10 to 60°C -20 to 70°C -40 to 85°C	120Ω	Fundamental
5.000000 to <5.999999MH	±10ppm to ±100ppm	±10ppm ±20ppm ±30ppm ±50ppm	±150ppm	0 to 50°C -10 to 60°C -20 to 70°C -40 to 85°C	100Ω	Fundamental
6.000000 to <8.999999MH	±10ppm to ±100ppm	±10ppm ±20ppm ±30ppm ±50ppm	±150ppm	0 to 50°C -10 to 60°C -20 to 70°C -40 to 85°C	80Ω	Fundamental
9.000000 to <9.999999MH	±10ppm to ±100ppm	±10ppm ±20ppm ±30ppm ±50ppm	±150ppm	0 to 50°C -10 to 60°C -20 to 70°C -40 to 85°C	60Ω	Fundamental
10.000000 to <12.999999M	±10ppm to ±100ppm	±10ppm ±20ppm ±30ppm ±50ppm	±150ppm	0 to 50°C -10 to 60°C -20 to 70°C -40 to 85°C	50Ω	Fundamental
13.000000 to <18.999999M	±10ppm to ±100ppm	±10ppm ±20ppm ±30ppm ±50ppm	±150ppm	0 to 50°C -10 to 60°C -20 to 70°C -40 to 85°C	35Ω	Fundamental
19.000000 to <40.000000M	±10ppm to ±100ppm	±10ppm ±20ppm ±30ppm ±50ppm	±150ppm	0 to 50°C -10 to 60°C -20 to 70°C -40 to 85°C	25Ω	Fundamental
30.000000 to <34.999999M	±10ppm to ±100ppm	±10ppm ±20ppm ±30ppm ±50ppm	±150ppm	0 to 50°C -10 to 60°C -20 to 70°C -40 to 85°C	80Ω	3RD Overtone
35.000000 to <39.999999M	±10ppm to ±100ppm	±10ppm ±20ppm ±30ppm ±50ppm	±150ppm	0 to 50°C -10 to 60°C -20 to 70°C -40 to 85°C	70Ω	3RD Overtone
40.000000 to <44.999999M	±10ppm to ±100ppm	±10ppm ±20ppm ±30ppm	±150ppm	0 to 50°C -10 to 60°C -20 to 70°C	65Ω	3RD Overtone

**Sales Office Contact Details:**

UK: +44 (0)1460 270200

Germany: +49 (0)7264 9145-0

France: +33 (0)5 34 50 91 18

USA: +1 (0)408.273.4530

Email: [info@iqdfrequencyproducts.com](mailto:info@iqdfrequencyproducts.com)Web: [www.iqdfrequencyproducts.com](http://www.iqdfrequencyproducts.com)



**Electrical Specification - maximum limiting values**

Frequency Range	Frequency Tolerance	Stability		Temperature Range	ESR Max	Vibration Mode
		Min	Max			
		±50ppm		-40 to 85°C		
45.000000 to <49.999999M	±10ppm to ±100ppm	±10ppm ±20ppm ±30ppm ±50ppm	±150ppm	0 to 50°C -10 to 60°C -20 to 70°C -40 to 85°C	60Ω	3RD Overtone
50.000000 to <89.999999M	±10ppm to ±100ppm	±10ppm ±20ppm ±30ppm ±50ppm	±150ppm	0 to 50°C -10 to 60°C -20 to 70°C -40 to 85°C	80Ω	3RD Overtone

*This document was correct at the time of printing; please contact your local sales office for the latest version*

**Sales Office Contact Details:**

UK: +44 (0)1460 270200

Germany: +49 (0)7264 9145-0

France: +33 (0)5 34 50 91 18

USA: +1 (0)408.273.4530

Email: [info@iqdfrequencyproducts.com](mailto:info@iqdfrequencyproducts.com)

Web: [www.iqdfrequencyproducts.com](http://www.iqdfrequencyproducts.com)

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [iqd manufacturer](#):*

Other Similar products are found below :

[LFXTAL071761CUTT](#) [LFMCXO063767BULK](#) [LFMCXO063773BULK](#) [LFOCXO063802BULK](#) [LFOCXO063809BULK](#)  
[LFTCXO063709BULK](#) [LFTCXO063710BULK](#) [LFTCXO063779BULK](#) [LFTCXO070028Cutt](#) [LFTVXO063701BULK](#)  
[LFTVXO063702BULK](#) [LFTVXO063703BULK](#) [LFTVXO063707BULK](#) [LFTVXO063791BULK](#) [LFXTAL003156](#) [LFMCXO063766BULK](#)  
[LFMCXO063771BULK](#) [LFOCXO063816BULK](#) [LFTCXO063713BULK](#) [LFTCXO063714BULK](#) [LFTCXO063716BULK](#)  
[LFTVXO063704BULK](#) [LFTVXO063705BULK](#) [LFTVXO063706BULK](#) [LFTVXO063789BULK](#) [LFTVXO063790BULK](#) [LFXTAL003113](#)  
[LFOCXO063809](#) [LFSPXO009581](#) [LFTCXO063784](#) [LFTVXO063786](#) [LFSPXO009686Bulk](#) [LFRBXO059244Bulk](#) [LFTVXO075802Cutt](#)  
[LFOCXO067293Bulk](#) [LFTCXO075792Cutt](#) [LFMCXO064079BULK](#) [LFSPXO071189](#) [LFOCXO067293](#) [LFXTAL012312BULK](#)  
[LFTCXO063780BULK](#) [LFSPXO056269CUTT](#) [LFOCXO063803BULK](#) [LFSPXO009592CUTT](#) [LFOCXO065520Bulk](#) [LFMISC070550Bulk](#)  
[LFSPXO025494Cutt](#) [LFMCXO064080BULK](#) [LFOCXO063804BULK](#) [LFSPXO019884BULK](#)