

# UL1007/UL1569 - 22AWG PVC Equipment Wire

100m, 305m reel



**Product Code:** UL1007/UL1569 – 22AWG PVC

## Product Description:

### Application

Internal wiring of appliances where exposed to oil at temperature not exceeding 60°C.

### Multi-construction

- Single

### Construction:

Conductor Material : Tinned copper  
 Conductor AWG : 22  
 Conductor Construction : T0.25±0.008×7 (7×30AWG)  
 Conductor Stranded Dia.(mm) : 0.76  
 Jacket Material : PVC  
 Jacket Nom. Thickness : 0.41  
 Jacket Dia.(mm) : 1.58±0.1  
 Jacket Colour : See Table Below


### Packaging

- 100M/305M reel

## Electrical Characteristics:

Max. Conductor DC Resistance at 20°C (Ω/Km) : 56  
 Rated Temperature  
     AWM/Style 1007 : 80°C  
     AWM/Style 1569 : 105°C  
 Rated Voltage (V) : 300  
 20°C Insulation Resistance(MΩ.KM) : >200

## Diagram:



## Part Number Table

Description	Colour	Reel Length (m)	Part Number
22AWG 7/30 UL1007/1569	Black	100	PP000145
	Blue		PP000146
	Red		PP000147
	White		PP000148
	Yellow		PP000149
	Black	305	PP000150
	Red		PP000151
	White		PP000152

**Important Notice :** This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. pro-POWER is the registered trademark of the Group. © Premier Farnell plc 2012.



# X-ON Electronics

Authorized Distributor

*Click to view similar products for [Pro Power manufacturer](#).*

Other Similar products are found below :

[PPCY4C075100M](#) [PPCY3C10050M](#) [PPC217](#) [PP001328](#) [PP001316](#) [PP001109](#) [PP001088](#)

[PP000940](#) [PP030](#) [PP000909](#) [PP001326](#) [PP001308](#) [PP000877](#) [PP000868](#) [PP000704](#)

[PP001163](#) [PP001156](#) [PP001085](#) [PP000510](#) [PP001076](#) [PP000944](#) [PP000914](#) [PP000407](#)

[PP000386](#) [PP000870](#)