




Product Description:

Application	For communication and signal control systems
Reference Standard	Customer's sample spec. and the general standard
Multi-Construction	1

Cable Construction:

Conductor	Tinned Copper
Construction	T0.36 ±0.008
Standard Dia.(mm)	0.36
Insulation Layer	Foam - Skin
Thickness (mm)	0.62
Insulation Dia.(±0.1mm)	1.6
Insulation Colour	Nature
Braiding (mm)	Tinned Copper
Construction	T0.10 ±0.00 8 × 16 × 6
Braiding Coverage	95%
Jacket	PVC
Thickness(mm)	0.25
Dia. (±0.15mm)	2.6
Jacket Colour	Black
Marking	RG Wire & Cable Limited RG 179 B/U 75Ω PVC [MM] [WkYr]
Packaging	100m Reel

Design:



Electrical Characteristics:

Max. Conductor DC Resistance at 20°C (Ω/Km)	<186
Min. Insulation DC Resistance at 20°C ($\text{M}\Omega \times \text{Km}$)	>100
Rated Temperature(°C)	+80
Rated Voltage(V)	30
Capacitance(pF/m)	54 \pm 5
Velocity Ratio(%)	80
Impedance(Ω)	75 \pm 3
Attenuation at 20°C (dB/100m) (\pm 8%)	
10MHz	6
100MHz	19.5
200MHz	28

Part Number Table

Description	Part Number
Cable, Coaxial, 100m, Black, RG179, PVC	PP000613

Important Notice : This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. pro-POWER is the registered trademark of the Group. © Premier Farnell plc 2012.

X-ON Electronics

Authorized Distributor

Click to view similar products for [Pro Power manufacturer](#).

Other Similar products are found below :

[PPCY4C075100M](#) [PPCY3C10050M](#) [PPC217](#) [PP001328](#) [PP001316](#) [PP001109](#) [PP001088](#)

[PP000940](#) [PP030](#) [PP000909](#) [PP001326](#) [PP001308](#) [PP000877](#) [PP000868](#) [PP000704](#)

[PP001163](#) [PP001156](#) [PP001085](#) [PP000510](#) [PP001076](#) [PP000944](#) [PP000914](#) [PP000407](#)

[PP000386](#) [PP000870](#)