

# BS 4808 0.22mm<sup>2</sup> PVC Equipment Wire

pro-POWER

## Reference Standard

BS4808 Part 2 Class 2 and Def. Stan. 61-12(Pt6) Type 2

**RoHS  
Compliant**

## Specifications:

Conductor Material	: Tinned Copper
Conductor Area CSA	: 0.22mm <sup>2</sup>
Nominal Construction	: T0.20 ± 0.020 × 7
Stranded Dia.(mm)	: 0.60
Jacket Material	: PVC
Jacket Thickness	: 0.3
Jacket Dia.(±0.1mm)	: 1.2
Reel Length (Metric)	: 100m



## Electrical Characteristics:

Max.Conductor DC Resistance at 20°C (Ω/Km)	: <86.2
Min.Insulation DC Resistance at 20°C (MΩ/Km)	: 200
Rated Temperature(°C)	: -25 to +85
Rated Voltage(V)	: 1,000
Flame Performance	: UL1581VW-1 IEC60332-1

## Part Number Table

Description	Colour	Part Number
Wire, 100m, 7/0.2mm, Tinned Copper	Red/Black	PP000077
	Red/Brown	PP000078
	Red/Green	PP000079
	Red/Blue	PP000080
	Orange/Black	PP000081
	Orange/Red	PP000082
	Yellow/Black	PP000083
	Yellow/Red	PP000084
	Yellow/Green	PP000085
	Green/Red	PP000086
	Violet/Red	PP000087
	Grey/Black	PP000088
	Grey/Blue	PP000089
	White/Black	PP000090
	White/Red	PP000091
	Pink/Black	PP000092
Green/Yellow	PP000093	

**Important Notice** : This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. pro-POWER is the registered trademark of the Group. © Premier Farnell plc 2012.

www.element14.com  
www.farnell.com  
www.newark.com  
www.cpc.co.uk

pro-POWER

# X-ON Electronics

Authorized Distributor

*Click to view similar products for [Pro Power manufacturer](#).*

Other Similar products are found below :

[PPCY4C075100M](#) [PPCY3C10050M](#) [PPC217](#) [PP001328](#) [PP001316](#) [PP001109](#) [PP001088](#)

[PP000940](#) [PP030](#) [PP000909](#) [PP001326](#) [PP001308](#) [PP000877](#) [PP000868](#) [PP000704](#)

[PP001163](#) [PP001156](#) [PP001085](#) [PP000510](#) [PP001076](#) [PP000944](#) [PP000914](#) [PP000407](#)

[PP000386](#) [PP000870](#)