Defence Standard / BS 4808 10/0.1mm PVC Equipment Wire - 100m Reel

pro-**Power**

Reference Standard

BS4808 Part 2 Class 2 and Def. Stan. 61-12(Pt6) Type 2

RoHS Compliant



Specifications:

Conductor Material : Tinned Copper
Conductor Area CSA : 0.078mm²
Construction : T0.10± 0.008×10

 Stranded Dia.(mm)
 : 0.36

 Jacket Material
 : PVC

 Jacket Thickness Min.
 : 0.30

 Jacket Dia.(mm)
 : 1.05 ±0.1

 Reel Length (Metric)
 : 100m

Electrical Characteristics:

 $\begin{array}{lll} \text{Max.Conductor DC Resistance at 20°C (}\Omega\text{/Km)} & : 241 \\ \text{Rated Temperature(°C)} & : -25 \text{ to +85} \\ \text{Rated Voltage(V)} & : 1 \text{kV rms} \\ 20°C \text{ Insulation Resistance(M}\Omega\text{.KM)} & : >200 \\ \text{Current Rating} & : 0.5 \text{A} \\ \text{Flame Performance} & : \text{UL1581VW-1} \\ \end{array}$

Part Number Table

Description	Colour	Part Number
Wire, 100m, 10/0.1mm, Tinned Copper	Black	PP000050
	Brown	PP000051
	Red	PP000052
	Orange	PP000053
	Yellow	PP000054
	Green	PP000055
	Blue	PP000056
	Pink	PP000057
	Grey	PP000058
	White	PP000059
	Violet	PP000060

IEC60332-1

Important Notice: This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. pro-POWER is the registered trademark of the Group. © Premier Farnell plc 2012.

www.element14.com www.farnell.com www.newark.com www.cpc.co.uk



X-ON Electronics

Authorized Distributor

Click to view similar products for Pro Power manufacturer.

Other Similar products are found below:

PPCY4C075100M PPCY3C10050M PPC217 PP001328 PP001316 PP001109 PP001088
PP000940 PP030 PP000909 PP001326 PP001308 PP000877 PP000868 PP000704
PP001163 PP001156 PP001085 PP000510 PP001076 PP000944 PP000914 PP000407
PP000386 PP000870