pro-**Power**



Application:

Horizontal Wiring in LAN

Multi-Construction

Cable Construction

Conductor Conductor Area CSA Wire Size AWG Construction Standard Dia.(mm) Insulation Average Thickness Insulation Dia.(mm) Al-Pet shield(on each pair, Al outward) Braiding Shield Construction

Jacket

Jacket Material

Thickness(mm) Dia.(mm) Jacket Colour **Colour**

Insulation colour are

Characteristics

 $\begin{array}{ll} \text{Max. Conductor DC Resistance at 20°C (} \Omega/\text{Km}) &: <76.^{\prime} \\ \text{Rated Temperature(°C)} &: 70 \\ \text{Velocity ratio} &: 78\% \\ \text{Impedance(} \Omega) &: 1-10 \end{array}$

RoHS Compliant

	Solid Bare Copper 0.26mm ²
:	23
:	0.58 ±0.01
:	0.58
:	Skin - Foam - Skin
:	0.4
:	1.45 ±0.1 × 2C Twist
:	≥115%
:	Tin-Plated Copper Wire
:	0.12 ±0.003 × 8 × 6

: 4 Pair

: Low Smoke Zero Halogen (LSZH) Flame Retardant Polyethylene

- : 0.8 : 7.8 ±0.25
- : Blue

: Blue, White Orange,White Green, White Brown, White

Km)	: <76.1	
	: 70	
	: 78%	
	: 1-100MHz	100 ±15
	100-250MHz	100 ±20
	250-500MHz	100 ±25
	500-1,000MHz	100 ±30


www.element14.com www.farnell.com www.newark.com www.cpc.co.uk



Performance:

Frequency (MHz)	Attenuation (dB/100m) Max.	NEXT (dB/100m) Min.	PSNEXT (dB/100m) Min.	ELFEXT dB/100m) Min.	PSELFEXT (dB/100m) Min.	Return loss (dB/100m) Min.
1	2.01	78	75	78	75	20
4	3.74	78	75	78	75	23.01
10	5.86	78	75	78	75	25
16	7.41	78	75	71.22	68.22	25
31.25	10.41	78	75	65.4	62.4	23.64
62.5	14.88	75.46	72.46	59.38	56.38	21.54
100	19.02	72.4	69.4	55.3	52.3	20.11
250	30.97	66.43	63.43	47.34	44.34	17.32
500	45.26	61.92	58.92	41.32	38.32	17.3
600	50.1	60.73	57.73	39.74	36.74	17.3
900	63.01	58.09	55.09	36.22	33.22	13.43

Design:



Part Number Table

Description	Part Number
Cable, MULTIPR, 4PR, CAT 7, LSZH, BLU, 100m	PP000416
Cable, MULTIPR, 4PR,, CAT 7, LSZH, BLU, 500m	PP000417

Important Notice : This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. pro-POWER is the registered trademark of the Group. © Premier Farnell pic 2012.

www.element14.com www.farnell.com www.newark.com www.cpc.co.uk



X-ON Electronics

Authorized Distributor

Click to view similar products for Pro Power manufacturer.

Other Similar products are found below :

 PPCY4C075100M
 PPCY3C10050M
 PPC217
 PP001328
 PP001316
 PP001109
 PP001088

 PP000940
 PP030
 PP000909
 PP001326
 PP001308
 PP000868
 PP000704

 PP001163
 PP001156
 PP001085
 PP0001076
 PP000944
 PP000914
 PP000407

 PP000386
 PP000870
 PP000870
 PP000944
 PP000914
 PP000407