
# **LOUDITY**



## Specification

Туре	Unit	LD-BZEG-0905
Rated Voltage	V(DC)	5
Operating Voltage	V(DC)	4~8
*Rated Current(max)	mA	30
*Sound Output at 10cm	dB	80
*Rated Frequency	Hz	2700±200
Lead pin material		Red Copper
Operating Temperature	$^{\circ}$	-30~+70
Storage Temperature	$^{\circ}$	-40~+85
Housing material	NORYL	
weight	g	2.0


<sup>\*</sup>Value Applying at Rated Voltage(DC)

#### **Environmental Test**

Storage in High temp.	Storage in +85±2°C test box for 240 hours, then expose to the room temperature for 2 hours without applying power			
Storage in Lower temp.	Storage in -40±2°C test box for 240 hours, then expose to the room temperature for 2 hours without applying power			
Vibration test	9. 3g 10  Make this test for the directions of 2	Amplitude:1.5mm Time:1min/axis  55 Hz  X,Y,Z for 2hours each(total 6 hours)		
Drop test	Drop from the height of 100cm to the surface of 10cm thick woosenboard,three directions(X,Y,Z)			
Solderability test	Soldering temp: 260±5 °C Hest applying time: 3±0.5sec	90%min lead terminals shall be wet with solder		
Lead pin strength pulling	The force 10 seconds of 9.8N is applied to each lead pin in axial direction	No damage and cutting off		

After test The value pf frequency/current/SPL shound be meet specifications

### Dimension(Unit:mm tolerance: ±0.5mm)



Wave Solder and Wash Allowed

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Audio Indicators & Alerts category:

Click to view products by Loudity manufacturer:

Other Similar products are found below:

M2BJ-BH24E 6-4 68S1240-PA MBA-624 F/BC 40P-DR LF FDG111PLF F/NRMB 24 BLACK LF PF-35N29WQ PFD-27A35PQ PL-27A35PSQ PS-531Q AB2020B-2-LW1 EBPT-401 PB06SD12AP PB-1220PEQ S6109 SC2036ACP SC616N-2 SC628FW SC628MPG SC648D SCS045MD9DT3S AB2025B-LW50-R ESZ-25B-5-250B F/BC 35-DR LF FCM12PLF F/EB20P-DR LF F/HU110MP24V-IP67B LF AI-2835-TF-LW150-2-R AI-4228-TF-LW305-R FSMD8585JSLF FSS-26T F/SU 21-02 LF F/TCW 05 WITH LABEL LF F/UCW 03 WITH LABEL LF F/UCW 06 WITH LABEL LF PKM22EPPH40S1-B0 PKM35-4A0 PL-35N29WQ PLD-27A35PQ PS-552Q CM-5 M2BJ-BH24E-D REF-202 LSC628ANR 5-100 PAL-328 03-810.001 RTO-1R07-001 PL-21N31PQ PF-27A25PSQ