

UL1007/UL1569 - 26AWG PVC Equipment Wire

305m reel



Physical & Mechanical Properties:

Temperature Range : -40°C to +105°C
 Bend Radius : 10X Cable Diameter
 Pull Tension : 2.18Lbs, Max.

Electrical Properties:

Voltage Rating : 300V
 Current Rating : 4A
 Inductance : 0.08 µH/ft, Nominal
 Conductor DCR : 41Ω / 1,000ft @ 20°C, Nominal
 Rated Temperature :
 AWM/STYLE 1007 : 80°C
 AWM/STYLE 1569 : 105°C

Specifications:

Conductor Material : Tinned Copper
 Conductor Size AWG : 26AWG
 Conductor Area CSA : 0.14mm²
 No. of Strands × Strand Size : 7×0.16mm (7×34AWG)
 Jacket Colour : See Table Below
 Jacket Material : PVC (Polyvinyl Chloride)
 Jacket Min. Average Thickness : 0.40mm
 External Diameter : 1.29mm
 Operating Temperature Max : 80°C
 Reel Length (Imperial) : 1,000ft
 Reel Length (Metric) : 305m

Part Number Table

Description	Colour	Part Number
26AWG 7/34 UL1007/1569	Black	PP000136
	Red	PP000137

Important Notice : This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. pro-POWER is the registered trademark of the Group. © Premier Farnell plc 2012.



X-ON Electronics

Authorized Distributor

Click to view similar products for [Pro Power manufacturer](#).

Other Similar products are found below :

[PPCY4C075100M](#) [PPCY3C10050M](#) [PPC217](#) [PP001328](#) [PP001316](#) [PP001109](#) [PP001088](#)

[PP000940](#) [PP030](#) [PP000909](#) [PP001326](#) [PP001308](#) [PP000877](#) [PP000868](#) [PP000704](#)

[PP001163](#) [PP001156](#) [PP001085](#) [PP000510](#) [PP001076](#) [PP000944](#) [PP000914](#) [PP000407](#)

[PP000386](#) [PP000870](#)