


## IS281- 4, IS281- 4GB



### DESCRIPTION

The IS281-4 and IS281-5GB are four channel optical isolators with each channel consists of an infrared emitting diode optically coupled to an NPN silicon photo transistor.

These devices belong to Isocom Compact Range of Optocouplers.



### FEATURES

- Half Pitch 1.27mm
- High AC Isolation voltage 3000V<sub>RMS</sub>
- Wide Operating Temperature Range -55°C to 110°C
- Pb Free and RoHS Compliant
- UL Approval E91231 Package Code "THP4"

### APPLICATIONS

- Hybrid Substrates with High Density Mounting
- Industrial System Controllers
- Measuring Instruments
- System Appliances

### ORDER INFORMATION

- Available in Tape and Reel with 2000pcs per reel

### ABSOLUTE MAXIMUM RATINGS (T<sub>A</sub> = 25°C)

Stresses exceeding the absolute maximum ratings can cause permanent damage to the device. Exposure to absolute maximum ratings for long periods of time can adversely affect reliability.

#### Input

Forward Current	50mA
Reverse Voltage	6V
Power dissipation	70mW

#### Output

Output Current	50mA
Collector to Emitter Voltage BV <sub>CEO</sub>	80V
Emitter to Collector Voltage BV <sub>ECO</sub>	7V
Power Dissipation	100mW

#### Total Package

Isolation Voltage	3000V <sub>RMS</sub>
Total Power Dissipation	170mW
Operating Temperature	-55 to 110 °C
Storage Temperature	-55 to 150 °C
Lead Soldering Temperature (10s)	260°C

#### ISOCOM COMPONENTS 2004 LTD

Unit 25B, Park View Road West, Park View Industrial Estate  
Hartlepool, Cleveland, TS25 1PE, United Kingdom  
Tel : +44 (0)1429 863 609 Fax : +44 (0)1429 863 581  
e-mail : sales@isocom.co.uk  
<http://www.isocom.com>

#### ISOCOM COMPONENTS ASIA LTD

Hong Kong Office,  
Block A, 8/F, Wah Hing Industrial mansion,  
36 Tai Yau Street, San Po Kong, Kowloon, Hong Kong.  
Tel : +852 2995 9217 Fax : +852 8161 6292  
e-mail : sales@isocom.com.hk



**IS281- 4, IS281- 4GB**

**ELECTRICAL CHARACTERISTICS (T<sub>A</sub> = 25°C unless otherwise specified)**

**INPUT**

Parameter	Symbol	Test Condition	Min	Typ.	Max	Unit
Forward Voltage	V <sub>F</sub>	I <sub>F</sub> = 20mA		1.2	1.4	V
Reverse Current	I <sub>R</sub>	V <sub>R</sub> = 4V			10	μA
Terminal Capacitance	C <sub>t</sub>	V <sub>F</sub> = 0V, f = 1KHz		30	250	pF

**OUTPUT**

Parameter	Symbol	Test Condition	Min	Typ.	Max	Unit
Collector-Emitter Breakdown Voltage	BV <sub>CEO</sub>	I <sub>F</sub> = 0, I <sub>C</sub> = 0.1mA	80			V
Emitter-Collector Breakdown Voltage	BV <sub>ECO</sub>	I <sub>F</sub> = 0, I <sub>E</sub> = 10μA	7			V
Collector-Emitter Dark Current	I <sub>CEO</sub>	I <sub>F</sub> = 0, V <sub>CE</sub> = 48V			100	nA

**COUPLED**

Parameter	Symbol	Test Condition	Min	Typ.	Max	Unit
Current Transfer Ratio	CTR	I <sub>F</sub> = 5mA, V <sub>CE</sub> = 5V IS281-4 IS281-4GB	50 100		600 600	%
Collector-Emitter Saturation Voltage	V <sub>CE(sat)</sub>	I <sub>F</sub> = 8mA, I <sub>C</sub> = 2.4mA			0.4	V
Floating Capacitance	C <sub>f</sub>	V <sub>CE</sub> = 0V, f = 1MHz		0.6	1	pF
Output Rise Time	t <sub>r</sub>	V <sub>CE</sub> = 10V, I <sub>c</sub> = 2mA, R <sub>L</sub> = 100Ω		2	18	μs
Output Fall Time	t <sub>f</sub>			3	18	
Turn-On Time	t <sub>ON</sub>			3		
Turn-Off Time	t <sub>OFF</sub>			3		
Turn-On Time	t <sub>ON</sub>	V <sub>CE</sub> = 5V, I <sub>c</sub> = 16mA, R <sub>L</sub> = 1.9kΩ		2		
Turn-Off Time	t <sub>OFF</sub>			40		
Storage Time	t <sub>s</sub>			25		

**ISOLATION**

Parameter	Symbol	Test Condition	Min	Typ.	Max	Unit
Input to Output Isolation Voltage	V <sub>ISO</sub>	RH = 40% - 60%, t = 1 min Note 1	3000			V <sub>RMS</sub>
Input to Output Isolation Resistance	R <sub>ISO</sub>	RH = 40% - 60%, V <sub>IO</sub> = 500V Note 1	5x10 <sup>10</sup>	1x10 <sup>11</sup>		Ω

Note 1 : Measured with input leads shorted together and output leads shorted together.




Fig 1 Forward Current vs  $T_A$




Fig 2 Collector Power Dissipation vs  $T_A$




Fig 3 Forward Current vs Forward Voltage




Fig 4 Forward Current Temperature Coefficient vs Forward Current




Fig 5 Pulse Forward Current vs Pulse Forward Voltage




Fig 6 Pulse Forward Current vs Duty Cycle




Fig 7 Collector Current vs Collector-Emitter Voltage




Fig 8 Collector Current vs Low Collector-Emitter Voltage




Fig 9 Current Transfer Ratio vs Forward Current




Fig 10 Collector Current vs TA




Fig 11 Normalized Current Transfer Ratio vs Forward Current




Fig 12 Normalized Current Transfer Ratio vs TA




Fig 13 Collector-Emitter Voltage vs Forward Current




Fig 14 Collector-Emitter Saturation Voltage vs  $T_A$




Fig 15 Collector Dark Current vs  $T_A$




Fig 16 Frequency Response




Fig 17 Switching Time vs Load Resistance






Fig 18 Switching Time vs  $T_A$



Switching Time Test Circuit


## IS281- 4, IS281- 4GB

### ORDER INFORMATION

UL Approval			
After PN	PN	Description	Packing quantity
None	IS281-4, IS281-4GB	Surface Mount Tape & Reel	2000 pcs per reel

### DEVICE MARKING




Example : IS281-4




THP4      denotes Device Part Number  
 /          denotes Isocom  
 Y          denotes 1 digit Year code  
 WW        denotes 2 digit Week code

## IS281- 4, IS281- 4GB

### PACKAGE DIMENSIONS (mm)




### RECOMMENDED SOLDER PAD LAYOUT (mm)






## IS281- 4, IS281- 4GB

### TAPE AND REEL PACKAGING



Description	Symbol	Dimension mm (inch)
Tape Width	W	$16 \pm 0.3$ (0.63)
Pitch of Sprocket Holes	$P_0$	$4 \pm 0.1$ (0.15)
Distance of Compartment to Sprocket Holes	F	$7.5 \pm 0.1$ (0.295)
	$P_2$	$2 \pm 0.1$ (0.079)
Distance of Compartment to Compartment	$P_1$	$12 \pm 0.1$ (0.47)

**IR REFLOW SOLDERING TEMPERATURE PROFILE**  
**One Time Reflow Soldering is Recommended.**  
**Do not immerse device body in solder paste.**



Profile Details	Conditions
<b>Preheat</b> - Min Temperature (T <sub>SMIN</sub> ) - Max Temperature (T <sub>SMAX</sub> ) - Time T <sub>SMIN</sub> to T <sub>SMAX</sub> (t <sub>s</sub> )	150°C 200°C 60s - 120s
<b>Soldering Zone</b> - Peak Temperature (T <sub>P</sub> ) - Time at Peak Temperature - Liquidous Temperature (T <sub>L</sub> ) - Time within 5°C of Actual Peak Temperature (T <sub>P</sub> - 5°C) - Time maintained above T <sub>L</sub> (t <sub>L</sub> ) - Ramp Up Rate (T <sub>L</sub> to T <sub>P</sub> ) - Ramp Down Rate (T <sub>P</sub> to T <sub>L</sub> )	260°C 10s max 217°C 30s max 60s - 100s 3°C/s max 6°C/s max
Average Ramp Up Rate (T <sub>smax</sub> to T <sub>P</sub> )	3°C/s max
Time 25°C to Peak Temperature	8 minutes max



## DISCLAIMER

Isocom Components is continually working to improve the quality and reliability of its products. Nevertheless, semiconductor devices in general can malfunction or fail due to their inherent electrical sensitivity and vulnerability to physical stress. It is the responsibility of the buyer, when utilizing Isocom Components products, to comply with the standards of safety in making a safe design for the entire system, and to avoid situations in which a malfunction or failure of such Isocom Components products could cause loss of human life, bodily injury or damage to property.

In developing your designs, please ensure that Isocom Components products are used within specified operating ranges as set forth in the most recent Isocom Components products specifications.

The Isocom Components products listed in this document are intended for usage in general electronics applications (computer, personal equipment, office equipment, measuring equipment, industrial robotics, domestic appliances, etc.). These Isocom Components products are neither intended nor warranted for usage in equipment that requires extraordinarily high quality and/or reliability or a malfunction or failure of which may cause loss of human life or bodily injury ("Unintended Usage"). Unintended Usage include atomic energy control instruments, airplane or spaceship instruments, transportation Instruments, traffic signal instruments, combustion control instruments, medical Instruments, all types of safety devices, etc... Unintended Usage of Isocom Components products listed in this document shall be made at the customer's own risk.

Gallium arsenide (GaAs) is a substance used in the products described in this document. GaAs dust and fumes are toxic. Do not break, cut or pulverize the product, or use chemicals to dissolve them. When disposing of the products, follow the appropriate regulations. Do not dispose of the products with other industrial waste or with domestic garbage.

The products described in this document are subject to the foreign exchange and foreign trade laws.

The information contained herein is presented only as a guide for the applications of our products. No responsibility is assumed by Isocom Components for any infringements of intellectual property or other rights of the third parties which may result from its use. No license is granted by implication or otherwise under any intellectual property or other rights of Isocom Components or others.

The information contained herein is subject to change without notice.

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [High Speed Optocouplers](#) category:*

*Click to view products by [Isocom](#) manufacturer:*

Other Similar products are found below :

[6N136F](#) [PS8502L2-AX](#) [ACNW261L-000E](#) [ACPL-344JT-000E](#) [ACPL-K49T-500E](#) [ACPL-K74T-000E](#) [ACPL-K75T-000E](#) [ACPL-W21L-560E](#) [ACPL-K44T-500E](#) [TLP187\(TPL,E\(T](#) [TLP2601\(TP1,F\)](#) [610737H](#) [6N137A-X001](#) [6N137A-X017T](#) [6N139-X007T](#) [HCPL2630M](#) [HCPL2731SM](#) [TLP555\(F\)](#) [HCPL2630SM](#) [PS2841-4A-F3-AX](#) [PS9817A-1-F3-AX](#) [PS9821-2-F3-AX](#) [ORPC-817D](#) [ORPC-817M/C](#) [ORPC-817M/B](#) [PT17-51C/L129\(BIN2\)](#) [TLP521-4GBSM](#) [UMW817C](#) [6N137S1\(TA\)](#) [TLP521GB](#) [TLP521GB-S](#) [PS2501](#) [PS2501-S](#) [TLP785GB](#) [TLP785GB-S](#) [LTV-214-G](#) [TLP2766A\(E](#) [TLP2766A\(LF4,E](#) [LCR-0202](#) [EL814S1\(TA\)-V](#) [PC817X4NSZ2B](#) [CYPC817](#) [OR-MOC3023](#) [TLP267J\(TPL,E\(T](#) [TLP109\(TPL,E\(O](#) [EL2514S1\(TU\)\(CLW\)-G](#) [EL816S2\(C\)\(TU\)-F](#) [TLP281-4](#) [MOC3023M](#) [ACPL-K49T-060E](#)