### **FEATURES AND SPECIFICATIONS**



# Fixed Wallplate 1 Port PowerCat UTP/ FTP Category 5E

#### **Features and Benefits**

The PowerCat 2 Port Shuttered Fixed Wallplate offers an economic alternative to the modular system, eliminating the need for separate components as only one part is needed. The Wallplate is a complete assembly, comprising 2, C5E RJLP Connectors, Fascia, Spring Loaded Shutters and a protected labelling facility. The product is designed to be compatible with UK single gang back boxes.

Molex Premise Networks unique patented RJLP RJ45 Connector is engineered to meet the highest performance standards in the industry and offers a low profile, space saving design, that allows installation in shallow back boxes and trunking.

Suitable for high speed data transmission, the PowerCat RJLP RJ45 was designed to meet the requirements of the C5E standard which demands compliance with the PowerSum principle of measurement and test.

- UK standard 86 x 86mm fascia
- Low profile C5E RJ45 Connector
- Spring loaded shutters
- FTP version provides through-shield continuity

#### **Technical Specification**

#### **Termination Tools:**

Molex and industry standard tooling

#### **IDC Terminations:**

Suitable for 0.4mm - 0.6mm solid or stranded cable, maximum o.d. 1.5mm. Two wires may be terminated for daisychain applications.

Patents pending on connector and module designs.

#### Mechanical

#### **Jack Connector**

Operating Life: Minimum 500

insertion cycles

Contact Material: Phosphor Bronze Contact Plating: 1.25 micrometers

Au/Ni

Material: UL 94V0

Thermoplastic

#### **IDC Connector**

Operating Life: Minimum 100

Reterminations

Contact Material: Phosphor Bronze
Contact Plating: Sn/Pb over Ni
Wire Size: 2x26-22 awg solid or

stranded

#### **Electrical**

D.C. Resistance:  $<20m\Omega$ 

D.C. Resistance Imbalance:  $<\!2.0m\Omega$  Insulation Resistance:  $>100m\Omega$  Attenuation (dB) @1MHz 0.0121

@16MHz 0.0193 @100MHz 0.1052

Crosstalk (dB) @1MHz -84.26

@16MHz -60.03

@100MHz -45.70

PowerSum Worst Pair(dB) @100MHz -41.83

Return Loss (dB) @1MHz -65.0 @16MHz -48.0 @100MHz - 30.0

#### ORDERING INFORMATION

Order No.	SAP No.	Description
WNC-00008-02	Consult Molex	2 Port PowerCat Fixed Shuttered UTP Wallplate 568B Category 5E, White
WNC-00011-02	Consult Molex	2 Port PowerCat Fixed Shuttered FTP Wallplate 568B Category 5E, White

#### **MOLEX PREMISE NETWORKS**

Americas Tel: 630 969 4550 www.molexpn.com **EMEA**Tel: 44 (0)2392 205800 www.molexpn.co.uk

**APAC**Tel: 61 3 9971 7111
www.molexpn.com.au

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

## Click to view similar products for molex manufacturer:

Other Similar products are found below:

60506-C-50 73108 72903 1062837003 0533241060 68301-1017 71506-C 880504 387790039 53254-0710 85071-0017 387204903

783472003 514412093 0026482195 0191310031 503308-4410 0008650814 791099208 0039000218 89762-1403 89762-1542 89762-1582

0011404526 00136 0022173102 0026615060 CR4006A30M003 0039532085 58098-0628 0003092041 0008520123 0011030025

0011184017 0022162060 0022552102 01312 M15730061 61432 6150300002 CS63W64 CS8264N CS8365N CS8369 62201-8780 62500
1774 M37730026 63103-50 63443-2215 63443-3160