

HIS is a range of two heat shrink tubing types in handy dispenser boxes. The range consists of HIS-3 and HIS-A (a dual wall tubing) with 3:1 shrink ratios. With their ideal shrink ratio of 3:1 these products replace many differently sized tubing solutions by fitting almost any heat shrink task. The handy dispenser boxes allow for proper storage and the tubing can remain dust-free even after breaking open a package.

HIS-3

Features and Benefits

HIS-3 with 3:1 shrink ratio, unlined tubing is the new generation of tubing in dispenser packs fitting highly variable substrate dimensions.

Another great benefit of HIS-3 is that only 5 sizes cover the same range of diameters from 1mm up to 20mm in 10 sizes of 2:1 shrink ratio tubing, thus reducing the inventory by half. To complete the range sizes 9/3 and 18/6 are also available.

Application

- General purpose electrical insulation
- Coloured Identification
- Protection against corrosion and mechanical abrasion

HIS-A

Features and Benefits

HIS-A is dual wall tubing with a 3:1 shrink ratio. The inner wall melts when heated and is forced into gaps. When the tubing cools down the adhesive forms a seal against moisture and protects the components. HIS-A is available in black only and comes in 6 sizes covering a wide range of applications due to its 3:1 shrink ratio.

Application

- Forms a seal against moisture
- Protection against corrosion and mechanical abrasion



HIS-3 can fit highly variable substrate dimensions.

Material Data		
RoHS	Type	HIS-3
	Material	Polyolefin, Cross-linked (POX)
	Shrink Ratio	3:1
	Longitudinal change after shrinkage	-10% max.
	Minimum Shrink Temperature (Metric)	+110 °C
	Operating Temperature	-55 °C to +125 °C
	Dielectric Strength (metric)	25 kV according to ASTM D 876
	Flammability	ASTM D2671

Material Data		
RoHS	Type	HIS-A
	Material	Polyolefin, Cross-linked (POX)
	Shrink Ratio	3:1
	Longitudinal change after shrinkage	-10% max.
	Minimum Shrink Temperature (Metric)	+120 °C
	Operating Temperature	-55 °C to +110 °C
	Dielectric Strength (metric)	15 kV/mm according to IEC 684 P2
	Flammability	ASTM D2671 (outer layer only)

HIS-3

Technical Table

Article-No.	Type	Supplied Ø D	Recov. Ø (D)	Wall (WT) nom.	Pack Cont. m	Colour
308-30150	HIS-3-1,5/0,5	1.5	0.5	0.5	10	Black (BK)
308-30152	HIS-3-1,5/0,5	1.5	0.5	0.5	10	Red (RD)
308-30153	HIS-3-1,5/0,5	1.5	0.5	0.5	10	Transparent (CL)
308-30156	HIS-3-1,5/0,5	1.5	0.5	0.5	10	Blue (BU)
308-30300	HIS-3-3/1	3.0	1.0	0.6	10	Black (BK)
308-30302	HIS-3-3/1	3.0	1.0	0.6	10	Red (RD)
308-30303	HIS-3-3/1	3.0	1.0	0.6	10	Transparent (CL)
308-30306	HIS-3-3/1	3.0	1.0	0.6	10	Blue (BU)
308-30307	HIS-3-3/1	3.0	1.0	0.6	10	Green-Yellow (GNYE)
308-30600	HIS-3-6/2	6.0	2.0	0.7	5	Black (BK)
308-30602	HIS-3-6/2	6.0	2.0	0.7	5	Red (RD)
308-30603	HIS-3-6/2	6.0	2.0	0.7	5	Transparent (CL)
308-30606	HIS-3-6/2	6.0	2.0	0.7	5	Blue (BU)
308-30607	HIS-3-6/2	6.0	2.0	0.7	5	Green-Yellow (GNYE)
308-30900	HIS-3-9/3	9.0	3.0	0.8	5	Black (BK)
308-30902	HIS-3-9/3	9.0	3.0	0.8	5	Red (RD)
308-30903	HIS-3-9/3	9.0	3.0	0.8	5	Transparent (CL)
308-30906	HIS-3-9/3	9.0	3.0	0.8	5	Blue (BU)
308-30907	HIS-3-9/3	9.0	3.0	0.8	5	Green-Yellow (GNYE)
308-31200	HIS-3-12/4	12.0	4.0	0.85	5	Black (BK)
308-31202	HIS-3-12/4	12.0	4.0	0.85	5	Red (RD)
308-31203	HIS-3-12/4	12.0	4.0	0.85	5	Transparent (CL)
308-31206	HIS-3-12/4	12.0	4.0	0.85	5	Blue (BU)
308-31207	HIS-3-12/4	12.0	4.0	0.85	5	Green-Yellow (GNYE)
308-31800	HIS-3-18/6	18.0	6.0	1.0	4	Black (BK)
308-31802	HIS-3-18/6	18.0	6.0	1.0	4	Red (RD)
308-31803	HIS-3-18/6	18.0	6.0	1.0	4	Transparent (CL)
308-31806	HIS-3-18/6	18.0	6.0	1.0	4	Blue (BU)
308-31807	HIS-3-18/6	18.0	6.0	1.0	4	Green-Yellow (GNYE)
308-32400	HIS-3-24/8	24.0	8.0	1.2	3	Black (BK)
308-32402	HIS-3-24/8	24.0	8.0	1.2	3	Red (RD)
308-32403	HIS-3-24/8	24.0	8.0	1.2	3	Transparent (CL)
308-32406	HIS-3-24/8	24.0	8.0	1.2	3	Blue (BU)
308-32407	HIS-3-24/8	24.0	8.0	1.2	3	Green-Yellow (GNYE)

All Dimensions in mm. Subject to technical changes.

HIS-A

Technical Table

Article-No.	Type	Supplied Ø D	Recov. Ø (D)	Wall (WT) nom.	Pack Cont. m	Colour
308-10300	HIS-A-3/1	3.0	1.0	1.0	10	Black (BK)
308-10600	HIS-A-6/2	6.0	2.0	1.2	5	Black (BK)
308-10900	HIS-A-9/3	9.0	3.0	1.3	5	Black (BK)
308-11200	HIS-A-12/4	12.0	4.0	1.4	5	Black (BK)
308-11800	HIS-A-18/6	18.0	6.0	2.2	4	Black (BK)
308-12400	HIS-A-24/8	24.0	8.0	2.5	3	Black (BK)

All Dimensions in mm. Subject to technical changes.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Wire Identification](#) category:

Click to view products by [Hellermann](#) manufacturer:

Other Similar products are found below :

[CU6337-000](#) [CU6342-000](#) [FCA-410-12](#) [11631010](#) [1-1768037-1](#) [1-1768037-2](#) [1-1768050-0](#) [PXLK-VI](#) [Q62184-1](#) [A64304-000](#) [QMT221](#)
[HK032WE1NF038B](#) [1330-0519-10](#) [1395199-1](#) [1395200-1](#) [1395202-1](#) [DMVF050WE-300S6](#) [D-SCE-1K-2.4-50-4-CS7834](#) [1538738-1](#)
[E90935-000](#) [EC1238-000](#) [EC1465-000](#) [EC1855-000](#) [EC1859-000](#) [EC1863-000](#) [EC5415-000](#) [EC7277-000](#) [EC7352-000](#) [EC7603-000](#)
[EC7707-000](#) [EC7735-000](#) [EC7768-000](#) [EC7828-000](#) [EC7854-000](#) [EC7952-000](#) [EC8128-000](#) [1768037-8](#) [1768041-7](#) [NC-127191-10-9](#)
[HS048WE2NF038B](#) [C03232-000](#) [HTCM-SCE-14-4H-9](#) [HTMS-3/16-9](#) [HT-SCE-1/4-2.0-4](#) [HT-SCE-3/16-2.0-4](#) [HTTMS-1/2-1.50-9](#) [HTTMS-](#)
[CM-1/2-4H-9](#) [HX-SCE-19.0-50-9](#) [HX-SCE-6.4-50-4](#) [C25254-000](#)