

308-30621



**Article Number:** 308-30621

**Heat Shrink Tubing, HIS-3-Bag, 3:1, 1/4", 6.4/2.0 dia., Polyolefin, Clear, 10/pkg**



Download spec sheet

## Base Data

**Local Order Number** 308-30621

**Type** HIS-3-BAG 6/2 CL

**Color** Clear (CL)

- Features and Benefits**
- Thin wall, flexible 3 to 1 shrink ratio material accommodates a wide range of component shapes and diameters.
  - Meets UL224 VW-1 specifications, making it ideal for high heat applications (excludes clear tubing).
  - Polyolefin material provides excellent insulation and mechanical strength with good resistance to solvents, oils and fuels.
  - Available in bulk reels, sticks and convenience bags (HIS-3 bags), for small to large volume applications.

**Product Description** TFN31 series heat shrink tubing features a flexible, thin wall and highly flame retardant polyolefin material with a higher operating temperature range than general-use heat shrink tubing. and offers good resistance to solvents, oils and fuels. The 3 to 1 shrink ratio accommodates a variety of component shapes and sizes. TFN31 tubing is available in bulk reels, sticks and convenience bags (HIS-3 bags), for projects of all sizes.

**Short Description** Heat Shrink Tubing, HIS-3-Bag, 3:1, 1/4", 6.4/2.0 dia., Polyolefin, Clear, 10/pkg

## Product Dimensions

**Length L (Metric)** 200 mm

**Length L3 (imperial)** 6.0 "

**Length L3 (metric)** 152.4 mm

**Shrink Ratio** 3:1

**Tensile Strength (MPa)** 14 MPa

**Trade Size** 1/4 "

**Tube Shape** Round

**Variant** Thin-Wall

**Volume Resistance (Ohm cm)** 10<sup>11</sup> Ω cm (ASTM D 876)

**Nominal Diameter (Imperial)** 1/4 "

**Nominal Diameter (Metric)** 6.4 mm

**Wall Thickness WT (Imperial)** 0.026 "

**Wall Thickness WT (Metric)** .65 mm

**Recovered Diameter d (metric)** 2.0 mm

**Recovered Diameter d (imperial)** 0.079 "

**Supplied Diameter D (imperial)** 0.25 "

**Supplied Diameter D (metric)** 6.4 mm

## Logistics and Packaging

**Quantity Per** bag

**Package Quantity** 10  
**Package Quantity (Metric)** 10 Pieces

## Material and Specifications

---

<b>Material</b>	Polyolefin, cross-linked (PO-X)
<b>Material Shortcut</b>	PO-X
<b>Dielectric Strength (Metric)</b>	20 kV/mm according to ASTM D 150
<b>Elongation at break</b>	800% nach ASTM D2671
<b>Flammability</b>	UL224 VW-1 (except clear)
<b>Halogenfree</b>	No
<b>Shrink Temperature</b>	+212 °F (+100 °C)
<b>Operating Temperature</b>	-67°F to +275°F (-55°C to +135°C)
<b>ROHS Compliant</b>	Yes
<b>Certification/Specification</b>	SAE - AMS - DTL-23053/5 Class 2 (clear) UL224 125 °C 600V VW-1 SAE - AMS - DTL-23053/5 Class 1 and 3
<b>UL Listed (US and Canada)</b>	Yes
<b>UL Recognized (US and Canada)</b>	Yes

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Wire Identification](#) category:*

*Click to view products by [Hellermann](#) manufacturer:*

Other Similar products are found below :

[CU6337-000](#) [CU6342-000](#) [FCA-410-12](#) [11631010](#) [1-1768037-1](#) [1-1768037-2](#) [1-1768050-0](#) [PXLK-VI](#) [Q62184-1](#) [A64304-000](#) [QMT221](#)  
[HK032WE1NF038B](#) [1330-0519-10](#) [1395199-1](#) [1395200-1](#) [1395202-1](#) [DMVF050WE-300S6](#) [D-SCE-1K-2.4-50-4-CS7834](#) [1538738-1](#)  
[E90935-000](#) [EC1238-000](#) [EC1465-000](#) [EC1855-000](#) [EC1859-000](#) [EC1863-000](#) [EC5415-000](#) [EC7277-000](#) [EC7352-000](#) [EC7603-000](#)  
[EC7707-000](#) [EC7735-000](#) [EC7768-000](#) [EC7828-000](#) [EC7854-000](#) [EC7952-000](#) [EC8128-000](#) [1768037-8](#) [1768041-7](#) [NC-127191-10-9](#)  
[HS048WE2NF038B](#) [C03232-000](#) [HTCM-SCE-14-4H-9](#) [HTMS-3/16-9](#) [HT-SCE-1/4-2.0-4](#) [HT-SCE-3/16-2.0-4](#) [HTTMS-1/2-1.50-9](#) [HTTMS-](#)  
[CM-1/2-4H-9](#) [HX-SCE-19.0-50-9](#) [HX-SCE-6.4-50-4](#) [C25254-000](#)