




**Panel Mount Indicator, Non-Relampable
Neon and Incandescent Technology
Mounting Hole, Ø 0.500"**



All dimensions are in inches



Recommended panel thickness: 0.030" to 0.090"

6" leads with 1/2" strip are standard

Storage temperature T_{STG} : -25°C - +80°C
Ambient temperature T_A : -20°C - +60°C
Voltage tolerance V_{OP} : ±10%

Part No.	Lens Color	Voltage	Current mA	Rated Life
Neon 115VAC Series				
WL-1050C1	Red	105-125VAC	1.5mA	25,000 Hrs
WL-1050C2	Clear	105-125VAC	1.5mA	25,000 Hrs
WL-1050C3	Amber	105-125VAC	1.5mA	25,000 Hrs
WL-1050C4	White	105-125VAC	1.5mA	25,000 Hrs
WL-1052C5	Green	105-125VAC	1.5mA	25,000 Hrs
Neon 230VAC Series				
WL-1051C1	Red	208-250VAC	1.5mA	25,000 Hrs
WL-1051C2	Clear	208-250VAC	1.5mA	25,000 Hrs
WL-1051C3	Amber	208-250VAC	1.5mA	25,000 Hrs
WL-1051C4	White	208-250VAC	1.5mA	25,000 Hrs
WL-1053C5	Green	208-250VAC	1.5mA	25,000 Hrs
Incandescent 12V Series				
WL-1090C1-12V	Red	12V-14V	80mA	25,000 Hrs
WL-1090C3-12V	Amber	12V-14V	80mA	25,000 Hrs
WL-1090C4-12V	White	12V-14V	80mA	25,000 Hrs
WL-1090C5-12V	Green	12V-14V	80mA	25,000 Hrs
Incandescent 28V Series				
WL-1090C1-28V	Red	24V-28V	40mA	25,000 Hrs
WL-1090C3-28V	Amber	24V-28V	40mA	25,000 Hrs
WL-1090C4-28V	White	24V-28V	40mA	25,000 Hrs
WL-1090C5-28V	Green	24V-28V	40mA	25,000 Hrs

Body Material: Nylon, white
Lens Material: Polycarbonate
Bezel Material: Stainless steel
Wire Gauge: 18 AWG
Wire Strip: 1/2"

Certifications: Most Wamco indicators carry Agency approvals. Please contact Wamco for the latest Agency information regarding the specific product series and voltage required.
Options: Additional options and lens styles available. Please contact Wamco for more information.

Drawn	SC	03/01/10	Panel Mount Indicators Neon and Incandescent	Datasheet: WL-105XCX Series WL-1090CX-XXX Series	Rev: 1
Checked	EB	03/01/10			
Approved	EB	03/02/10			

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Other Tools](#) category:

Click to view products by [Wamco](#) manufacturer:

Other Similar products are found below :

[CR-05FL7--150R](#) [CR-05FL7--698K](#) [899-2-KT46](#) [899-5-KT46](#) [CR-0AFL4--332K](#) [CR-12FP4--260R](#) [CRCW04021100FRT7](#)
[CRCW04021961FRT7](#) [5800-0090](#) [CRCW04024021FRT7](#) [CRCW040254R9FRT7](#) [CRCW0603102JRT5](#) [59065-5](#) [00-8273-RDPP](#) [00-8729-](#)
[WHPP](#) [593033](#) [593058](#) [593072](#) [593564100](#) [593575](#) [593591](#) [593593](#) [011349-000](#) [LTLA506SBLAMNBL](#) [CRCW08052740FRT1](#) [LUC-](#)
[012S070DSM](#) [LUC-018S070DSP](#) [599-2021-3-NME](#) [599-JJ-2021-03](#) [00-5080-YWPP](#) [5E4750/01-20R0-T/R](#) [LW1A-L1-GL](#) [LW1A-P1-GD](#)
[LW1L-A1C10V-GL](#) [LW1L-M1C70-A](#) [0202-0173](#) [00-9089-RDPP](#) [00-9300-RDPP](#) [CRCW2010331JR02](#) [01-1003W-8/32-10](#) [601-GP-08-](#)
[KT39](#) [601-JJ-06](#) [601-SPB](#) [601YSY](#) [602-JJ-03](#) [602SPB](#) [602Z](#) [603-JJ-07-FP](#) [603-JJY-04](#) [604J](#)