




PKI 10 A rot/red

Measuring and Testing Equipment:Sockets:4 mm system

Product description	
Description	Pole terminal with claw edge and captive insulated head and insulating ring. 4 mm diameter nickel-plated brass threaded bolt with 2 mm diameter transverse hole. For insulated, non-rotating installation in equipment chassis and switchpanels with a wall thickness up to 2 mm.
Type	PKI 10 A rot/red
Order No.	930 103-101
System	4 mm system
Housing Color	red
Other standard types	black color, order no. 930 103-100; blue color, order no. 930 103-102; yellow color, order no. 930 103-103; green color, order no. 930 103-104; yellow/green color, order no. 930 103-188
Drawing	



Technical data		
Type of contact	socket	
Type of termination	M 4 thread	
Rated voltage	DC 60 V	
Rated current	35 A	

Contact resistance	2 mOhm
Mounting	screw
Material	
Contact material	brass
Contact surface material	nickel-plated
Housing material	PF
Environmental conditions	
Temperature range	-25 °C to +100 °C
Inflammability class	
Housing	94 V-0

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Test Sockets category:

Click to view products by Hirschmann manufacturer:

Other Similar products are found below:

AXS-5032-04-02 AXS-3225-04-06 AXS-7050-04-12 5662 BP30-10-B BP30GNN-1 PKG BP30-10Y-1 PKG AXS-7050-04-01 AXS-5032-04-06 AXS-2520-04-01 AXS-5032-04-04 930308101 931714101 15.0084-21 563-0500 20.1020-21 20-313137 20-313139 20-313144 20-313140 20-313143 22.1042 + 22.2370-22 23.1010-23, 24, 25, 26, 27 23.3060-23 24.0160-1+25.0035 24.0160-4+25.0035 24.116-22 5281 5279 450-3704-01-06-00 AXS-3225-04-04 AXS-3225-04-10 AXS-7550-06-03 AXS-7550-06-05 269RB 2713BB BP30BN-1 PKG BP30RN-1 PKG 571-0200 450-3422-01-06-00 450-3888-01-04-00 BP30GP10 571-0400 571-0600 66.9131-23 66.9427-22 BP21-2BRN-B PKG 930058104 930103102 930103188