

- ◆ Automotive Wire
- ◆ Teflon® Wire
- ◆ 300V Solid Wire
- ◆ 300V Stranded Wire
- ◆ 600V Stranded Wire
- ◆ Speaker Wire
- ◆ Black/Red Bonded Speaker Wire
- ◆ Magnet Wire

HOOK-UP WIRE



Features:

- **Broad Line – Over 500 Types**
- **Packaged in a variety of lengths, gauges and colors**
- **Shrink wrapped spools**
- **Small quantity packages available**



ELECTRONICS, INC.

HOOK-UP WIRE

PRODUCT/APPLICATION INFORMATION

AUTOMOTIVE WIRE (WA SERIES) – 80° C

GAUGES: 18-16-14-12-10
INSULATION: P.V.C.
VOLTAGE RATING: 120 Volts
COLORS: Black, Brown, Red, Orange, Yellow, Green, Blue, Violet, Gray, White
PACKAGES: 10, 15, 20, 30 & 40 Feet
SPOOLS: 100 Feet
STRAND COUNT: 18ga = 16 strand
 All others = 19 strand

APPLICATIONS:

- Used in all automotive and truck applications
- J1128 industry certification

TEFLON® WIRE (WT SERIES) – 200° C

GAUGES: 26-24-22-20-18
INSULATION: Teflon® (TFE)
VOLTAGE RATING: 600 Volts
COLORS: Black, Brown, Red, Orange, Yellow, Green, Blue, Violet, Gray, White
SPOOLS: 25 and 100 feet

- Silver plated copper conductor
- Resistance to oils, alkalis, acids, flame and moisture
- Meets Mil 16878/4 and Mil 22759/11 specs

STRAND COUNT: 22, 20, 18ga = 19 strand
 24, 26ga = 7 strand

APPLICATIONS:

- All hi-temp or hi-rel applications
- Used in critical, high performance; military; commercial; racing

300V SOLID WIRE (WHS SERIES) – 90° C

GAUGES: 26-24-22-20-18-16
INSULATION: P.V.C.
COLORS: Black, Brown, Red, Orange, Yellow, Green, Blue, Violet, Gray, White
SPOOLS: 25 and 100 feet

- UL Style 1007
- CSA TR-64/1569
- Passes UL VW-1.S vertical flame test
- OSHA acceptable

APPLICATIONS:

- Internal wiring of electrical and electronic equipment
- Internal wiring of panels, meters, computers, business machines, appliances & control panels
- Point to point wiring where 300V required

MAGNET WIRE (WM SERIES)

GAUGES: 36-34-32-30-28-26-24-22-20-18
INSULATION: NONE
SPOOLS: 1/2 lb.

- Solid bare copper conductor
- Polyurethane/Polyamide (Nylon) Coated
- Solderable
- RoHS Compliant

APPLICATIONS:

- Transformers
- Inductors
- Motors
- Electromagnets
- Potentiometers

300V STRANDED WIRE (WH SERIES) – 90° C

GAUGES: 26-24-22-20-18-16
INSULATION: P.V.C.
COLORS: Black, Brown, Red, Orange, Yellow, Green, Blue, Violet, Gray, White
SPOOLS: 25 and 100 feet

- UL Style 1007
- CSA TR-64/1569
- Passes UL VW-1.S vertical flame test
- OSHA acceptable
- All tinned copper

STRAND COUNT: 22, 24, 26ga = 7 strand
 20ga = 10 strand
 16, 18ga = 16 strand

APPLICATIONS:

- Internal wiring of electrical and electronic equipment
- Internal wiring of panels, meters, computers, business machines, appliances & control panels
- Point to point wiring where 300V required

600V STRANDED WIRE (WH6 SERIES) – 105° C

GAUGES: 18-16-14-12-10
INSULATION: P.V.C.
COLORS: Black, Brown, Red, Orange, Yellow, Green, Blue, Violet, Gray, White
SPOOLS: 25 and 100 feet

- UL Style 1015
- CSA type TEW
- UL VW-1.S vertical flame test
- OSHA acceptable
- All tinned copper

STRAND COUNT: 10ga = 105 strand
 12ga = 65 strand
 14ga = 41 strand
 16ga = 26 strand
 18ga = 16 strand

APPLICATIONS:

- Internal wiring of electrical, electronic equipment and machinery
- Internal wiring of panels and meters
- Point to point wiring where 600V required

SPEAKER WIRE (CLEAR)

GAUGES: 22/2-20/2-18/2-16/2-14/2-12/2-10/2
INSULATION: P.V.C.
SPOOLS: 25 and 100 feet

- OSHA acceptable

APPLICATIONS:

- Lamps, radios, jukeboxes, HiFi & stereo

BLACK/RED BONDED SPEAKER WIRE

GAUGES: 18/2-16/2-14/2-12/2-10/2
INSULATION: P.V.C.
SPOOLS: 25 and 100 feet

- OSHA acceptable

APPLICATIONS:

- Easy identification
- Stereos, lamps, automotive, truck



NTE Electronics, Inc.
 44 Farrand Street, Bloomfield, NJ 07003
 Phone: 973-748-5089
 www.nteinc.com

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [nte manufacturer](#):

Other Similar products are found below :

[747](#) [797](#) [868](#) [NEH680M50FE](#) [NEHH1.0M450CB](#) [NTE48](#) [NTE526A](#) [228A](#) [231](#) [954](#) [2023](#) [510](#) [R04-11A30-120](#) [04-SLPE3750A](#) [5615](#) [591](#)
[7056](#) [7448](#) [NEH.10M50AA](#) [NEH2.2M63AA](#) [NEH330M35DD](#) [NEH33M10AA](#) [NEV.22M100AA](#) [NTE528](#) [NTE542](#) [NTE74154](#) [04-](#)
[SCBW25L-BK](#) [04-SCBW32L-BK](#) [04-SCW10C-BK](#) [04-SCBW19L-GR](#) [04-SCW19L-WH](#) [04-SCW19L-OR](#) [04-SCW38L-WH](#) [04-SCBW50L-](#)
[OR](#) [04-SCBW50L-GR](#) [04-SCW10C-GR](#) [04-SCW10C-OR](#) [04-SCBW32L-GR](#) [04-SCBW32L-WH](#) [04-SCBW32L-OR](#) [04-SCBW6C-WH](#) [04-](#)
[SCBW6C-GR](#) [04-SCBW6C-OR](#) [04-SCBW25L-GR](#) [04-SCBW25L-WH](#) [04-ESNF-500L](#) [04-SL.625-R-5](#) [04-SCW5C-WH](#) [04-ESNF-1000L](#)
[04-SL1.00-O](#)