

Dial Gage 2109S-10 Indicator

(JIS/ISO Standard)




New Dial Indicator

The new workhorse of dial indicators is now available, with increased environmental resistance, increased resistance to shock and a more rigid spindle.

Mitutoyo's Dial Gage 2109S-10 now offers users more stability and longer life, thanks to advances to the inner workings of the rack and pinion gear system. Shock resistance is increased with a more robust gear train, while contamination resistance has been dramatically increased over other indicators of this type with a tighter seal around the bezel and frame, and the elimination of a lifting lever screw.

A long slot in the lifting lever makes the contact point for the lift a straight line, creating a smoother lifting action and leading to longer operational life. A flat crystal allows easier reading, and jeweled bearings inside provide longer, more accurate life.



The contact point becomes a straight line for smoother operation.

Specifications

Order No.	2109S-10
Graduation	0.001mm
Total Range	1mm
Range Per Rev.	0.2mm
Dial Reading	0-100-0
Accuracy	±0.005mm
Measuring Face	1.5N or less

Distributed By:

Mitutoyo

www.mitutoyo.com

Mitutoyo America Corporation

Regional Offices

Michigan

Phone: (734) 459-2810

Illinois

Phone: (630) 978-5385

California

Phone: (626) 961-9661

M³ Solution Center

Massachusetts

Phone: (978) 692-8765

Indiana

Phone: (317) 577-6070

North Carolina

Phone: (704) 875-8332

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [mitutoyo](#) manufacturer:

Other Similar products are found below :

[2109S-10](#) [530-104](#) [103-129](#) [500-171-30](#) [7010SN](#) [148-104](#) [530-118](#) [293-832](#) [959150](#) [2046SB](#) [543-391B](#) [500-184-30](#) [102-301](#) [575-123](#) [148-201](#) [500-196-30](#) [2046S](#) [7301](#)