

APIX2 Transmitter with Dual Port HDMI and HDCP Support

Data Sheet ADV7682

FEATURES

APIX®2 transmitter with HDCP

High-bandwidth Digital Content Protection (HDCP) 1.4 support with internal preprogrammed HDCP keys

Dual channel encryption engine supports simple daisychain implementation for remote displays

Independent encryption of video and audio

Support for two independent video streams and two synchronous audio streams

Up to 3000 Mbps sustained downstream link bandwidth
Up to 187.5 Mbps upstream link bandwidth

Media independent interface (MII), serial port interface (SPI), I²C, and GPIO interfaces for sideband communication

Dual High-Definition Multimedia Interface (HDMI®) receiver Supports all HDMI video resolutions up to the maximum

APIX video link bandwidth of 2.57 Gbps

All mandatory and additional 3D video formats supported HDCP 1.4 decryption support on each port

Hardware controller for automated HDCP repeater

functions across APIX and HDMI HDCP blocks

HDCP repeater support, up to 24 KSVs supported

Integrated CEC controller, CEC 1.4 compatible

Adaptive TMDS equalizer

ITU-R BT.656 support

8-bit ITU-R BT.656 interface with embedded timing

720p supported at 148.5 MHz clock rate

Audio support

HDMI audio extraction support

Supports multiplexed (TDM) I²S audio I/O

On-chip SRC for synchronization to external master clocks and to synchronize two independent audio streams

General

Dual interrupt controller with APIX link status reporting

Internal EDID RAM

100-lead LQFP_EP, 14 mm × 14 mm package

Qualified for automotive applications

APPLICATIONS

Automotive infotainment

Infotainment head units

Rear seat entertainment systems

Automotive media port applications

HDMI repeaters and video switches

For more information about the ADV7682, including the complete data sheet, contact your local Analog Devices, Inc., sales office at www.analog.com/sales.



Rev. SpA Document Feedback

Information furnished by Analog Devices is believed to be accurate and reliable. However, no responsibility is assumed by Analog Devices for its use, nor for any infringements of patents or other rights of third parties that may result from its use. Specifications subject to change without notice. No license is granted by implication or otherwise under any patent or patent rights of Analog Devices. Trademarks and registered trademarks are the property of their respective owners.

SIMPLIFIED FUNCTIONAL BLOCK DIAGRAM




Figure 1.

ADV7682 Data Sheet

NOTES

 $APIX^{\circledast} \ is \ a \ registered \ mark \ of \ INOVA \ Semiconductors \ GMbH.$

 $I^2 C\ refers\ to\ a\ communications\ protocol\ originally\ developed\ by\ Philips\ Semiconductors\ (now\ NXP\ Semiconductors).$



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Display Interface IC category:

Click to view products by Analog Devices manufacturer:

Other Similar products are found below:

AD9887AKSZ-140 AD9887AKSZ-170 PI3HDX1204B1ZHEX PI3HDX1204EZHEX HD3SS213ZQER SN65DP149RSBR RSF34W100RF RSF33W100RC SN75DP126SSRHUR AD9985ABSTZ-110 TDP142RNQT AD9398KSTZ-150 AD9398KSTZ-100 AD9880KSTZ-100 AD9880KSTZ-150 AD9883ABSTZ-110 AD9883ABSTZ-140 AD9883ABSTZ-140 AD9883AKSTZ-140 AD9883AKSTZ-140 AD9883AKSTZ-140 AD9884AKSZ-140 AD9888KSZ-140 AD9884AKSTZ-170 AD9983AKSTZ-170 AD9983AKSTZ-170 AD9985BSTZ-170 AD9985