

## Application


- Horizontal and building backbone cable.
- Support current **Category 5** and **Category 5 enhanced** applications, such as:  
10 Base-T, 100 Base-T, 1000 Base-T (Gigabit Ethernet), FDDI, ATM

## Standards

- Aktuelle Normung: **ISO/IEC 11801, EN 50173**
- Zukünftige Normung: ISO/IEC 11801 2<sup>nd</sup> edition, EN 50173 2<sup>nd</sup> edition und prEN 50288-3-1

## Construction & Dimensions

- Construction: shielded 4 twisted pairs
- Conductor: solid bare copper
- Conductor diameter: AWG 24 (0,52 mm)
- Conductor insulation material: Polyethylene (PE)
- Diameter over insulation: 1.10 mm ± 0.05 mm
- Drain wire: AWG 26 tinned copper
- Shield: Aluminium/polyester foil
- Jacket material: PVC (Flame retardant)
- Outer diameter: 6.0 mm ± 0.3 mm



### Colour code

- Pair 1 White-Blue/Blue
- Pair 2 White-Orange/Orange
- Pair 3 White-Green/Green
- Pair 4 White-Brown/Brown

## Electrical characteristics (at 20 °C)

### Attenuation

Frequency	1	4	10	16	20	31.25	62.5	100	MHz
Maximum <sup>1)</sup>	4.0	4.0	6.3	8.0	9.0	11.4	16.5	21.3	dB/100m
Typical	2.0	3.8	6.0	7.6	8.5	10.8	15.0	19.2	dB/100m

### NEXT

Frequency	1	4	10	16	20	31.25	62.5	100	MHz
Minimum <sup>1)</sup>	60.0	56.3	50.3	47.2	45.8	42.9	38.4	35.3	dB
Typical	70	62	57	54	52	49	45	43	dB

### Power Sum NEXT

Frequency	1	4	10	16	20	31.25	62.5	100	MHz
Minimum <sup>1)</sup>	57.0	53.3	47.3	44.2	42.8	39.9	35.4	32.3	dB
Typical	68	60	55	52	50	47	43	41	dB

### Power Sum ELFEXT

Frequency	1	4	10	16	20	31.25	62.5	100	MHz
Minimum <sup>1)</sup>	60.8	48.8	40.8	36.7	34.8	30.9	24.9	20.8	dB
Typical	73	61	53	47	45	41	37	33	dB

### ACR

Frequency	1	4	10	16	20	31.25	62.5	100	MHz
Minimum <sup>1)</sup>	56.0	52.3	44.0	39.2	36.8	31.5	21.8	14.0	dB/100m
Typical	68.0	58.2	51.0	46.4	43.5	38.2	30.0	23.8	dB/100m

### Power Sum ACR

Frequency	1	4	10	16	20	31.25	62.5	100	MHz
Minimum <sup>1)</sup>	53.0	49.3	41.0	36.2	33.8	28.5	18.8	11.0	dB/100m
Typical	66.0	56.2	49.0	44.4	41.5	36.2	28.0	21.8	dB/100m

<sup>1)</sup>: Values according to cable requirements of ISO/IEC 11801 category 5 enhanced



### Electrical characteristics (at 20 °C)

Nominal mutual capacitance at 1 kHz	50 nF/km
Maximum conductor DCR	93,5 Ohm/km
NVP - Nominal Velocity of Propagation	0.70 c
SKEW – Propagation delay difference (100 MHz)	typical $\leq$ 15 ns/100m
Impedance 1 - 100 MHz	100 $\pm$ 15 Ohm

### General and environmental characteristics

Temperature range - operation	-20°C - +60°C
Temperature range - installation	+0°C - +50°C
Minimum bending radius - operation	24 mm
Minimum bending radius - installation	48 mm
Maximum pulling tension	80 N
Flame retardancy	IEC 332-1
Energy of flame	515 kJ/m
Weight (approx.)	43 kg/km
Maximum operating voltage	48 V rms
Maximum continuous current per conductor (25°C)	1.4 A

### Ordering information

#### MARKING

Text on the cable jacket                      Inkjet printing

**BELDEN 1633E FTP CAT5E 4PR AWG24 ISO/IEC 11801 EN 50173 VERIFIED 100 OHM**

Meter marking:                      Yes

#### JACKET COLOUR

Colour	RAL code	Belden colour code
Grey	RAL 7032	3251

#### PACKAGING (PUT UP)

Belden code	Delivery length	Weight	Remark
43132 xxxx 240	500 m	21.0 kg	Non returnable reel
43132 xxxx 241	1000 m	42.0 kg	Non returnable reel

xxxx: Belden colour code

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Belden](#) manufacturer:*

Other Similar products are found below :

[HIPWP2LA](#) [AX270172](#) [8916-BRN-100](#) [8916-GRN/YEL-500](#) [8916-YEL-500](#) [8917 002100](#) [8917-005-500](#) [8917-GRN/YEL-100](#) [8918-GRY-1000](#) [8919-BRN-1000](#) [8919-DK-BLU-100](#) [8920-BRN-1000](#) [8920-GRY-1000](#) [8920-RED-1000](#) [7805R-GRY-100](#) [7810A-BLK-500](#) [8104-CHR-500](#) [8108-CHR-100](#) [8125-CHR-100](#) [8132-CHR-1000](#) [8133-CHR-1000](#) [8155-CHR-1000](#) [8162-CHR-1000](#) [8164-CHR-100](#) [8164-CHR-1000](#) [8185-CHR-100](#) [8205-CHR-1000](#) [8218-BLK-1000](#) [8221-BLK-1000](#) [8233-BLK-1000](#) [8237-BLK-500](#) [8238-BLK-500](#) [8240-BLK-U1000](#) [8241A-BLK-1000](#) [8262-BLK-1000](#) [8263-BLK-U1000](#) [8268-BLK-500](#) [8279-BLK-1000](#) [83002 0041000](#) [83002 0101000](#) [83003-VIO-100](#) [83003-VIO-500](#) [83004 0051000](#) [83006 0041000](#) [83007 0081000](#) [83008-WHT-1000](#) [83010-BRN-100](#) [83010-DK-GRN-1000](#) [83023-BRN-100](#) [83023-DK-GRN-100](#)