


Pin 1 –  $V_{IN}$   
 Pin 2 –  $V_{OUT}$   
 Case – Ground

**K Package – TO-3**



Pin 1 –  $V_{IN}$   
 Pin 2 – Ground  
 Pin 3 –  $V_{OUT}$   
 Case – Ground

**V Package – TO-218**

## 5 AMP POSITIVE VOLTAGE REGULATORS

### FEATURES

- 0.01%/V LINE REGULATION
- 0.5% LOAD REGULATION
- 1% OUTPUT TOLERANCE  
(–A VERSIONS)
- AVAILABLE IN 5V, 12V AND 15V OPTIONS
- COMPLETE SERIES OF PROTECTIONS:
  - CURRENT LIMITING
  - THERMAL SHUTDOWN
  - SOA CONTROL

### Order Information

Part Number	K-Pack (TO-3)	V-Pack (TO-218)	Temp. Range
IP1R18Axx-zz	✓		-55 to +150°C
IP1R18xx-zz	✓		"
IP3R18AZz-xx	✓	✓	0 to +125°C
IP3R18zz-xx	✓	✓	"

#### Note:

xx = Voltage Code (05, 12, 15)      zz = Package Code (K, V)  
 eg. IP1R18AK-05      IP3R18V-12

### ABSOLUTE MAXIMUM RATINGS ( $T_{case} = 25^{\circ}C$ unless otherwise stated)

$V_I$	DC Input Voltage	35V
$P_D$	Power Dissipation	Internally limited
$T_J$	Operating Junction Temperature Range	See Table Above
$T_{STG}$	Storage Temperature Range	-65°C to +150°C
$T_L$	Lead Temperature (Soldering, 10 sec)	300°C

**ELECTRICAL CHARACTERISTICS** ( $T_J = 25^\circ\text{C}$  unless otherwise stated)

Parameter	Test Conditions <sup>2</sup>	IP1R18A-05 IP3R18A-05			IP1R18-05 IP3R18-05			Units
		Min.	Typ.	Max.	Min.	Typ.	Max.	
$V_O$ Output Voltage		4.95	5	5.05	4.85		5.15	V
	$I_O = 5\text{mA to } 5\text{A}$ $P_{OUT} \leq 50\text{W}$ $V_{IN} = 8\text{V to } 20\text{V}$ $T_J = \text{Over Temp. Range } ^1$	4.85		5.15	4.75		5.25	V
$\frac{\Delta V_O}{\Delta V_I}$ Line Regulation	$V_{IN} = 7.5\text{V to } 35\text{V}$		3	15	6		30	mV
	$I_O = 5\text{mA}^3$ $T_J = \text{Over Temp. Range } ^1$		6	30	12		60	
$\frac{\Delta V_O}{\Delta I_O}$ Load Regulation	$I_O = 5\text{mA to } 5\text{A}^3$		5	25	10		50	mV
	$T_J = \text{Over Temp. Range } ^1$		10	50	20		100	
$I_Q$ Quiescent Current	$I_O = 5\text{mA}$ $T_J = \text{Over Temp. Range } ^1$			7			7	mA
$\Delta I_Q$ Quiescent Current Change	$I_O = 5\text{mA to } 5\text{A}$ $T_J = \text{Over Temp. Range } ^1$			10			10	mA
	$I_O = 5\text{mA}$ $V_{IN} = 7.5\text{V to } 35\text{V}$ $T_J = \text{Over Temp. Range } ^1$			3			3	
$V_D$ Dropout Voltage	$I_O = 5\text{A}$ $\Delta V_{OUT} = 100\text{mV}$ $T_J = \text{Over Temp. Range } ^1$		2.5	3	2.5		3	V
Ripple Rejection	$I_O = 1\text{A}$ $f = 120\text{Hz}$ $T_J = \text{Over Temp. Range } ^1$	60	80		60	80		dB
Thermal Regulation	$t_p = 20\text{ms}$ $\Delta P = 50\text{W}$		0.002	0.01	0.002		0.02	%/W
$I_{PEAK}$ Peak Output Current	$V_{IN} = 10\text{V}$ $T_J = \text{Over Temp. Range } ^1$		8	12	8		12	A
$I_{SC}$ Short Circuit Current	$V_{IN} = 10\text{V}$		7		7			A
	$V_{IN} = 35\text{V}$		2		2			
$e_n$ Output Noise Voltage	$f = 10\text{Hz to } 100\text{kHz}$		40		40			$\mu\text{V}$
$R_{\theta JC}$ Thermal Resistance Junction to Case	K Package		1.0	1.5	1.0		1.5	$^\circ\text{C/W}$
	V Package		1.0	1.5	1.0		1.5	

**Notes**

- 1) Applies over full temperature range:-  
 $T_J = -55$  to  $+150^\circ\text{C}$  for IP1R18A-05 / IP1R18-05  
 $T_J = 0$  to  $+125^\circ\text{C}$  for IP3R18A-05 / IP3R18-05  
All other specifications apply at  $T_J = 25^\circ\text{C}$  unless otherwise stated.
- 2) Test conditions unless otherwise stated:-  
 $V_{IN} = 10\text{V}$ ,  $I_{OUT} = 2.5\text{A}$ .  
Although Power Dissipation is internally limited, these specifications apply for Power Dissipation up to 50W.
- 3) Load and Line regulation are electrically independent and are measured using pulse techniques at low duty cycle in order to maintain constant junction temperature. To determine the effects on the output voltage due to device heating, refer to thermal regulation specification.

**ELECTRICAL CHARACTERISTICS** ( $T_J = 25^\circ\text{C}$  unless otherwise stated)

Parameter	Test Conditions <sup>2</sup>	IP1R18A-12 IP3R18A-12			IP1R18-12 IP3R18-12			Units
		Min.	Typ.	Max.	Min.	Typ.	Max.	
$V_O$ Output Voltage		11.88	12	12.12	11.64	12	12.36	V
	$I_O = 5\text{mA to } 5\text{A}$ $P_{OUT} \leq 50\text{W}$ $V_{IN} = 15\text{V to } 27\text{V}$ $T_J = \text{Over Temp. Range } ^1$	11.64		12.36	11.40		12.60	V
$\frac{\Delta V_O}{\Delta V_I}$ Line Regulation	$V_{IN} = 14.5\text{V to } 35\text{V}$		5	30		10	60	mV
	$I_O = 5\text{mA}^3$ $T_J = \text{Over Temp. Range } ^1$		10	60		20	120	
$\frac{\Delta V_O}{\Delta I_O}$ Load Regulation	$I_O = 5\text{mA to } 5\text{A}^3$		10	60		20	120	mV
	$T_J = \text{Over Temp. Range } ^1$		20	120		40	240	
$I_Q$ Quiescent Current	$I_O = 5\text{mA}$ $T_J = \text{Over Temp. Range } ^1$			7			7	mA
$\Delta I_Q$ Quiescent Current Change	$I_O = 5\text{mA to } 5\text{A}$ $T_J = \text{Over Temp. Range } ^1$			10			10	mA
	$I_O = 5\text{mA}$ $V_{IN} = 14.5\text{V to } 35\text{V}$ $T_J = \text{Over Temp. Range } ^1$			3			3	
$V_D$ Dropout Voltage	$I_O = 5\text{A}$ $\Delta V_{OUT} = 250\text{mV}$ $T_J = \text{Over Temp. Range } ^1$		2.5	3		2.5	3	V
Ripple Rejection	$I_O = 1\text{A}$ $f = 120\text{Hz}$ $T_J = \text{Over Temp. Range } ^1$	52	72		52	72		dB
Thermal Regulation	$t_p = 20\text{ms}$ $\Delta P = 50\text{W}$		0.002	0.01		0.002	0.02	%/W
$I_{PEAK}$ Peak Output Current	$V_{IN} = 17\text{V}$ $T_J = \text{Over Temp. Range } ^1$		8	12		8	12	A
$I_{SC}$ Short Circuit Current	$V_{IN} = 17\text{V}$		4			4		A
	$V_{IN} = 35\text{V}$		2			2		
$e_n$ Output Noise Voltage			75			75		$\mu\text{V}$
$R_{\theta JC}$ Thermal Resistance Junction to Case	K Package		1.0	1.5		1.0	1.5	$^\circ\text{C/W}$
	V Package		1.0	1.5		1.0	1.5	

**Notes**

- 1) Applies over full temperature range:–  
 $T_J = -55$  to  $+150^\circ\text{C}$  for IP1R18A-12 / IP1R18-12  
 $T_J = 0$  to  $+125^\circ\text{C}$  for IP3R18A-12 / IP3R18-12  
All other specifications apply at  $T_J = 25^\circ\text{C}$  unless otherwise stated.
- 2) Test conditions unless otherwise stated:–  
 $V_{IN} = 17\text{V}$  ,  $I_{OUT} = 2.5\text{A}$  .  
Although Power Dissipation is internally limited, these specifications apply for Power Dissipation up to 50W.
- 3) Load and Line regulation are electrically independent and are measured using pulse techniques at low duty cycle in order to maintain constant junction temperature. To determine the effects on the output voltage due to device heating, refer to thermal regulation specification.

**ELECTRICAL CHARACTERISTICS** ( $T_J = 25^\circ\text{C}$  unless otherwise stated)

Parameter	Test Conditions <sup>2</sup>	IP1R18A-15 IP3R18A-15			IP1R18-15 IP3R18-15			Units
		Min.	Typ.	Max.	Min.	Typ.	Max.	
$V_O$ Output Voltage	$I_O = 5\text{mA to } 5\text{A}$	14.85	15	15.15	14.55	15	15.45	V
	$P_{OUT} \leq 50\text{W}$ $V_{IN} = 18\text{V to } 30\text{V}$ $T_J = \text{Over Temp. Range } ^1$	14.55		15.45	14.25		15.75	V
$\frac{\Delta V_O}{\Delta V_I}$ Line Regulation	$V_{IN} = 17.5\text{V to } 35\text{V}$		8	40		16	80	mV
	$I_O = 5\text{mA}^3$ $T_J = \text{Over Temp. Range } ^1$		16	80		32	160	
$\frac{\Delta V_O}{\Delta I_O}$ Load Regulation	$I_O = 5\text{mA to } 5\text{A}^3$		16	80		32	160	mV
	$T_J = \text{Over Temp. Range } ^1$		32	160		64	320	
$I_Q$ Quiescent Current	$I_O = 5\text{mA}$ $T_J = \text{Over Temp. Range } ^1$			7			7	mA
$\Delta I_Q$ Quiescent Current Change	$I_O = 5\text{mA to } 5\text{A}$ $T_J = \text{Over Temp. Range } ^1$			10			10	mA
	$I_O = 5\text{mA}$ $V_{IN} = 17.5\text{V to } 35\text{V}$ $T_J = \text{Over Temp. Range } ^1$			3			3	
$V_D$ Dropout Voltage	$I_O = 5\text{A}$ $\Delta V_{OUT} = 300\text{mV}$ $T_J = \text{Over Temp. Range } ^1$		2.5	3		2.5	3	V
Ripple Rejection	$I_O = 1\text{A}$ $f = 120\text{Hz}$ $T_J = \text{Over Temp. Range } ^1$	50	70		50	70		dB
Thermal Regulation	$t_p = 20\text{ms}$ $\Delta P = 50\text{W}$		0.002	0.01		0.002	0.02	%/W
$I_{PEAK}$ Peak Output Current	$V_{IN} = 20\text{V}$ $T_J = \text{Over Temp. Range } ^1$		8	12		8	12	A
$I_{SC}$ Short Circuit Current	$V_{IN} = 20\text{V}$		3.5			3.5		A
	$V_{IN} = 35\text{V}$		2			2		
$e_n$ Output Noise Voltage			90			90		$\mu\text{V}$
$R_{\theta JC}$ Thermal Resistance Junction to Case	K Package		1.0	1.5		1.0	1.5	$^\circ\text{C/W}$
	V Package		1.0	1.5		1.0	1.5	

**Notes**

- 1) Applies over full temperature range:–  
 $T_J = -55$  to  $+150^\circ\text{C}$  for IP1R18A-15 / IP1R18-15  
 $T_J = 0$  to  $+125^\circ\text{C}$  for IP3R18A-15 / IP3R18-15  
All other specifications apply at  $T_J = 25^\circ\text{C}$  unless otherwise stated.
- 2) Test conditions unless otherwise stated:–  
 $V_{IN} = 20\text{V}$  ,  $I_{OUT} = 2.5\text{A}$  .  
Although Power Dissipation is internally limited, these specifications apply for Power Dissipation up to 50W.
- 3) Load and Line regulation are electrically independent and are measured using pulse techniques at low duty cycle in order to maintain constant junction temperature. To determine the effects on the output voltage due to device heating, refer to thermal regulation specification.

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [seagate](#) manufacturer:*

Other Similar products are found below :

[ST1000NX0423](#)