





Neutral disconnect terminals

WNT 2.5

WNT 4

WNT 6

WNT 10



Max. technical data

Dimensions / approvals

Width/length/height (mm) with TS 35 x 7.5

Insulation stripping length/clamping screw/screwdriver blade

VDE rated data 0611 Part 5

Rated voltage/current/cross-section

Rated voltage/impulse voltage/pollution severity

Further technical data

Tightening torque range clamping screw / N disconnecter Nm

Torque setting with DMS 2 electric screwdriver

Clampable conductors

Solid H07V-U mm²

Stranded H07V-R mm²

Flexible H07V-K mm²

Flexible H07V-K and ferrule acc. to DIN 46 228/1 mm²

Flexible H07V-K and ferrules with plastic insul. collar mm²

Max. clamping range in mm²/Gauge pin acc. to 60 947-7-1 Size

Cont. current of cross-connect. 2-pole A

Cont. current of cross-connect. multi-pole A

UL/CSA rated data

Voltage/current/conductor size UL

Voltage/current/conductor size CSA

Ordering data Version

For busbar 10 x 3 Blue Wemid

For busbar 10 x 3 as PA disconnecter Dark beige Wemid (VDE 0107)

32 A/4 mm²

5/60/47

10 mm/M 2.5/3.5 x 0.6

400 V/24 A/2.5 mm²

400 V/6 kV/3

0.4...0.6 / 0.4...0.6

1

0.5...4

1.5...4

0.5...4

0.5...2.5

0.5...(2.5)

0.13...4

A 3

600 V/25 A/22...12 AWG

600 V/20 A/26...12 AWG

Type Cat. No. Qty.

WNT 2.5 1010680000 100

WNT 2.5 1010600000 100

41 A/6 mm²

6/60/47

10 mm/M 3/3.5 x 0.6

400 V/32 A/4 mm²

400 V/6 kV/3

0.5...1.0 / 0.4...0.8

2

0.5...6

1.5...6

0.5...6

0.5...4

0.5...4

0.13...6

A 4

600 V/35 A/22...10 AWG

600 V/35 A/26...10 AWG

Type Cat. No. Qty.

WNT 4 1010780000 100

WNT 4 1010700000 100

57 A/10 mm²

8/60/47

12 mm/M 3.5/4.0 x 0.8

400 V/41 A/6 mm²

400 V/6 kV/3

0.8...1.2 / 0.8...1.6

3

0.5...10

1.5...10

0.5...10

0.5...6

0.5...6

0.5...10

A 5

600 V/45 A/20...8 AWG

600 V/45 A/20...8 AWG

Type Cat. No. Qty.

WNT 6 1010880000 50

WNT 6 1010800000 50

76A/16 mm²

10/60/47

12 mm/M 4/5.5 x 1.0

400 V/57 A/10 mm²

400 V/6 kV/3

1.2...2.0 / 0.8...1.6

4

1.5...16

1.5...16 (16 mm² w. 2.4 Nm)

1.5...16

1.5...16

1.5...16

1.31...16

B 6

600 V/60 A/16...8 AWG

600 V/65 A/16...6 AWG

Type Cat. No. Qty.

WNT 10 1010980000 50

WNT 10 1010900000 50

End plate



Thickness 1.5 mm
Blue Wemid
Dark beige Wemid

WAP 2.5-10 1050080000 50

WAP 2.5-10 1050000000 50

WAP 2.5-10 1050080000 50

WAP 2.5-10 1050000000 50

WAP 2.5-10 1050080000 50

WAP 2.5-10 1050000000 50

WAP 2.5-10 1050080000 50

WAP 2.5-10 1050000000 50

Support plate



for SSch 10 x 3
Blue Wemid
Dark beige Wemid

Thickness 1.5 mm
Distance WHP-WHP max. 200mm

WHP 2.5-10 1050280000 20

WHP 2.5-10 1050200000 20

WHP 2.5-10 1050280000 20

WHP 2.5-10 1050200000 20

WHP 2.5-10 1050280000 20

WHP 2.5-10 1050200000 20

WHP 2.5-10 1050280000 20

WHP 2.5-10 1050200000 20

Busbar 10 x 3

Distance f. upper edge busbar to upper edge of TS 35 = 25.5 mm



Cu 140 A

SSch 10 x 3 Cu

0348900000 1 m

SSch 10 x 3 Cu

0348900000 1 m

SSch 10 x 3 Cu

0348900000 1 m

SSch 10 x 3 Cu

0348900000 1 m

Clamping yoke



Supply for SSch 10 x 3
16...50 mm² stranded
16...35 mm² flexible
Gauge pin B9

ZB 35 K

ZB 35

ZB 35 K 0502680000 20

ZB 35 0266500000 20

ZB 35 K 0502680000 20

ZB 35 0266500000 20

ZB 35 K 0502680000 20

ZB 35 0266500000 20

ZB 35 K 0502680000 20

ZB 35 0266500000 20

Test plug



PS 2.3 0180400000 20

PS 2.3 0180400000 20

PS 2.3 0180400000 20

PS 2.3 0180400000 20

End bracket

WEW 35 / 2 1061200000 50

WEW 35 / 2 1061200000 50

WEW 35 / 2 1061200000 50

WEW 35 / 2 1061200000 50

Bridge on the external side

Cross-section of connection is reduced by one level

Marking tags



DEK

WS

DEK Standard

WS White neutral

WS indiv. printed

DEK 5 see "Accessories"

WS 12/5 1609860000 720

WS 12/5 1773380000 300

DEK 6 see "Accessories"

WS 12/6 1609900000 600

WS 12/6 1609910000 120

DEK 8 see "Accessories"

WS 12/6.5 1609920000 540

WS 12/6.5 1609930000 108

DEK 8 see "Accessories"

WS 12/6.5 1609920000 540

WS 12/6.5 1609930000 108

Mounting rails, end brackets, further marking materials see "Accessories"

) Ferrules with opt. diameter for terminals with pitch of 5mm: Cat. No. 1333100000

Neutral disconnect terminals

WNT 16N



WNT 35N



WNT 70N



Max. technical data

Dimensions / approvals

Width/length/height (mm) with TS 35 x 7.5

Insulation stripping length/clamping screw/screwdriver blade

VDE rated data 0611 Part 5

Rated voltage/current/cross-section

Rated voltage/impulse voltage/pollution severity

Further technical data

Tightening torque range clamping screw / N disconnect Nm

Torque setting with DMS 2 electric screwdriver

Clampable conductors

Solid H07V-U mm²

Stranded H07V-R mm²

Flexible H07V-K mm²

Flexible H07V-K and ferrule acc. to DIN 46 228/1 mm²

Flexible H07V-K and ferrules with plastic insul. collar mm²

Max. clamping range in mm²/Gauge pin acc. to 60 947-7-1 Size

UL/CSA rated data

Voltage/current/conductor size UL

Voltage/current/conductor size CSA

Ordering data

For busbar 10 x 3 Version Blue Wemid

Support plate

for SSch 10 x 3 Blue Wemid
Dark beige Wemid



Thickness 1.5 mm
Distance WHP-WHP max. 200mm

Busbar 10 x 3

Cu 140 A

Distance f. upper edge busbar to upper edge of TS 35 = 25.5 mm

Clamping yoke

Supply for SSch 10 x 16...50 mm² stranded



ZB 35 K

ZB 35

Test plug



End bracket

Bridge on the external side

Cross-section of connection is reduced by one level

Marking tags

DEK Standard
WS White neutral
WS indiv. printed



DEK

WS

- / -
12/60/47
12 mm/M 4/5.5 x 1.0
400 V/76 A/16 mm ²
400 V/6 kV/3
1.2...2.2 / 0.8...1.6
4
1.5...16
1.5...25 (25 mm ² with 2.4 Nm)
1.5...16
1.5...16
1.5...16
1.5...25 B 7

Type	Cat. No.	Qty.
WNT 16N	1019000000	50

WHP 2.5-10	1050280000	20
WHP 2.5-10	1050200000	20

SSch 10 x 3 Cu	0348900000	1 m
----------------	------------	-----

ZB 35 K	0502680000	20
ZB 35	0266500000	20

PS 2.3	0180400000	20
--------	------------	----

WEW 35 / 2	1061200000	50
------------	------------	----

WQB-PEN16N	1079600000	10
------------	------------	----

DEK 5	see "Accessories"	
WS 12/6.5	1609920000	540
WS 12/6.5	1609930000	108

- / -
16/66/51
18mm/M 6/5.5 x 1.0
400 V/125 A/35 mm ²
400 V/6 kV/3
2.5...5 / 1.2...2.4
-
2.5...16
2.5...50
2.5...35
2.5...35
2.5...35
2.5...35 B 9

Type	Cat. No.	Qty.
WNT 35N	1718550000	20

WHP 2.5-10	1050280000	20
WHP 2.5-10	1050200000	20

SSch 10 x 3 Cu	0348900000	1 m
----------------	------------	-----

ZB 35 K	0502680000	20
ZB 35	0266500000	20

PS 2.3	0180400000	20
--------	------------	----

WEW 35 / 2	1061200000	50
------------	------------	----

WQB-PEN35N	1079500000	10
------------	------------	----

DEK 5	see "Accessories"	
WS 12/6.5	1609920000	540
WS 12/6.5	1609930000	108

207 A/95 mm ²
20.5/75/86
22 mm/M 8/S 6 DIN 6911
400 V/192 A/70 mm ²
400 V/6 kV/3
6.0...10 / 2.5...5
-
10...16
10...95
10...70
10...70
10...70
10...95 B 11

600 V/175 A/6...2/0 AWG

Type	Cat. No.	Qty.
WNT 70N	9512210000	10

WHP 2.5-10	1050280000	20
WHP 2.5-10	1050200000	20

SSch 10 x 3 Cu	0348900000	1 m
----------------	------------	-----

ZB 35 K	0502680000	20
ZB 35	0266500000	20

PS 4	0299600000	20
------	------------	----


WEW 35 / 2	1061200000	50
------------	------------	----

WQB-PEN70N	1079700000	10
------------	------------	----

DEK 5	see "Accessories"	
WS 12/6.5	1609920000	540
WS 12/6.5	1609930000	108

Mounting rails, end brackets, further marking materials see "Accessories"

TN-S-Circuit



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [weidmuller](#) manufacturer:

Other Similar products are found below :

[8924550000](#) [56956](#) [0133660000](#) [6720000227](#) [6720005111](#) [68676](#) [69718](#) [EXO24CH](#) [7760056106](#) [7760056348](#) [7940000218](#) [8005181001](#)
[8008180000](#) [8432240000](#) [8463580000](#) [8545830000](#) [8689870000](#) [8705640000](#) [9001080000](#) [9003720000](#) [9004250000](#) [9004780000](#)
[9013260000](#) [9014100000](#) [9019040000](#) [9026010000](#) [9028630000](#) [903708](#) [9037350000](#) [9046290000](#) [9129643500](#) [913155](#) [9159530000](#)
[919656](#) [919764](#) [9202230000](#) [9202850000](#) [9456750000](#) [9457913000](#) [980811](#) [980826](#) [9912800003](#) [9916080000](#) [9916280012](#) [9918380000](#)
[9919371205](#) [9919371224](#) [9925710000](#) [9927480024](#) [1166660000](#)