

# SKINTOP® accessories metric

Halogen-free counter nut



## SKINTOP® GMP-HF-M

### Application

The halogen-free counter nuts with metric thread are adapted in quality and workmanship to our metric SKINTOP® cable glands. For universal use if personal and property protection is a priority:

- Offices
- Public buildings
- Underground railways
- Tunnel construction
- Ventilation systems

- Industrial plants
- Warehouses
- Building services
- Ship and boat building

### Advantage

- Hexagonal counter nut
- Metric thread
- Extremely flame-retardant
- Halogen-free
- Self-extinguishing, no dripping

### Note

- Designed for use in connection with SKINTOP® ST-HF-M



### Technical Data



Note  
Dimension sheet available on request



Colour delivered  
RAL 7035 light grey



Material  
Polyamide UL94 V0 - halogen free



Range of temperature  
-20°C up to +100°C

Part number	Part designation / size	Width across flats mm	PU pieces
<b>SKINTOP® GMP-HF-M</b>			
53119200	12 x 1.5	17	100
53119210	16 x 1.5	22	100
53119220	20 x 1.5	27	100
53119230	25 x 1.5	34	100
53119240	32 x 1.5	41	100

# SKINTOP® ST-HF-M

Halogen-free cable gland in accordance with EN 50262 for fast assembly



## SKINTOP® ST-HF-M Completely halogen-free

### Application


The easy-to-assemble metric cable gland with the proven properties of the internationally well-known SKINTOP® glands. SKINTOP® ST-HF-M is suitable for universal use when personal and property protection is a priority.

- Offices
- Public buildings
- Underground railways

- Tunnel construction
- Ventilation systems
- Industrial plants
- Warehouses
- Building services
- Ship and boat building

### Advantage

- Maximum reliability
- Metric thread
- Extremely flame-retardant
- Completely halogen-free
- Self-extinguishing, no dripping
- Permanent vibration protection



## Technical Data

⚠ Caution  
Installation dimensions and  
tightening torques  
see T21

📄 Approvals  
VDE / EN 50262  
Filament wire test  
EN 60695-2-1/1  
+960°C

🎨 Colour delivered  
RAL 7035 light grey

🛡 Degree of protection  
IP 68

🏠 Material  
Polyamide UL94 V0 - halogen free  
Seal: LSE 1 - halogen free  
O-ring: LSE 1 - halogen free

🌡 Range of temperature  
-20°C up to +100°C

Part number	Part designation / size	Clamping range F mm	SW mm	C mm	D mm	PU pieces
<b>SKINTOP® ST-HF-M</b>						
53111407	ST-HF-M 12 x 1.5	4 - 5,5	15	30	8	100
53111417	ST-HF-M 16 x 1.5	4,5 - 9	19	34	8	100
53111427	ST-HF-M 20 x 1.5	7 - 13	25	37	9	100
53111437	ST-HF-M 25 x 1.5	9 - 17	30	40	10	50
53111447	ST-HF-M 32 x 1.5	11 - 21	36	47	10	25

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Wire Identification category](#):*

*Click to view products by [Lapp Kabel manufacturer](#):*

Other Similar products are found below :

[CU6337-000](#) [CU6342-000](#) [FCA-410-12](#) [11631010](#) [1-1768037-1](#) [1-1768037-2](#) [1-1768050-0](#) [PXLK-VI](#) [Q62184-1](#) [A64304-000](#) [QMT221](#)  
[HK032WE1NF038B](#) [1330-0519-10](#) [1395199-1](#) [1395200-1](#) [1395202-1](#) [DMVF050WE-300S6](#) [D-SCE-1K-2.4-50-4-CS7834](#) [1538738-1](#)  
[E90935-000](#) [EC1238-000](#) [EC1465-000](#) [EC1855-000](#) [EC1859-000](#) [EC1863-000](#) [EC5415-000](#) [EC7277-000](#) [EC7352-000](#) [EC7603-000](#)  
[EC7707-000](#) [EC7735-000](#) [EC7768-000](#) [EC7828-000](#) [EC7854-000](#) [EC7952-000](#) [EC8128-000](#) [1768037-8](#) [1768041-7](#) [NC-127191-10-9](#)  
[HS048WE2NF038B](#) [C03232-000](#) [HTCM-SCE-14-4H-9](#) [HTMS-3/16-9](#) [HT-SCE-1/4-2.0-4](#) [HT-SCE-3/16-2.0-4](#) [HTTMS-1/2-1.50-9](#) [HTTMS-](#)  
[CM-1/2-4H-9](#) [HX-SCE-19.0-50-9](#) [HX-SCE-6.4-50-4](#) [C25254-000](#)