


343-1850  
343-1861  
343-1873 1/1  
Data sheet

# Interface Module

Interface module for ribbon cable acc. to IEC 603-1 / DIN 41651



Description		Item-No.	Pack.-unit pcs
Interface module	No. of poles: 10 Dimensions "L": 35 mm / 1.38 in	289-611	1
with male connector	14: 40 mm / 1.57 in 16: 45 mm / 1.77 in	289-612 289-613	1 1
<p>Interface module with male connector for female connector with IDC acc. to DIN 41651 part 1 and 2. Short and long latches for the female connector, with and without strain relief, are shipped loose.</p> <ul style="list-style-type: none"> <li>• Mounting carrier for DIN 35 rail with lateral marking system.</li> <li>• Marking with the WMB multi marking system or with marking strips with cover.</li> </ul>		<b>Technical Data</b>	
		Operating voltage	AC/DC 125 V
		Nominal current	1 A
		Connector contact	Phosphor-bronze
			0.38 µm Au selectively over 1.3 µm Ni
		Performance level	3
		Nominal voltage acc. to VDE 0110/189	125 V / 1.5 kV / 2
		Dimensions incl. mounting carrier (LxWxH)	(Lx3.35x1.69") in (Lx85x46*) mm (Lx3.35x1.69") in * from upper edge of DIN 35 rail
		Wire connection	WAGO series 736 CAGE CLAMP® terminal strips 0.08-2.5 mm² / AWG 28-12 ** ** AWG12: THHN, THWN
		Stripped length	5.6 mm / 0.22 in
		Mating direction	vertical
		Ambient operating temperature	-20 °C...+55 °C
		Storage temperature	-40 °C...+70 °C
		Standards / prescriptions	IEC 603-1 / DIN 41651 Part 1 and 2

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [efl](#) manufacturer:*

Other Similar products are found below :

[EFL](#)