



NOTES:

1. Rating: 300V 8A (IEC 250V 10A)  
PITCH: 5.00mm
2. Insulation Withstands Voltage:  
AC 2000V/MIN
3. Insulation Resistance:  
500M $\Omega$  or more at DC500V
4. Using Temperature Range:  
-40°C~+105°C
5. Screw Torque Value: 4 kg-cm
6. Suitable Electric Wire: AWG 26~14  
(0.5~1.5mm<sup>2</sup>)
7. Undimensioned Tolerances:

-	∧	□	0.05/10
⊥	//	≡	0.2/10
PITCH ERROR			0.05/10
UNDIMENSIONED TOLERANCES			±0.3

P	2	3	4	5	6	7	8	9	10	11	12	13	14
U	5.00	10.00	15.00	20.00	25.00	30.00	35.00	40.00	45.00	50.00	55.00	60.00	65.00
V	10.00	15.00	20.00	25.00	30.00	35.00	40.00	45.00	50.00	55.00	60.00	65.00	70.00
P	15	16	17	18	19	20	21	22	23	24	25	26	
U	70.00	75.00	80.00	85.00	90.00	95.00	100.0	105.0	110.0	115.0	120.0	125.0	
V	75.00	80.00	85.00	90.00	95.00	100.0	105.0	110.0	115.0	120.0	125.0	130.0	

Tolerances For PITCH ERROR

4	SOLDER PIN	0082BD0100	P	BRASS	Tin Plated
3	CLAMP	0012BD0600	P	Stainless Steel	
2	SCREW	S000004800	P	STEEL	M2.5 Zn Plated
1	HOUSING	0082A0XX00	1	PA66(V2)	GREEN
ITEM	NAME OF PART	NO. OF PART	Q'TY	MATERIAL	NOTES
DWG.		DATE	99,11,25	UNITS	MM SHEET/OF 1/2
CHK.		DATE		SCALE	3:1 ( : )
APP.		DATE		NAME	20.590M/XX
				DWG NO.	

△		梁紅英	01.5.30
REV.	CONTENT	CHK.	DATE



## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [imo manufacturer](#):*

Other Similar products are found below :

[20.155MV/12-E](#) [MC14N-S-10110AC](#) [MB09-S-10=24](#) [DPS-1-030-24](#) [SRF-1C-SL-12VDC](#) [MB09-S-1024](#) [LDC18RRS](#) [SFSYE0111](#)  
[21.1500M/6-E](#) [20.3304M/2-E](#) [21.910M/5-E](#) [20.95MA/2-E](#) [21.95MHF/2-E](#) [PE69-4032](#) [DPS-1-060-24](#) [CS20A-A2](#) [CS20A-U1](#) [VFC02](#)  
[MSSTC11DA06](#) [20.95MHF/3-E](#) [B3T10](#) [XKL-040-21](#) [20.3304M/4-E](#) [SRDH-1A-SL-24VDC](#) [20.2500M/5-E](#) [21.155MH/12](#) [SRRHN-2CN-](#)  
[SL-12VDC](#) [QYE21XXF24DC](#) [20.920M/5-E](#) [MC10N-S-10110AC](#) [21.1550MF/8-E](#) [20.910M/6-E](#) [20.95MH/3-E](#) [21.95MV/3](#) [MA05-S-](#)  
[01230AC](#) [SRRHN-2CN-SL-5VDC](#) [LB69-4040](#) [20.3001M/6](#) [21.1500M/3-E](#) [SFSYE0311](#) [21.95MHF/6-E](#) [20.95MV/2-E](#) [20.155MV/4-E](#)  
[20.155MH/4-E](#) [20.950M/2-E](#) [MT5 1-50-FAR](#) [BS3P3REDO](#) [MB12-S-10=24](#) [MA05-S-1024DC](#) [20.155MVF/8-E](#)