



Drawings not to scale  
All dimensions in mm

## SPECIFICATION

CONTACT FORM / STYLE		Normally Open
SWITCHING VOLTAGE	Max. Vac RMS	60
SWITCHING CURRENT	Max. A	0.25
SWITCHING CAPACITY	Max. VA	3
OPERATING ANGLE	Deg.°	60° ± 10°
CONTACT RESISTANCE	Max. mΩ	5
OPERATING TEMPERATURE	Deg. °C	-37° +10°
STORAGE TEMPERATURE	Deg. °C	-40° +125°
CASE MATERIAL		Steel Tin Plated
CABLE / TERMINATION		1 Pin

**TIP-OVER SWITCH - Mercury Free**

PART NUMBER  
**CW1260-0**

Rev. No.	Revision Note	Date	Signature
A	Web Site 1999	1-5-99	RG

The Comus Group of Companies consist of:  
Assemtch Europe Limited  
E. Bachem GmbH  
Comus International  
W. Gunther GmbH  
Gunther Belgium  
Gunther France  
S.T.G.

As part of the company policy of continued product improvement, specifications may change without notice. Our sales office will be pleased to help you with the latest information on this product range and details of our full design and manufacturing service. All products are supplied to our standard conditions of sale otherwise agreed in writing.

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [comus](#) manufacturer:*

Other Similar products are found below :

[WGA56D25Z](#) [WG660D110Z](#) [WG280A25Z](#) [PGN-SP-003](#) [WG660D10Z](#) [WGA316D25R](#) [WG660D90Z](#) [S1456](#) [S1366](#) [S1355](#) [WGA316D45R](#)  
[3570.1331.121](#) [WG280D90Z](#) [WGA312D25Z](#) [WG280D10R](#) [3572.1220.051](#) [WG660D125Z](#) [WGA56A10Z](#) [CTC 012](#) [CTI 302](#)  
[RF3002A/HFS30](#) [WG280D90R](#) [WG280A10Z](#) [WGA012D25](#) [WG660D25Z](#) [MS24](#) [PPS24](#) [3570.1411.053](#) [VFS30](#) [WG280D45R](#)  
[WG480D75Z](#) [WG660D75Z](#) [WGA56D25R](#) [PGN-SP-002](#) [WGA56D40Z](#) [WG660D50Z](#) [WG280D50Z](#) [WGA56A25Z](#) [WG280D75Z](#) [PSM](#)  
[S1747](#) [WG480D90Z](#) [WG480D40Z](#) [WG280A45Z](#) [MMPSA 240/30 LH](#) [PSSM](#) [MPSM](#) [3563.1231.053](#) [WGA56D10Z](#) [WG280D45Z](#)