

#### General ordering data

Order No.	0380480000
Short text for material	SAK 2.5/35 BL
EAN	4008190131869
Qty	100

#### IEC/EN 60079-7 rating data

Certificate No.	KEMA97ATEX1798U
max. voltage	550 V
Current	21 A
Conductor cross-section, max.	2 mm <sup>2</sup>
Marking EN 60079-7	Ex e II
Marking ATEX Directive 94/9/EC	Ex II 2 G D

#### Additional technical data

No. of identical terminals	1
Type of connection	screwed
Type of mouting	clipped
Version	Feed-through terminal
Installation advice	TS 35
UL 94 flammability rating of insulation material	V2
Insulating material	PA 66
Colour of insulating material	blue
Operating temperature range	- 50 °C, + 100 °C
Open sides	right
No. of levels	1
No. of terminal strips per level	2
Levels cross-connected internally	No
End plate required	Yes
Explosion-tested version "Ex e"	No
Connection direction	on side

#### CSA rating data

Voltage CSA	600 V
CSA current	25 A
Max. cross-section (CSA)	AWG 10
Min. cross-section (CSA)	AWG 26

### Conductors for clamping (rated connection)

Stripping length	10 mm
Type of connection	Screw connection
No. of connections	2
Tightening torque range	0.4...0.6 Nm
Solid, max.	6 mm <sup>2</sup>
Twin wire end ferrule, max.	1,50 mm <sup>2</sup>
Connection direction	on side
Flexible, min.	0,5 mm <sup>2</sup>
2nd type of connection	screwed
Solid, min.	0,5 mm <sup>2</sup>
Twin wire-end ferrule, min.	0,50 mm <sup>2</sup>
Torque level with DMS electric screwdriver	1
Flexible, max.	4 mm <sup>2</sup>
flexible w. ferrule AEH, max. DIN 46228-1	4 mm <sup>2</sup>
Flexible, max., ferrule with plastic collar (DIN 46228 pt 4)	4 mm <sup>2</sup>
flexible w. ferrule AEH, min. DIN 46228-1	0,5 mm <sup>2</sup>
Flexible, min., ferrule with plastic collar (DIN 46228 pt 4)	0,5 mm <sup>2</sup>
Clamping range, max.	6 mm <sup>2</sup>
Clamping range, min.	0,13 mm <sup>2</sup>
Clamping screw	M 2.5
Blade size	0.6 x 3.5 mm
Gauge to IEC 60947-1	A3
AWG conductor size, max.	5,26 mm <sup>2</sup>
Stranded, max.	4 mm <sup>2</sup>
Stranded, min.	0,5 mm <sup>2</sup>
AWG conductor size, min.	AWG 26

### Dimensions

Length	44,1 mm
Height of lowest version	40 mm
Width	6,1 mm

### Disconnect terminals

Torque level with DMS electric screwdriver	1
--	---

### Rating data

Rated cross-section	2,5 mm <sup>2</sup>
Rated voltage	800 V
Rated impulse withstand voltage	8 kV
Rated current	24 A
Norm	IEC 60947-7-1
Current with max. conductor	41 A
Pollution severity	3

### UL rating data

Voltage UL	600 V
Current (UL)	20 A
Min. cross-section (UL)	AWG 22
Max. cross-section (UL)	AWG 12

### Approvals

Approvals



### Approvals

Approvals



### Classifications

ETIM 2.0	EC000897
ETIM 3.0	EC000897
eClass 4.1	27-14-11-20
eClass 5.0	27-14-11-20
eClass 5.1	27-14-11-20

### Related products

Order No.	Short text for material
0499560000	SAK 2.5/10/35
0380460000	SAK 2.5/35
0380440000	SAK 2.5/35 OR
0268860000	SAKD 2.5/35
0268880000	SAKD 2.5/35 BL

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [weidmuller](#) manufacturer:*

Other Similar products are found below :

[56956](#) [0133660000](#) [68676](#) [69718](#) [EXO24CH](#) [7940000218](#) [8005181001](#) [8008180000](#) [8432240000](#) [8463580000](#) [8545830000](#) [8689870000](#)  
[8705640000](#) [9001080000](#) [9003720000](#) [9004250000](#) [9004780000](#) [9013260000](#) [9014100000](#) [9019040000](#) [9026010000](#) [9028630000](#) [903708](#)  
[9037350000](#) [9046290000](#) [9129643500](#) [913155](#) [919656](#) [919764](#) [9202230000](#) [9202850000](#) [9204260000](#) [9456750000](#) [9457913000](#) [980811](#)  
[980826](#) [9912800003](#) [9916080000](#) [9916280012](#) [9918380000](#) [9919371224](#) [9925710000](#) [9926252005](#) [9927480024](#) [1166660000](#) [11751](#)  
[1222550000](#) [ACT20X-2HDI-2SDO-RNC-S](#) [ACT20X-HUI-SAO-S](#) [ACT20X-SAI-HAO-S](#)