

R&S® HMC8015 Power Analyzer

All in one: the new
compact class that
has it all




ROHDE & SCHWARZ

Test & Measurement

Product Brochure | 01.00

R&S®HMC8015 Power Analyzer At a glance

The R&S®HMC8015 power analyzer is the first compact tester for AC/DC load and standby current characterization that enables measurements without additional tools such as a computer or remote infrastructure. In addition to a numerical and graphical display with 26 key parameters, the instrument delivers performance and compliance protocols in line with IEC 62301, EN 50564 and EN 61000-3-2.

The power analyzer is the only instrument in its class that graphically displays harmonic analysis up to the 50th harmonic on the logarithmic scale. Its user-configurable, dual-channel trend chart function for U, I, P, S, Q and F etc. is unique as well. The instrument's 5 V measurement range provides embedded developers with a previously unattainable level of resolution for power and energy measurements.

The R&S®HMC8015 also sets new standards when it comes to documentation. It simultaneously displays up to 10 user-configurable measurands with a refresh rate of 10 measurements per second. A logging function makes it possible to store this data with a timestamp in CSV format

for a nearly unlimited period of time. Screen content can also be saved to a USB flash drive anytime at the push of a button.

A PASS/FAIL function enables users to monitor numerous measurands either on the instrument's display or externally via an analog/digital output on the rear panel. The inrush function captures and graphically displays inrush current and voltage waveforms.

The instrument's standard hardware-based integrator delivers highly precise, seamless power consumption analysis and adds up watt and ampere hours according to polarity. An additional sensor input for a current probe or shunt expands the tester's current measurement range as required. A three-stage filter in the voltage and current circuit of the acquisition system can be activated, if necessary.

The LXI-Core 1.4-compliant power analyzer can be remotely controlled via an Ethernet, USB or GPIB interface (R&S®HMC8015-G). The commands are based entirely on the SCPI standard. The virtual COM port and the test and measurement class (TMC) are supported for communications via USB. Cost-free driver packages for LabVIEW, LabWindows/CVI, VXI and IVI.net are also available for fast, complication-free integration of the R&S®HMC8015 into existing systems.

Key facts

- Power measurement range: 50 μ W to 12 kW
- Analog bandwidth: DC to 100 kHz
- Sampling rate: 500 ksample/s
- 16-bit resolution for current and voltage
- Basic accuracy: 0.05%
- 26 different measurement and mathematical functions



2



R&S®HMC8015 Power Analyzer Benefits and key features

Clear display of all measured parameters

- Brilliant QVGA color display (320 x 240 pixel)
- Simultaneous display of up to 10 numerical measurement functions
- User-configurable measurement display
- Graphical display modes ¹⁾ for inrush, harmonic analysis, waveform and trend chart

Measurement accuracy

- Basic accuracy: 0.05%
- Signal acquisition from DC to 100 kHz at a sampling rate of 500 ksample/s
- Simultaneous display of current and voltage, each with 16-bit resolution
- Three-stage filter system adaptable to the measurement task at hand
- Long-term data logging in CSV format via USB flash drive

Everyday measurement functions

- Genuine consumption meter thanks to hardware-based integrator
- 26 different measurement and mathematical functions
- Limit testing with PASS/FAIL indication ²⁾ for up to six limits selectable from 14 measurands (e.g. U, I, P, S, Q, F)

Ports and extensibility

- Front panel: 4 mm safety connectors
- Rear panel: 4 BNC ports ²⁾ for analog and digital inputs and outputs
- Additional sensor input ²⁾ for current probe or shunt
- USB port (virtual COM port, TMC)
- Ethernet port (LXI) with integrated web server
- IEEE-488 (GPIB) port (R&S®HMC8015-G)
- Compliance test ³⁾ for key standby and harmonic standards
- Remote control via SCPI-based commands
- Driver packages for LabVIEW, LabWindows/CVI, VXI, IVI.net

¹⁾ With HVC151 advanced analysis option.

²⁾ With HVC152 advanced I/O option.

³⁾ With HVC153 compliance test option.

Enhanced functions

As seen in the table, up to three options can be added to the base unit. They can be ordered directly from the factory (HOC15x) or at later time (HVC15x) as a voucher.

HOC151/HVC151 advanced analysis option

The advanced analysis option complements the base unit's measurands by also displaying peak values for voltage, current and power. These are acquired seamlessly at the full sampling rate of 500 ksample/s. The following additional graphic functions are available:

Inrush function

The inrush function makes it possible to graphically display switch-on behavior (see picture on next page). Triggering can be either manual or edge-based (pos./neg.) when user-defined voltage or current thresholds are reached. 8192 samples are acquired at all times with a logging period of 16 ms to 67 s.

| Function | Description | Base unit R&S®HMC8015 | Opt./voucher HOC/HVC151 | Opt./voucher HOC/HVC152 | Opt./voucher HOC/HVC153 |
|--|---|--------------------------|----------------------------|----------------------------|----------------------------|
| P | Active power (W) | • | | | |
| S | Apparent power (VA) | • | | | |
| Q | Reactive power (var) | • | | | |
| PF | Lambda power factor (λ) | • | | | |
| PHI | Phase shift (ϕ) | • | | | |
| FU | Voltage frequency value (Hz) | • | | | |
| FI | Current frequency value (Hz) | • | | | |
| FPLL | Acquisition frequency (Hz) | • | | | |
| URMS | RMS voltage (U RMS) | • | | | |
| UAVG | Average voltage (U AVG) | • | | | |
| IRMS | RMS current (I RMS) | • | | | |
| IAVG | Average current (I AVG) | • | | | |
| UTHD | Total harmonic distortion U | • | | | |
| ITHD | Total harmonic distortion I | • | | | |
| WHM, WHP, WH, AHM, AHP, AH | Energy counter (integrator values) | • | | | |
| Logging | Measured value logging (CSV) | • | | | |
| USB, Ethernet (GPIB optional - R&S®HMC8015-G) | Remote control interfaces | • | | | |
| UPPeak | Maximum voltage (U PEAK) | | • | | |
| UMPeak | Minimum voltage (U PEAK) | | • | | |
| IPPeak | Maximum current (I PEAK) | | • | | |
| IMPeak | Minimum current (I PEAK) | | • | | |
| PPPeak | Maximum power (P PEAK) | | • | | |
| PMPeak | Minimum power (P PEAK) | | • | | |
| Harmonics | Bargraph of up to 50 harmonics | | • | | |
| Waveform | Waveform display (displays one period of voltage, current or power) | | • | | |
| Trend chart | Current and voltage displayed as a waveform | | • | | |
| Inrush | Triggered display of waveform (single shot) | | • | | |
| Sensor input | Input for current probe/external shunt | | | • | |
| DIN/AIN | Digital/analog inputs and outputs (BNC) | | | • | |
| Limit/PASS-FAIL | Limit display | | | • | |
| IEC62301 | Standby standard | | | | • |
| EN50564 | Extended standby standard | | | | • |
| EN61000-3-2 | Harmonic current for EMC, CE approval | | | | • |

Harmonic analysis

Harmonic analysis can be displayed in a table or graph or even logarithmically for better readability. The bargraph can optionally show up to the 50th harmonic of voltage and/or current. The bargraph shows the amplitude of the harmonic selected with the cursor.

Waveform function


The waveform function shows the voltage, current and power of an input signal period over time. The example shows a load with phase-angle control.

Trend chart function

The trend chart function makes it possible to observe longer periods of time and can be displayed on up to two channels. 15 selectable measurands are available, e.g. U, I, P, S, Q, F. The y-axis is scaled in line with progress. The time axis can be varied from 5 s/div to 10 min/div.




Inrush function.




Harmonic analysis: bargraph.

| Order | U[V] | Phi(U)[°] | I[A] | Phi(I)[°] |
|-------|-------|-----------|--------|-----------|
| 1 | 231.9 | -0.0 | 261.8m | 0.6 |
| 3 | 1.7 | 41.5 | 15.5m | -141.6 |
| 5 | 6.1 | -163.6 | 21.0m | -172.8 |
| 7 | 2.0 | -11.7 | 11.7m | 124.0 |
| 9 | 1.3 | -160.2 | 9.4m | 101.6 |
| 11 | 0.3 | -122.1 | 8.0m | 48.3 |
| 13 | 0.4 | 51.6 | 6.4m | 6.2 |
| 15 | 0.7 | -179.3 | 5.1m | -66.2 |
| 17 | 0.2 | 69.2 | 4.0m | -115.5 |
| 19 | 0.4 | 94.8 | 4.4m | -177.0 |
| 21 | 0.2 | -150.2 | 3.6m | 138.9 |
| 23 | 0.2 | -4.2 | 3.9m | 78.9 |

Harmonic analysis: tabular display.



Waveform function: load with phase-angle control.



Trend chart function.

HOC152/HVC152 advanced I/O option

The advanced I/O option activates the following additional functions:

Sensor input

A current-proportional voltage of 100 mV, 1 V or 4 V (full-scale amplitude) can be applied to the sensor input (4 mm safety connectors) in order to significantly expand the power measurement range. Current probes, current transformers and shunts can be connected to the input. The gradient (e.g. mV/A) can be set individually.

PASS/FAIL function

The PASS/FAIL function can be used to monitor up to six user-defined (upper or lower) limits, which can be selected from a total of 14 measurands (e.g. U, I, P, S, Q, F). The results appear on the display or are transferred to another device connected via the analog or digital output on the rear panel. The analog output delivers voltage proportional to the limits (± 5 V).

Four BNC ports on the rear panel can be assigned to various sources/sinks. The analog output allows users to choose either limits (PASS/FAIL) or measurands U, I or P as a source.

The signal at the analog input (± 10 V) can be displayed on the screen with 16-bit resolution as well. The digital output can be assigned to the limit (PASS/FAIL) or the measurement frequency used. The signal at the digital input is available as additional information on the display as status (0/1), frequency (up to 200 kHz) or PWM (0 to 100%). Both inputs are loggable.

HOC153/HVC153 compliance test option ¹⁾

This option includes wizards for the IEC 62301 (standby), EN 50564 (extended standby) and EN 61000-3-2 (harmonic current for EMC, CE approval) standards, making it possible to carry out autonomous measurements without PC. The results are displayed in a table on the screen and can be saved to a USB flash drive in HTML format.

Optional accessories

The HZC50 (30 A) and HZC51 (1000 A) AC/DC current probes significantly extend the power measurement range of the R&S®HMC8015. Current probes are connected to the sensor input using a 4 mm safety connector.

The HZC815 adapter makes it easy and safe to connect a DUT to the R&S®HMC8015. The DUT is powered via the installation connector on the top of the adapter.


¹⁾ In development.



HZC51 AC/DC current probe.



R&S®HMC8015 power analyzer with the HZC815 adapter.



DE, UK, CHN/AUS and US versions of the HZC815.

Specifications

| Specifications | | |
|-----------------------------|-------------------------------------|---|
| Analog bandwidth | | DC to 100 kHz |
| Frequency accuracy | | 0.1 % of reading |
| A/D converter resolution | voltage and current | 16 bit |
| Basic accuracy | | 0.05 % of reading |
| Display resolution | | 5 digits, 10 updates/s |
| Sampling frequency | | 500 kHz |
| Input impedance | | 2 M Ω |
| PLL synchronization sources | | U, I, external |
| Filters | | |
| Analog signal filter | | 1 kHz |
| Digital filter | depends on measurement frequency | adaptive filter |
| Frequency filter | independent of analog signal filter | 500 Hz |
| Additional inputs/outputs | | |
| Analog input | | ± 10 V (U peak) |
| Analog input accuracy | | 0.5 % of reading |
| Analog output | | ± 5 V (U peak) |
| Digital input | | |
| Limits (PASS/FAIL) | bandwidth | 100 kHz |
| | PWM | 1 kHz |
| | state | ≤ 10 Hz |
| Signal threshold | logical zero | 0 V to 2 V |
| | logical one | 3 V to 24 V |
| Digital output | up to 100 mA source/sink | 5 V, TTL |
| Display | | 8.9 cm (3.5") TFT (color) 320 x 240 pixel (QVGA) |
| Network connection | AC | 100 V to 115 V/230 V at 50 Hz to 60 Hz |
| Power consumption | | max. 35 W, typ. 15 W |
| Operating temperature range | | +5 °C to +40 °C |
| Storage temperature range | | -25 °C to +60 °C |
| Standards | | CAN/CSA-C22.2 NO. 61010-1, UL 61010-1, DIN EN61010-1, DIN EN61326-1, DIN EN55011 |
| Common mode voltage | | CAT II, 600 V (U RMS) |
| Dimensions | | 222 mm x 88 mm x 280 mm (8.74 in x 3.46 in x 11.02 in) |
| Weight | | approx. 3.25 kg (7.16 lb) |
| Warm-up time | | 60 min |

All specifications refer to a sine reference signal, PF = 1, voltage to ground = 0 V, analog filter deactivated, digital filters activated and are valid for measurement values > 1 % of measurement range.



Rear panel interfaces (shown here:
R&S®HMC8015-G with GPIB interface).

Measurement ranges and accuracy

Measurement ranges

| | CF3 | CF6 | Peak value |
|------------------|---------|----------|------------|
| Voltage | 5 V | 2.5 V | ±15 V |
| | 15 V | 7.5 V | ±45 V |
| | 30 V | 15 V | ±90 V |
| | 60 V | 30 V | ±180 V |
| | 150 V | 75 V | ±450 V |
| | 300 V | 150 V | ±900 V |
| | 600 V | 300 V | ±1800 V |
| Current (500 mΩ) | 5 mA | 2.5 mA | ±15 mA |
| | 10 mA | 5 mA | ±30 mA |
| | 20 mA | 10 mA | ±60 mA |
| | 50 mA | 25 mA | ±150 mA |
| | 100 mA | 50 mA | ±300 mA |
| | 200 mA | 100 mA | ±600 mA |
| Current (10 mΩ) | 0.5 A | 0.25 A | ±1.5 A |
| | 1 A | 0.5 A | ±3 A |
| | 2 A | 1 A | ±6 A |
| | 5 A | 2.5 A | ±15 A |
| | 10 A | 5 A | ±30 A |
| | 20 A | 10 A | ±60 A |
| Sensor | 0.033 V | 0.0165 V | ±0.1 V |
| | 0.33 V | 0.165 V | ±1 V |
| | 1.33 V | 0.665 V | ±4 V |

Measurement accuracy (± displayed in % ± peak value range in %)

| Frequency | Voltage | Current/sensor | Active power |
|----------------------|------------------------|------------------------|------------------------|
| DC | 0.05 + 0.05 | 0.05 + 0.05 | 0.05 + 0.05 |
| f < 45 Hz | 0.05 + 0.05 | 0.05 + 0.05 | 0.075 + 0.075 |
| 45 Hz < f < 66 Hz | 0.05 + 0.05 | 0.05 + 0.05 | 0.05 + 0.05 |
| 66 Hz < f < 1 kHz | 0.05 + 0.1 | 0.05 + 0.1 | 0.075 + 0.075 |
| 1 kHz < f < 10 kHz | (0.1 + 0.02 · F) + 0.1 | (0.1 + 0.03 · F) + 0.1 | (0.1 + 0.07 · F) + 0.1 |
| 10 kHz < f < 100 kHz | (0.1 + 0.04 · F) + 0.1 | (0.1 + 0.04 · F) + 0.2 | (0.1 + 0.07 · F) + 0.1 |

Voltage, current: F = frequency in kHz

Sensor input: F = frequency in kHz · 2

Additional measurement uncertainties

| | | | |
|-------------------|----------------------------|---|--------------------|
| Power factor < 1 | – | – | ±(0.2 + 0.2 · F) % |
| Common mode error | ±0.01% of peak value range | | |

These specifications apply between +20°C and +30°C at 80% relative humidity after 60 min of warm-up time.

Ordering information

| Designation | Type | Order No |
|---|----------------|--------------|
| Base unit (incl. power cable and manual) | | |
| Power Analyzer | R&S®HMC8015 | 3593.8646.02 |
| Power Analyzer, with IEEE-488 (GPIB) interface | R&S®HMC8015-G | 3593.8875.02 |
| Software options (firmware) | | |
| Advanced Analysis, voucher upgrade | HVC151 | 3622.0795.02 |
| Advanced Analysis, factory direct order | HOC151 | 3622.0789.02 |
| Advanced I/O, voucher upgrade | HVC152 | 3622.3788.02 |
| Advanced I/O, factory direct order | HOC152 | 3622.3542.02 |
| Compliance Test, voucher upgrade | HVC153 | 3622.3794.02 |
| Compliance Test, factory direct order | HOC153 | 3622.3559.02 |
| External accessories (additional equipment, peripherals, etc.) | | |
| Network Adapter for R&S®HMC8015, EU connector | R&S®HZC815-EU | 3593.8850.02 |
| Network Adapter for R&S®HMC8015, GB connector | R&S®HZC815-GB | 3622.2246.02 |
| Network Adapter for R&S®HMC8015, US connector | R&S®HZC815-USA | 3622.2252.02 |
| Network Adapter for R&S®HMC8015, CHN/AUS connector | R&S®HZC815-CHN | 3623.3952.02 |
| 19" Rackmount Kit, 2 HU, for R&S®HMC family | R&S®HZC95 | 5800.2054.02 |
| AC/DC Current Probe, 30 A, 4 mm connectors | R&S®HZC50 | 3622.4690.02 |
| AC/DC Current Probe, 1000 A, 4 mm connectors | R&S®HZC51 | 3622.4684.02 |



Service that adds value

- | Worldwide
- | Local and personalized
- | Customized and flexible
- | Uncompromising quality
- | Long-term dependability

About Rohde & Schwarz

The Rohde & Schwarz electronics group offers innovative solutions in the following business fields: test and measurement, broadcast and media, secure communications, cybersecurity, radiomonitoring and radiolocation. Founded more than 80 years ago, this independent company has an extensive sales and service network and is present in more than 70 countries. The electronics group is among the world market leaders in its established business fields. The company is headquartered in Munich, Germany. It also has regional headquarters in Singapore and Columbia, Maryland, USA, to manage its operations in these regions.

Sustainable product design

- | Environmental compatibility and eco-footprint
- | Energy efficiency and low emissions
- | Longevity and optimized total cost of ownership

Certified Quality Management

ISO 9001

Certified Environmental Management

ISO 14001

Rohde & Schwarz GmbH & Co. KG

www.rohde-schwarz.com

Rohde & Schwarz training

www.training.rohde-schwarz.com

Regional contact

- | Europe, Africa, Middle East | +49 89 4129 12345
customersupport@rohde-schwarz.com
- | North America | 1 888 TEST RSA (1 888 837 87 72)
customer.support@rsa.rohde-schwarz.com
- | Latin America | +1 410 910 79 88
customersupport.la@rohde-schwarz.com
- | Asia Pacific | +65 65 13 04 88
customersupport.asia@rohde-schwarz.com
- | China | +86 800 810 82 28 | +86 400 650 58 96
customersupport.china@rohde-schwarz.com

R&S® is a registered trademark of Rohde & Schwarz GmbH & Co. KG
 Trade names are trademarks of the owners
 PD 3607.3374.12 | Version 01.00 | February 2016 (gk)
 R&S®HMC8015 Power Analyzer
 Data without tolerance limits is not binding | Subject to change
 © 2016 Rohde & Schwarz GmbH & Co. KG | 81671 Munich, Germany



3607337412

3607.3374.12 01.00 PDF 1 en



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [rohde & schwarz](#) manufacturer:

Other Similar products are found below :

[HMF2525](#) [HMP2020](#) [HMP2030](#) [RT-ZP03](#) [HZ24](#) [HV512](#) [HMC8041](#) [RTC1K-102](#) [RTC1K-202](#) [HA-Z211](#) [RTB2002 \(RTB2K-72\)](#) [RTB2004](#)
[+ RTB-B241 \(RTB2K-104\)](#) [RTM-B222](#) [RTM-B223](#) [RTM-B225](#) [RTM-B2210](#) [RTM-B243](#) [RTM-B2410](#) [R&S FPL1003-P4](#) [R&S® FPH-B8](#)
[NGE103B](#) [NGL-K103](#) [FPC-COM1](#) [RTB2K-202](#) [RTB2K-74](#) [RTC1K-COM2](#) [HMC8042](#) [HZ22](#) [RTB2K-104](#) [HM8118.02](#) [HA-Z302](#)
[RTB2002 + RTB-B221 \(RTB2K-102\)](#) [RTB-PK1](#) [RTM-K1](#) [RTM-B242](#) [R&S HMP4030](#) [R&S NRX](#) [R&S RTM-K36](#) [HMC8012](#) [HZ42](#) [RTM-](#)
[K3](#) [RTM-K15](#) [RTM-K18](#) [R&S HM7042-5](#) [RTB2004 \(RTB2K-74\)](#) [RTM3K-COM4](#) [RTM-K2](#) [RTM-K5](#) [RTM-K6](#) [RTM-K7](#)