
Pushbutton, Single Pole

FL SR



NTE			Actuator		Diag	
Type No.	No. Circuitry Action		ion	Material	Color	No.
54-380	SPDT	ON	ON	Polyamide	Black	S66

S66



Specifications


Current Rating: 3A 125VAC Insulation Resistance: 100 Megohms (min.) Dielectric Strength: 1000V RMS (min.) Temperature Rating: $+14^{\circ}F$ to $+131^{\circ}F$ ($-10^{\circ}C$ to $+55^{\circ}C$) Electrical Life: 10,000 cycles Mechanical Life: 30,000 cycles Terminal Type: Solder Lug Mounting Hole: .244 (6.2)

Pushbutton, Single Pole



	NTE Type No. Circuitry		Action		Actuator		Diag
					Material	Color	No.
	54-385	SPST	OFF	(ON)	Molded ABS Resin	Red	S67
NEW	54-385A	SPST	OFF	ON	Molded ABS Resin	Red	S67

SPECIAL NOTE: () = Momentary Function



Specifications

Current Rating: 3A 125VAC Insulation Resistance: 100 Megohms (min.) at 500VDC Dielectric Strength: 1000V RMS (min.) Temperature Rating: +14°F to +131°F (-10°C to +55°C) Electrical Life: 5,000 cycles Mechanical Life: 30,000 cycles Terminal Type: Solder Lug Mounting Hole: .700 (17.8)

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for nte manufacturer:

Other Similar products are found below :

 747
 797
 868
 NEH680M50FE
 NEHH1.0M450CB
 NTE48
 NTE526A
 228A
 231
 954
 2023
 510
 R04-11A30-120
 04-SLPE3750A
 5615
 591

 7056
 7448
 NEH.10M50AA
 NEH2.2M63AA
 NEH330M35DD
 NEH33M10AA
 NEV.22M100AA
 NTE528
 NTE542
 NTE74154
 04

 SCBW25L-BK
 04-SCBW32L-BK
 04-SCW10C-BK
 04-SCBW19L-GR
 04-SCW19L-WH
 04-SCW19L-OR
 04-SCW38L-WH
 04-SCBW50L

 OR
 04-SCBW50L-GR
 04-SCW10C-GR
 04-SCW10C-OR
 04-SCBW32L-GR
 04-SCBW32L-WH
 04-SCBW32L-OR
 04-SCBW6C-WH
 04

 SCBW6C-GR
 04-SCBW6C-OR
 04-SCBW25L-GR
 04-SCBW25L-WH
 04-ESNF-500L
 04-SCW5C-WH
 04-ESNF-1000L

 04-SL1.00-O
 04-SCBW6C-OR
 04-SCBW25L-GR
 04-SCBW25L-WH
 04-ESNF-500L
 04-SCW5C-WH
 04-ESNF-1000L