

CXP, 150Gb/s Active Optical Cable

DESCRIPTION

The 150Gb/s CXP - CXP Active Optical Cable (AOC) is a natural building block in the range of CXP cable assemblies. It provides a cost effective, high performance, plug and play solution.

Form factor CXP delivers the highest hardware faceplace port density.

The AOC features optical engines inside both cable connectors improving speed and distance versus traditional copper assemblies.

The assembly is a full duplex, 12 channel construction whereby each channel is capable of transmitting data at rates up to 12.5Gb/s

Typical applications are serving transmission distances between 5 and 100m



FEATURES & BENEFITS

Cost effective

- Simplified designs
- Limited number of discrete components in the link
- Elimination of on-site cleaning

Ease of installation

- Plug and Play
- No dust contamination
- Closed optical system providing 100% eye-safety

Interoperability

- SFF- 8642 compliant
- Supports Infiniband SDR, DDR and QDR data rates
- Same brand transceiver on each end

Reliability

- 100% final tested
- Assembled under clean room environment
- Optimum Signal Integrity

TARGET MARKETS / APPLICATIONS

- Data Center
- High Performance Computing
- Switching
- Industrial

XLERATETM-12X

FCi

TECHNICAL INFORMATION

MATERIALS

- ► Fiber cable:
 - Multi-mode
 - OFNP
- Mates with:
 - 84 pos CXP board connector

ELECTRICAL PERFORMANCE

- ▶ Power supply voltage: 3.3V
- ► Data rate per lane: 12.5 Gbps
- ► Power consumption: 2.1 W (typ.)
- Transmitter type: VCSEL
- Receiver type: PIN-diode

PACKAGING

- ▶ Blister reel up to 30 meter length
- ▶ Box beyond 30 meter length

ENVIRONMENTAL

- RoHS 6/6 compliant
- ► Laser Class 1 / CDRH
- Case temperature 0 70 degrees C
- ► Halogene free (optional)


SPECIFICATIONS

- Module meets MSA Small Form Factor SFF-8642
- Cable assembly supports Infiniband SDR, DDR and QDR
- ▶ Product Specification: GS-12-1073

APPROVALS AND CERTIFICATIONS

TUV : DE2-015589
UL : E251142-A2


► FDA : 0820640-xxx rev 004



PART NUMBERS

ICD150GVP2410-XX	Straight exit boot 90 degree exit boot	
ICD150GVP2430-XX		

Suffix XX	Cable Length (m)	Category	Colour
01	1	OM2	Orange
03	3	OM2	Orange
05	5	OM2	Orange
10	10	OM2	Orange
15	15	OM2	Orange
20	20	OM2	Orange
30	30	ОМ3	Aqua
50	50	ОМ3	Aqua
C0	100	ОМ3	Aqua



ELXCXP1500612EA4



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for D-Sub Micro-D Connectors category:

Click to view products by Amphenol manufacturer:

Other Similar products are found below:

M243082311F M2430834F M24308/4-6F 65-1920-15 M83513/01-HN M83513/03-A10N M83513/03-B14C M83513/03-D09C M83513/03-D11N M83513/03-G02N M83513/03-G05N M83513/03-G08C M83513/03-G09N M83513/03-G12N M83513/03-H13N M83513/04-E15N M83513/04-G04C M83513/10-E01NP M83513/13-B01NP M83513/13-C01NN M83513/16-A01CP M83513/22-D01NP M83513/25-B01NP 6R2004A30F015 6R4006A28A120 703006A13F060 704002A03F200 705001A13F120 7-1532020-5 748567-1-P MDB1-31SH003 MDM-15PBS-L58 MDM-15PCBRM7T MDM-15PH003B-A174 75-068624-59S MDM-15PH034B MDM-15SH001L MDM-15SH004B MDM-21PH003K MDM-25PH003B-A174 MDM-25PHW01F-A174 MDM-37PH006L-A174 MDM-37PH048M5-A174 MDM-37SCBRP-A174 MDM-51PBS-L56 MDM-51PSF MDM-51SH003M7 MDM-51SSM7-A174 MDM-9PBSP-L58 MDM-9PH003M7