



LM808 WiFi 433 Mbps USB Adapter 802.11 ac

1T1R 802.11 a/b/g/n/h/i/e/ac WLAN

Product LM808
 Part No 808-0402
 Revised 19/12/2014



Features

- Supports All IEEE Standards
IEEE 802.11ac/a/b/g/n/d/e/h/i
- Backward compatible with 802.11a/b/g devices while operating over 802.11n
- Maximum Data Rates at
72.2 Mbps Using 20MHz bandwidth
150 Mbps Using 40MHz bandwidth
433.3Mbps Using 80MHz bandwidth
- Operates over ISM bands (2.4GHz and 5GHz)
20MHz / 40MHz / 80MHz Bandwidth Transmission
- Modulation
OFDM with BPSK, QPSK, 16QAM, 64QAM and 256QAM
Convolutional Coding Rate: 1/2, 2/3, 3/4, and 5/6
- WiFi Direct and support for WiFi P2P PAN network



Overview

The LM808 WLAN USB Adapter uses a USB 2.0 interface in order to communicate with the host. It uses a Realtek IC that fully supports all of the 808.11 Bands, IEEE 802.11 ac Draft 2.0 and 802.11 a/b/g/n specifications, plus is backward compatible while using 802.11n standard.

The LM808 Series Adapter is for users requiring a high-performance wireless client. Also supporting the WiFi Direct feature that can easily build a WiFi P2P PAN network.

The LM808 supports the Orthogonal Frequency Division Multiplexing (OFDM) with one transmits and one receive paths (1T1R).

Features include support for both 20MHz, 40MHz and 80MHz channel bandwidth, and combined with BPSK, QPSK, 16QAM, 64QAM and 256QAM modulation of the individual subcarriers and offers a compatible coding rate of 1/2, 2/3, 3/4, and 5/6, and provides up to 433.3 Mbps over IEEE 802.11ac while using 80MHz bandwidth.



LM808 WiFi 433 Mbps USB Adapter 802.11 ac

1T1R 802.11 a/b/g/n/h/i/e/ac WLAN

Product	LM808
Part No	808-0402
Revised	19/12/2014

Packaging Options

SRP - Single Retail Pack
Part No 808-0403

AO - Adapter Only
Part No 808-0402

1 x WiFi USB Adapter.

1 x WiFi USB Adapter.

- User Guides, Manuals and Widcomm Configuration Software available to download via our website - <http://www.lm-technologies.com/support/downloads>

General Specification

Product Name	LM808
Chipset	Realtek RTL8811AU
No. of Transmitters	1T 1R
Standard	IEEE 802.11ac/a/b/g/n/d/e/h/i
Data Transfer Rate	1, 2, 5.5, 11, 6, 9, 12, 18, 24, 36, 48, 54, 60, 90, 120, 150, 173.3, 180, 240, 270, 300, and maximum of 433.3Mbps
Modulation Method	CCK, DQPSK, DBPSK, BPSK, QPSK, 16QAM, 64QAM, 256QAM
Frequency Band	2.4 GHz and 5 GHz ISM Band
RF Output Power (tolerance ± 2 dBm)	17dBm – 802.11b@11Mbps 15dBm – 802.11g@54Mbps 13dBm – 802.11a@54Mbps 13dBm – 802.11n@MCS7_HT20 13dBm – 802.11n@MCS7_HT40 11dBm – 802.11ac@NSS1 MCS9_BW20, BW40, BW80 -82dBm – 802.11b@11Mbps -71dBm – 802.11g@54Mbps
Receiver Sensitivity	-67dBm – 802.11n@MCS7_BW20 -64dBm – 802.11n@MCS7_BW40 -57dBm – 802.11ac@NSS1_MCS9_BW20 -54dBm – 802.11ac@NSS1_MCS9_BW40 -51dBm – 802.11ac@NSS1_MCS9_BW80
Operating Temperature	-10 – 70° C ambient temperature 5 to 90 % (non-condensing)
Storage Temperature	-40 ~ 80°C ambient temperature 5 to 95 % (non-condensing)
Dimension	29.5mm x 15.0mm x 8.0 mm (LxWxH) USB Type A Connector + Housing





LM808 WiFi 433 Mbps USB Adapter 802.11ac

1T1R 802.11 a/b/g/n/h/i/e/ac WLAN

Product LM808
Part No 808-0402
Revised 19/12/2014

Dimensions



Revision History

1.0	19/DEC/2014	Updated Datasheet
-----	-------------	-------------------

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [lm technologies](#) manufacturer:

Other Similar products are found below :

[LM506](#) [LM930-0635](#) [LM931-0552](#) [LM254](#) [530-0653](#) [530-0654](#) [LM817-0655](#) [LM780](#) [LM252](#) [LM910-0630](#) [LM253](#) [LM251](#) [LM822-1459](#)