Product data sheet Characteristics

HU361 SWITCH NOT FUSIBLE HD 600V 30A 3P NEMA1



n	·Λ	а	ı	n

Commercial Status	Commercialised
Product or component	Single Throw Safety Switch
type	
[In] rated current	30 A
Product certifications	UL listed
NEMA degree of protection	NEMA 1 steel
<u>-</u>	
Device composition	None
Disconnector device	Non-fusible disconnect
type	
Short-circuit current	200 kA maximum
Device mounting	Surface
Number of poles	3
Electrical connection	Lugs
Series name	Heavy duty
[Ue] rated operational voltage	600 V AC/DC
AWG gauge	146 AWG copper
33-	126 AWG aluminium
	* * *

Ordering and shipping details

Category	00008 - H&HU, 2&3P, N1, 30-200A	
Discount Schedule	DE1	
GTIN	00785901505723	
Nbr. of units in pkg.	1	
Package weight(Lbs)	7.64	
Product availability	Stock - Normally stocked in distribution facility	
Returnability	Υ	
Country of origin	US	

Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS	Will be Compliant on 3Q2014
REACh	Reference not containing SVHC above the threshold

Contractual warranty

Period	18 months

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for schneider manufacturer:

Other Similar products are found below:

LU9M1 7D 7S 7XA1 FNQR2 8501RS44V24 8501RSD14P14V51 8501XO20V03Y414 9001KXRK 9001SKR9P35RH25 9001SKT35L31 9003K2C003GA 9007AA1 9007BA1 9007C54D 9007C62A2 9007CA11 9007FA3 9007HA4 9007HA6 9007KA1 9007KB11 9007MS01S0206 9007MS02S0300 9012GAR4 9012GAW2 9012GBW1 9012GDW5E3 9012GFW1 9012GNG1 9012GNG3 9012GNG6 9013FHG39J69 9013GHG2J30 9050JCK2F30V14 GV2ME32 GVAN20 GZ1E02 A9F04102 A9F04106 A9F05110 A9F07102 ABL8RPS24030 DL1BLB ATS01N206QN RSL1PRJU 9001KA35 9001KA3G 9001KA4 9001KR1GH5