Detailed Specifications & Technical Data

ENGLISH MEASUREMENT VERSION



34410 Hook-up/Lead - UL AWM Style 3191

For more Information please call

1-800-Belden1



General Description:

CSPE - Chlorosulphonated Polyethylene insulation has excellent heat resistance, color stability and electrical properties and is recommended for Class 130(B) insulation systems.

Physical Characteristics (Overall)

Conductor

AWG:

# Conductors	AWG	Stranding	Conductor Material
1	10	65x28	TC - Tinned Copper

Total Number of Conductors:

Insulation

Insulation Material:

Insulation Material	Wall Thickness (in.)
CSPE - Chlorosulphonated Polyethylene	0.045

Overall Insulation

Overall Cable

Overall Nominal Diameter: 0.209 in.

Applicable Specifications and Agency Compliance (Overall)

Applicable Standards & Environmental Programs

UL AWM Style:	3191	
UL Rating:	600 V, 105°C	
CSA Rating:	300 V RMS, 105°C	
CSA Type:	CL1052	
EU Directive 2011/65/EU (ROHS II):	Yes	
EU Directive 2000/53/EC (ELV):	Yes	
EU Directive 2002/95/EC (RoHS):	Yes	
EU RoHS Compliance Date (mm/dd/yyyy):	01/01/2004	
EU Directive 2002/96/EC (WEEE):	Yes	
EU Directive 2003/11/EC (BFR):	Yes	
CA Prop 65 (CJ for Wire & Cable):	Yes	
MII Order #39 (China RoHS):	Yes	
Plenum/Non-Plenum		

Plenum (Y/N): No

Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
34410 0082000	2,000 FT	104.000 LB	GRAY	F	#10 STR CSPE 105C 600V
34410 010100	100 FT	5.500 LB	BLACK		#10 STR CSPE 105C 600V
34410 0102000	2,000 FT	104.000 LB	BLACK	С	#10 STR CSPE 105C 600V
34410 010500	500 FT	25.500 LB	BLACK	CF	#10 STR CSPE 105C 600V

F = MAY CONTAIN MORE THAN 1 PIECE. MINIMUM LENGTH OF ANY ONE PIECE IS 50'

Page 1 of 2

Detailed Specifications & Technical Data

ENGLISH MEASUREMENT VERSION



34410 Hook-up/Lead - UL AWM Style 3191

Revision Number: 1 Revision Date: 01-07-2011

© 2016 Belden, Inc All Rights Reserved

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability. Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Page 2 of 2

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Hook-up Wire category:

Click to view products by Belden manufacturer:

Other Similar products are found below:

002333-000 M81044/12-22-6 M81044/9-8-9 743094-001 81044/12-18-9CS3209 ATFC0311-20-5D EF5675-000 BFWUL3239-24-PINK
22759/34-16-9CS2621 22759/42-24-9CS2620 933205-000 30802-009-250 99M0111-20-2 A00594-000 190571-000 22759/41-12-9CS2620
22759/41-16-9CS2620 22759/43-10-9CS2873 CM9524-000 31510-010-250 34401-010-250 34402-010-500 M81044/9-4-9 391441-BK007
400R0111-10-9 431660-000 ATFC0311-20-0 44/7024-26-9-9 44A0112-22-9CS3184 BFW-UL3239-24-WHITE 55/0312-26-6L-CS2570
55A0811-12-9 55A6087-20-9-9-9 55A7400-22-9/96-9CS2275 55A9002-30-5 55PC0211-20-5CS2502 55PC0811-6-9CS2637 55PC1211-22-9-9CS3278 C07683-000 34020-008-2000 391850-BK199 392075-RD199 W28-6HU 437545-000 44A0112-24-9CS3184 44A0211-16-8-1KF/1 44A0211-16-9CS3030 084299-000 100E0111-0.50-9 100E0111-0.75-9