



CC4V-T1A

Tuning Fork Crystal 30 kHz – 1.0 MHz




100% leadfree, RoHS - compliant


Miniature SMT ceramic package
Package height 0.90 mm
SMD-package in Tape and Reel
Ind. and Ext. temperature ranges
AEC-Q200 automotive compliant
High stability, low aging
Low power consumption
High shock and vibration resistance

DIMENSIONS

Package:



Recommended Solder Pad:



All dimensions in mm typical

DESCRIPTION:

This SMD ceramic package has been specially designed for miniature industrial and telecom applications. This part is available for extended operating temperature range and is compliant with the AEC-Q200 quality standards for automotive applications.

The crystals are supplied in special trays (100 crystals per tray). For pick-and-place equipment, the parts are available in 12 mm tape:
 7" (178 mm) reel with 2'000 crystals
 13" (330 mm) reel with 10'000 crystals

ELECTRICAL CHARACTERISTICS AT 25°C:

Frequency Range	F _L	30–200	201–560	1'000	kHz
Load capacitance ¹⁾	C _L	7.0 9.0 12.5	4.0	10.0	pF
Frequency tolerance ²⁾	ΔF/F	+/-20	+/-100	+/-100	ppm
	ΔF/F	+/-100	+/-250	+/-500	ppm
Drive level max.	P	1.0			μW
Insulation resistance min.	R _i	500			MΩ
Aging first year max.	ΔF/F	+/-3			ppm

Frequency Example ³⁾	F _L	32.768	240.000	1'000	kHz
Series resistance typ./max.	R _S	50 / 65	2.6 / 4.5	0.5 / 1.2	kΩ
Motional capacitance typ.	C ₁	2.1	1.8	1.1	fF
Static capacitance typ.	C ₀	1.2	1.3	1.0	pF
Turnover temperature	T ₀	25 +/-5	30 +/-5	39 +/-5	°C
Frequency vs. temperature	ΔF/F ₀	-0.035 ppm/°C ² (+/-10%)			ppm

1) Other load capacitances on request.

2) Tighter and wider frequency tolerances on request.

3) Values for other frequencies consult factory.

STANDARD FREQUENCIES:

Frequency kHz					Frequency MHz
32.768	36.409	38.400	40.000	76.800	1.000
100.000	128.000	153.600	200.000	240.000	
Other frequencies between 30 kHz and 1.008 MHz on request					

ENVIRONMENTAL CHARACTERISTICS:

		Conditions	Max. Dev.
Storage temp. range		–55 to +125°C	
TA Operating temperature range		–40 to +85°C	
TB Extended oper. temp. range		–40 to +125°C	
TC Extended oper. temp. range		–55 to +125°C	
Shock resistance	$\Delta F/F$	5000 g, 0.3 ms, $\frac{1}{2}$ sine	+/- 5 ppm
Vibration resistance	$\Delta F/F$	20 g / 10–2000 Hz	+/- 5 ppm

TERMINATIONS AND PROCESSING:

Type	Termination	Processing
CC4V-T1A	For SMD mounting Au plated pads	Reflow soldering 260°C / 20 s max.

PRODUCT DESCRIPTION AND ORDERING INFORMATION:

CC4V-T1A	<u>32.768kHz</u>	<u>12.5pF</u>	<u>+/-20ppm</u>	<u>TA</u>	<u>QC</u>
<u>Frequency F_L</u>					
<u>C_L Load Capacitance</u>					
7.0 pF					
9.0 pF					
12.5 pF					
<u>Frequency tolerance</u>					
+/- 20 ppm					
+/- 100 ppm					
				<u>Temperature Range</u>	
				TA = -40 to 85°C (Standard)	
				TB = -40 to +125°C	
				TC = -55 to +125°C	
Optional: if not defined, 'Standard' will apply				<u>Qualification</u>	
				QC = Commercial (Standard)	
				QA = Automotive AEC-Q200	
				QM = Medical	
A unique part number will be generated for each product specification, i.e: 20xxxx-MG02 20xxxx-PG10 Please contact us.					
				2'000 pcs (in 12mm tape on 7" reel)	
				10'000 pcs (in 12mm tape on 13" reel)	

All specifications subject to change without notice.



A COMPANY OF THE SWATCH GROUP

Micro Crystal AG
Mühlestrasse 14
CH-2540 Grenchen
Switzerland

Tel. +41 32 655 82 82
Fax +41 32 655 82 83
sales@microcrystal.com
www.microcrystal.com

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for micro crystal manufacturer:

Other Similar products are found below :

[RV-8523-C3-EVALUATION-BOARD](#) [RV-3028-C7 ON BOARD 32.768kHz TA QC](#) [RV-3049-C2-EVALUATION-BOARD-OPTION-B](#) [RV-3029-C2-EVALUATION-BOARD-OPTION-B](#) [RV-8803-C7-EVALUATION-BOARD](#) [OV-7604-C7-EVALUATION-BOARD](#) [RV-8263-C7-EVALUATION-BOARD](#) [CM7V-T1A-32.768kHz-9pF-20PPM-TC-QC](#) [RV-2251-C3-EVALUATION-BOARD](#) [RV-3029-C3-32.768k-OPTION-B-TB-QA](#) [RV-3029-C3-TB-QA-OPT.B](#) [CC4V-T1A-32.768kHz-9pF-20PPM-TA-QC](#) [RV-2123-C2-TA-QC-020](#) [CC4V-T1A 32.768KHZ +-20PPM 9PF](#) [MS1V-T1K-32.768kHz-7pF-20PPM-TA-QC-Au](#) [CC7V-T1A-32.768k-12.5pF-20PPM-TA-QA](#) [CC4V-T1A 32.768KHZ 12.5PF +-20PPM](#) [CM7V-T1A-32.768k-6pF-20PPM-TB-QA](#) [RV-3029-C2-TB-QA-OPT.A](#) [OM-0100-C8-100.00kHz-20PPM-TA-QC](#) [CM7V-T1A-32.768k-9pF-20PPM-TA-QA](#) [RV-8803-C7-32.768k-3PPM-TA-QA](#) [CM8V-T1A-32.768kHz-7pF-20PPM-TB-QC](#) [RV-3049-C3-TB-QA-OPT.A](#) [CC5V-T1A 32.768KHZ +-20PPM 9PF](#) [RV-8564-C3-TA-QC-020](#) [MS1V-T1K 32.768KHZ +-20PPM 10PF](#) [CM7V-T1A-32.768kHz-12.5pF-100PPM-TC-QC](#) [RV-3029-C3-32.768k-OPTION-A-TB-QA](#) [CC7V-T1A-32.768k-9pF-20PPM-TC-QA](#) [CM7V-T1A-32.768k-9pF-20PPM-TC-QA](#) [CC7V-T1A-32.768kHz-7pF-20PPM-TB-QC](#) [CM7V-T1A-100.000kHz-9pF-100PPM-TA-QC](#) [RV-4162-C7-TA-QC-020](#) [CC7V-T1A-32.768k-9pF-20PPM-TA-QA](#) [RV-3029-C2-32.768k-OPTION-A-TB-QA](#) [RV-3049-C3-32.768kHz-OPTION-B-TA-QC](#) [RV-8564-C2-32.768kHz-20PPM-TA-QC](#) [CC7V-T1A-32.768kHz-7pF-10PPM-TA-QC](#) [CM7V-T1A-32.768k-9pF-20PPM-TB-QA](#) [OM-7605-C8-20PPM-TA-QA](#) [CC7V-T1A-32.768k-12.5pF-20PPM-TB-QA](#) [CC7V-T1A-32.768kHz-12.5pF-10PPM-TA-QC](#) [OV-7604-C7](#) [RV-3149-C3-32.768kHz OPTION B TA QC](#) [RV-3049-C3-32.768k-OPTION-B-TB-QA](#) [CC4V-T1A-32.768kHz-7pF-20PPM-TA-QC](#) [CM9V-T1A-32.768kHz-7pF-100PPM-TA-QC](#) [CM7V-T1A-32.768k-7pF-100PPM-TB-QA](#) [CM7V-T1A-0.3-32.768kHz-9pF-20PPM-TA-QC](#)