

## This document was generated on 10/20/2015 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:	<u>1300990106</u>		
Status:	Active		
Overview:	Strain-Relief Cord Grips		
Description:		rd-Sealing Grip, 3/4" NPT, 90° Angle Male, Cable Diameter	
	15.88-19.05mm (.625750")	, Stainless Steel Mesh	
Documents:			
Drawing (PDF)	Compliance (DDE)	Product Literature (PDF)	
RoHS Certificate of	<u>Compliance (PDF)</u>		
Agency Certificatio	n		Series image - Reference only
CSA		LR32159	
00/1			EU ELV
General			Not Reviewed
Product Family		Cable Grips	EU RoHS China RoHS
Series		<u>130099</u>	Not Reviewed
Eye Type NEMA Rating		N/A NEMA 3R	REACH SVHC
O-Ring		No	Not Reviewed
Overview		Strain-Relief Cord Grips	Halogen-Free
Product Literature O	rder No	987650-8064	Status
Product Name		MAX-LOC®	Not Reviewed
Туре		Strain Relief Grip	Need more information on product
UPC		78678855434	environmental compliance?
Use With		3/4" NPT MAX-LOC® Lock Nut <u>130099-0144</u> , 3/4" NPT	Email productcompliance@molex.com
		MAX-LOC® Gasket Sealing Ring <u>130099-0150</u> , 3/4" NPT MAX-LOC® O-Rin <u>g 130180-0333</u>	Please visit the Contact Us section for any
Woodhead		Yes	non-product compliance questions.
			China ROHS Not Reviewed
Physical			ELV Not Reviewed
Approximate Break	Strength	317.51kg (700 lbs) N/A	
Body Style		90° Angle	
Cable Diameter		15.88-19.05mm (.625750")	Search Parts in this Series
Color - Grommet		Orange	<u>130099</u> Series
Gender		Male	
Material - Body		Nylon	
Material - Grip		Stainless Steel	
Mesh Length Number of Holes		0.229m (9.00")	
Thread Size		3/4" NPT	
Material Info			
Old Part Number		5543M	
Reference - Drawin	a Numbers		
Sales Drawing		SD-130099-004	

This document was generated on 10/20/2015

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Cable Glands, Strain Reliefs & Cord Grips category:

Click to view products by Molex manufacturer:

Other Similar products are found below :

120-116-1-1-20BP
120-116-1-1-32BE
120-117-40
120-123-14
120-125-16
120-125-16R
120-125-16Y
120-125-24Y
120-125-24Y

28
120-125-28R
120-125-32
120-125-32R
120-125-40
120-125-56
120-126-16
120-126-20
120-126-20BL
120-126-20R
120-