

D369-P33-NS1 Product Details

[Share](#) [Print](#) [Email](#)



D369-P33-NS1

TE Internal Number: D369-P33-NS1

Active

[View 3D PDF](#)

369 Series Connectors

Always EU RoHS/ELV Compliant (Statement of Compliance)

Product Highlights:

- Wire-to-Wire
- Applies To Wire/Cable
- Connection Type = Connector Assembly
- Connector Style = Plug
- For Use With Shell Size 3

[View all Features](#)

Quick Links

- ▶ Pricing & Availability
- ▶ Search for Tooling
- ▶ Product Feature Selector
- ▶ Contact Us About This Product

[Add to My Part List](#) [Request Sample](#) [Find Similar Products](#) [Buy Product](#)

Documentation & Additional Information

Product Drawings:

- None Available

Catalog Pages/Data Sheets:

- None Available

Product Specifications:

- None Available

Application Specifications:

- None Available

Instruction Sheets:

- None Available

CAD Files: (CAD Format & Compression Information)

- 2D Drawing (DXF, Version 3)
- 3D Model (IGES, Version 3)
- 3D Model (STEP, Version 3)

Related Products:

- Tooling

[List all Documents](#)

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- Key Type = Keyway Polarization N
- Sealed = Yes
- Wire/Cable Type = Discrete Wire
- Termination Method to Wire/Cable = Crimp
- Strain Relief = Without
- Shell Size = 3

Mechanical Attachment:

- Mating Retention Type = Button Latch

Electrical Characteristics:

- Operating Voltage Reference = At Sea Level
- Voltage (V rms) = 1300
- Shielded = No

Termination Features:

- Connection Type = Connector Assembly
- Seal Type = Interface and Wire Seals

Dimensions:

- Contact Qty Size 22D = 3

Body Features:

- Mating Retention = With
- Fluid Type = EN2591-317

Contact Features:

- Contact Type = Socket

Housing Features:

- Connector Style = Plug
- Housing Color = Black
- Mating Alignment Type = Keyed

Configuration Features:

- Number of Positions = 3

Industry Standards:

- RoHS/ELV Compliance = RoHS compliant, ELV compliant
- RoHS/ELV Compliance History = Always was RoHS compliant

Environmental:

- Operating Temperature (°C [°F]) = -55 - +175 [-67 - +347]
- Fluid Resistance = Moisture/Spray

Conditions for Usage:

- Applies To = Wire/Cable
- For Use With = Shell Size 3

Operation/Application:

- Application Use = Wire-to-Wire
- Contact Transmits (Typical Application) = Signal

Other:

- Brand = DEUTSCH

Corporate Information

- [About TE](#)
- [Investors](#)
- [News Room](#)
- [Supplier Portal](#)
- [Careers](#)
- [Terms & Conditions](#)
- [Privacy Policy](#)

Quick Links

- [Distributor Inventory](#)
- [Product Cross Reference](#)
- [Documents & Drawings](#)
- [Product Compliance Support Center](#)
- [Site Map](#)

Customer Support

- [Email or Chat With Us](#)
- [Find a Phone Number](#)
- [Knowledge Base](#)
- [Manage Your Account](#)

Keep Me Informed

Receive TE News, Events & Technology Updates

Enter your email address



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Rack & Panel Connectors](#) category:

Click to view products by [TE Connectivity](#) manufacturer:

Other Similar products are found below :

[00170420102](#) [00171420202](#) [00171440002](#) [008026165000265](#) [00-8219-072-000-112P44](#) [008219072000112P5](#) [008219072000112P61](#) [00-8223-096-580-102](#) [02-014-013-5200-000](#) [00-8129-015-610-108](#) [613467-000](#) [CTJ112E01E-513](#) [CTJ116E03A-513](#) [M81714/63-22S L/C](#) [M81714/65-12-1](#) [66020-2](#) [CW8958-000](#) [699886-000](#) [D250-50632](#) [70.400.3240.0](#) [70.955.2453.3](#) [733753-000](#) [F22831-000](#) [780-522-DPX34RG8-02](#) [MMA25-0051R1](#) [MMA25-0341D1](#) [8660-501](#) [87.060.0053.0](#) [900709N001](#) [QRP4-12P-C\(01\)](#) [QR/P6-6S-C\(01\)](#) [AC-600003-004](#) [1218600-1](#) [D-659-0061](#) [DMC-MD 24 C-T](#) [1-445717-6](#) [1484398-2](#) [1484399-2](#) [1484469-2](#) [MR-34MG](#) [1484225-1](#) [1484398-1](#) [1484510-4](#) [1604997-2](#) [1663130-1](#) [1663767-7](#) [1663767-8](#) [MTC100-BF1-P31CS015](#) [MTC100-KT2-0083](#) [MTC100-KT2-0123-003](#)