

Data Sheet

Type Number: 55707

Sytem: Nickel Metal Hydride/

KOH Electrolyte

MH 13654 (N)

0

Nominal Voltage [V]: 1.2
Nominal Capacity C [mAh]: 65
Typical Capacity C [mAh]: 70

at 13 mA / 1.00 V

Weight, approx. [g]

 Dimensions [mm]:
 min.
 max.

 Diameter [d]:
 15.4
 15.5

 Height [h]:
 5.8
 6

Coding: Manufacturing 5 digit code

(123 = day/4 = year/5 = version)

80

 Temperature Ranges [°C]
 min.
 max.

 Storage: less than 30 days
 -40
 80

 less than 90 days
 -40
 65

 less than 1 year
 -40
 50

 Discharge:
 -20
 80

Charging Method:

Charge:

UL Recognition:

Normal Charging: $6.5\,$ mA for $14-16\,$ h Accelerated Charging (20°C): $13\,$ mA for 7 h Fast Charging: $32.5\,$ mA for $3\,$ h *

Time controlled, voltage control recommended **Trickle Charging:**1.95 mA

Overcharge (20°C): 6.5 mA continuous

13 mA up to 1 year

Charge Retention [%] at 20°C: 90

Capacity available after 1 month Storage at 20°C

Internal Resistance [Ohm]: 1.25

at charged cells, 20°C, DC: 0.2 CA/2 CA, (IEC 61951-2)

Impedance [Ohm]: 0.22

at charged cells, 20°C, AC: 1kHz, (IEC 61951-2)

Typical Capacities [mAh]:

at 65 mA / 0.90 V 50

Max. Discharge Current (cont.) [mA]: 130

Life Expectancy (typical):

IEC Cycle: 1000 Cycles

Trickle Charge: up to 6 years (20°C)

Trickle Charge: up to 3 years (45°C)

Capacities based on normal charging

 $^{^{\}ast}$ for fully discharged cells, 20 $^{\circ}\text{C}$

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for varta manufacturer:

Other Similar products are found below:

56456 702 099 18750 4114 210 501 4610 726 406 4122 210 511 LCD-CHARGER + 4XAA 2400MAH 449915B 4607 726 406
55171403014 55625603059 55615602940 4112101411 4 022 211 111 4 106 101 436 4 020 211 111 MINI CHARGER + 2XAA 2100MAH
MINI-CHARGER 17730 LCD-SMART-CHARGER 414086X POCKET-CHARGER + 4XAA 2100MAH 458980A LCD MULTI
CHARGER CG511-150-PB EE UNIVERSAL CHARGER CG401D-050-PB CG511-050-PB CU303-018-PB 413675G CG381D-G-100-PB
CU202-030-PB 55615603059 CG381D-G-150-PB CG481G-050-PB CU303-030-PB CG511D-030-PB CA317-PB CU201G-B-030-PB
095668F 4600 726 406 CA418-PB CG481G-030-PB CG511D-100-PB CG511-030-PB CG381D-G-050-PB CU302-030-PB CG341-030-PB CU201G-B-050-PB CA39-PB