
Comus Group of Companies

PRODUCT DATA SHEET



Drawings not to scale All dimensions in mm (inches) nominal

SPECIFICATION

Parameters	Туре		
Contact Form		С	
Contact Material		Rh	
Switching Capacity	Max. W/VA	3	
Switching Voltage	Max. Vac/dc	30	
Switching Current	Max. A	0.2	
Carry Current	Max. A	0.5	
Dielectric Strength	Min. Vdc	200	
Contact Resistance	Max. mΩ	100	
Insulation Resistance	Min. Ω	10 ⁹	
Pull-In Sensitivity	AT	15-30	
Drop-out Sensitivity	Min. AT	5	
Switching Time without Bounce	Max. ms	1.0	
Bounce Time	Max. ms	1.5	
Release Time	Max. ms	0.5	
Resonant Frequency	Тур. Hz	-	
Operating Frequency	Max. Hz	200	
Vibration	Hz	10-1000Hz/20g	
Shock (11ms)	g	50	
Capacitance	Тур. рҒ	1.5	
Operating Temperature Range		-40 +125	
Test Coil		0551	

REED SWITCHES - Dry Contact

Rev. No.	Revision Note	Date	Signature
A	Web Site 1999	1-12-99	RG

As part of the company policy of continued product improvement, specifications may change without notice. Our sales office will be pleased to help you with the latest information on this product range and details of our full design and manufacturing service. All products are supplied to our standard conditions of sale otherwise agreed in writing.

PART NUMBER ORD 0551

The Comus Group of Companies consist of:
Assemtech Europe Limited
E. Bachem GmbH
Comus International
W. Gunther GmbH
Gunther Belgium
Gunther France
S.T.G.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Magnetic/Reed Switches category:

Click to view products by Comus manufacturer:

Other Similar products are found below:

59200-020 MDSR-4-12-23 MMRB20006 PSW-21 AMS-17-B AMS-20MG AMS-37-G_W/Brk AMS-38S-I AMS-38SW AMS-39B-B AMS-39B-W HRB10030 2116900170 AMS-10S-B AMS-25B-B AMS-37BROWN AMS-37GRAY AMS-38MG AMS-38SB AMS-9-B AMS-T10C(B) 4350238 505-171W WHITE 505-211B 505-391G 505-5114W WHITE 505-70B 507-382B BMC-33B HM00-01800 4350186 4360013 505-101-GC 505-101-GS 505-101WC 505-172W 505-201W 505-392W 505-90G 505-90I 507-381BB RSW-21A-I ODC-56B FF6-21-DC-03-SS FF6-11-AC-06 FF6-21-AC-06 DRR-129(42-48) ODC-56A AMS-10MGW AMS-37B GRAY